



# PRODUCT INFORMATION SHEET

**MATERION**

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Name of the substance** Nickel Product  
**Identification number** 028-002-01-4 (Index number)  
**Registration number** -  
**Document number** 010  
**Synonyms** None.  
**Issue date** 26-May-2022  
**Version number** 01

### 1.3. Details of the supplier of the product information sheet

#### Supplier

**Company name** Materion Electronic Materials  
**Address** 6070 Parkland Boulevard  
Mayfield Heights, OH 44124  
United States  
**Division**  
**Telephone** 1.216.383.4019  
**e-mail** ehs@materion.com  
**Contact person** Theodore Knudson

**1.4. Emergency telephone number** See Section 16.

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Not available.  
**Uses advised against** None known.

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The substance has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

#### Classification according to Regulation (EC) No 1272/2008 as amended

##### Health hazards

Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.
Carcinogenicity	Category 2	H351 - Suspected of causing cancer.
Specific target organ toxicity - repeated exposure	Category 1 (Respiratory system)	H372 - Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.

**Hazard summary** Suspected of causing cancer. Prolonged exposure may cause chronic effects.

### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

**Contains:** NICKEL POWDER; [PARTICLE DIAMETER < 1MM]

#### Hazard pictograms



**Signal word** Danger

#### Hazard statements

H317 May cause an allergic skin reaction.  
H351 Suspected of causing cancer.  
H372 Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.

## Precautionary statements

### Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

### Response

P302 + P350	If on skin: Wash with plenty of water.
P304 + P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	If exposed or concerned: Get medical advice/attention.
P391	Collect spillage.

### Storage

P405	Store locked up.
------	------------------

### Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

### Supplemental label information

For further information, please contact the Product Stewardship Department at +1.216.383.4019.

### 2.3. Other hazards

This substance does not meet vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII.

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

#### General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
NICKEL POWDER; [PARTICLE DIAMETER < 1MM]	100	7440-02-0 231-111-4	-	028-002-01-4	
<b>Classification:</b> Carc. 2;H351, Aquatic Chronic 3;H412					7,S

#### List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

#### Composition comments

The full text for all H-statements is displayed in section 16.

## SECTION 4: First aid measures

#### General information

If you feel unwell, seek medical advice (show the label where possible).

#### 4.1. Description of first aid measures

##### Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

##### Skin contact

Wash off with soap and water. Get medical attention if irritation develops and persists.

##### Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

##### Ingestion

Rinse mouth. Get medical attention if symptoms occur.

#### 4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

#### 4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

## SECTION 5: Firefighting measures

#### General fire hazards

No unusual fire or explosion hazards noted.

#### 5.1. Extinguishing media

##### Suitable extinguishing media

Powder. Dry sand. Water Spray or Fog

##### Unsuitable extinguishing media

Carbon dioxide (CO<sub>2</sub>).

<b>5.2. Special hazards arising from the substance or mixture</b>	No unusual fire or explosion hazards noted.
<b>5.3. Advice for firefighters</b>	
<b>Special protective equipment for firefighters</b>	Wear suitable protective equipment.
<b>Special firefighting procedures</b>	Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.

## SECTION 6: Accidental release measures

<b>6.1. Personal precautions, protective equipment and emergency procedures</b>	
<b>For non-emergency personnel</b>	Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up. For personal protection, see section 8 of the PIS.
<b>For emergency responders</b>	Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the PIS.
<b>6.2. Environmental precautions</b>	Avoid discharge into drains, water courses or onto the ground.
<b>6.3. Methods and material for containment and cleaning up</b>	Stop the flow of material, if this is without risk. For waste disposal, see section 13 of the PIS.
<b>6.4. Reference to other sections</b>	For personal protection, see section 8 of the PIS. For waste disposal, see section 13 of the PIS.

## SECTION 7: Handling and storage

<b>7.1. Precautions for safe handling</b>	Do not handle until all safety precautions have been read and understood. Wear appropriate personal protective equipment. Wash hands thoroughly after handling.
<b>7.2. Conditions for safe storage, including any incompatibilities</b>	Store locked up. Store away from incompatible materials (see Section 10 of the PIS).
<b>7.3. Specific end use(s)</b>	Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Austria. TRK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Material	Type	Value	Form
Nickel Product	STEL	2 mg/m <sup>3</sup>	Inhalable dust.
	TWA	0,5 mg/m <sup>3</sup>	Inhalable dust.
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	STEL	2 mg/m <sup>3</sup>	Inhalable dust.
	TWA	0,5 mg/m <sup>3</sup>	Inhalable dust.

##### Belgium. Exposure Limit Values

Material	Type	Value
Nickel Product	TWA	1 mg/m <sup>3</sup>
<b>Components</b>	<b>Type</b>	<b>Value</b>
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m <sup>3</sup>

##### Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Material	Type	Value
Nickel Product	TWA	0,05 mg/m <sup>3</sup>
<b>Components</b>	<b>Type</b>	<b>Value</b>
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,05 mg/m <sup>3</sup>

**Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09**

<b>Material</b>	<b>Type</b>	<b>Value</b>
Nickel Product	MAC	0,5 mg/m3
<b>Components</b>	<b>Type</b>	<b>Value</b>
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	MAC	0,5 mg/m3

**Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.**

<b>Material</b>	<b>Type</b>	<b>Value</b>
Nickel Product	TWA	1 mg/m3
<b>Components</b>	<b>Type</b>	<b>Value</b>
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m3

**Czech Republic. OELs. Government Decree 361**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Nickel Product	Ceiling	1 mg/m3	Aerosol, inhalable.
	TWA	0,5 mg/m3	Aerosol, inhalable.
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	Ceiling	1 mg/m3	Aerosol, inhalable.
	TWA	0,5 mg/m3	Aerosol, inhalable.

**Denmark. Exposure Limit Values**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Nickel Product	TLV	0,05 mg/m3	Dust.
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TLV	0,05 mg/m3	Dust.

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended**

<b>Material</b>	<b>Type</b>	<b>Value</b>
Nickel Product	TWA	0,5 mg/m3
<b>Components</b>	<b>Type</b>	<b>Value</b>
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m3

**Finland. Workplace Exposure Limits**

<b>Material</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
Nickel Product	TWA	0,01 mg/m3	Respirable.
<b>Components</b>	<b>Type</b>	<b>Value</b>	<b>Form</b>
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,01 mg/m3	Respirable.

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

<b>Material</b>	<b>Type</b>	<b>Value</b>
Nickel Product	VME	1 mg/m3

**Regulatory status:** Indicative limit (VL)

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	VME	1 mg/m3
<b>Regulatory status:</b> Indicative limit (VL)		

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Material	Type	Value	Form
Nickel Product	AGW	0,03 mg/m3	Inhalable fraction.
		0,006 mg/m3	Respirable fraction.
Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	AGW	0,03 mg/m3	Inhalable fraction.
		0,006 mg/m3	Respirable fraction.

**Greece. OELs (Decree No. 90/1999, as amended)**

Material	Type	Value
Nickel Product	TWA	1 mg/m3
Components	Type	Value
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m3

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

Material	Type	Value
Nickel Product	Ceiling	0,1 mg/m3
Components	Type	Value
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	Ceiling	0,1 mg/m3

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Material	Type	Value	Form
Nickel Product	TWA	0,05 mg/m3	Dust.
Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,05 mg/m3	Dust.

**Ireland. Occupational Exposure Limits**

Material	Type	Value
Nickel Product	TWA	0,5 mg/m3
Components	Type	Value
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m3

**Italy. Occupational Exposure Limits**

Material	Type	Value	Form
Nickel Product	TWA	1,5 mg/m3	Inhalable fraction.
Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1,5 mg/m3	Inhalable fraction.

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

Material	Type	Value
Nickel Product	TWA	0,05 mg/m3

**Latvia. OELs. Occupational exposure limit values of chemical substances in work environment**

Components	Type	Value
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,05 mg/m3

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Material	Type	Value
Nickel Product	TWA	0,5 mg/m3
Components	Type	Value
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m3

**Norway. Administrative Norms for Contaminants in the Workplace**

Material	Type	Value
Nickel Product	TLV	0,05 mg/m3
Components	Type	Value
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TLV	0,05 mg/m3

**Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817**

Material	Type	Value
Nickel Product	TWA	0,25 mg/m3
Components	Type	Value
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,25 mg/m3

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

Material	Type	Value	Form
Nickel Product	TWA	1,5 mg/m3	Inhalable fraction.
Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1,5 mg/m3	Inhalable fraction.

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Material	Type	Value
Nickel Product	STEL	0,5 mg/m3
	TWA	0,1 mg/m3
Components	Type	Value
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	STEL	0,5 mg/m3
	TWA	0,1 mg/m3

**Slovakia. OELs for carcinogens and mutagens. Regulation No. 46/2002 on carcinogenic and mutagenic substances**

Material	Type	Value	Form
Nickel Product	TWA	0,05 mg/m3	Inhalable fraction.
Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,05 mg/m3	Inhalable fraction.

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Material	Type	Value	Form
Nickel Product	TWA	0,006 mg/m3	Respirable fraction.

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,006 mg/m3	Respirable fraction.

**Spain. Occupational Exposure Limits**

Material	Type	Value
Nickel Product	TWA	1 mg/m3

Components	Type	Value
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m3

**Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)**

Material	Type	Value	Form
Nickel Product	TWA	0,5 mg/m3	Total dust.

Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m3	Total dust.

**Switzerland. SUVA Grenzwerte am Arbeitsplatz**

Material	Type	Value	Form
Nickel Product	TWA	0,5 mg/m3	Inhalable fraction.

Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m3	Inhalable fraction.

**UK. EH40 Workplace Exposure Limits (WELs)**

Material	Type	Value
Nickel Product	TWA	0,5 mg/m3

Components	Type	Value
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m3

**Biological limit values**

**Czech Republic. Limit Values for Indicators of Biological Exposure Tests in Urine and Blood, Annex 2, Tables 1 and 2, Government Decree 432/2003 Sb.**

Material	Value	Determinant	Specimen	Sampling Time
Nickel Product	0,077 µmol/mmol	Nickel	Creatinine in urine	*
	0,04 mg/g	Nickel	Creatinine in urine	*

Components	Value	Determinant	Specimen	Sampling Time
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	0,077 µmol/mmol	Nickel	Creatinine in urine	*
	0,04 mg/g	Nickel	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV) , Social Affairs and Ministry of Health**

Material	Value	Determinant	Specimen	Sampling Time
Nickel Product	0,1 umol/l	Nickel	Urine	*

**Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV) , Social Affairs and Ministry of Health Components**

Value	Determinant	Specimen	Sampling Time	
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	0,1 umol/l	Nickel	Urine	*

\* - For sampling details, please see the source document.

**Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices**

Material	Value	Determinant	Specimen	Sampling Time
Nickel Product	0,02 mg/g	Nickel	Creatinine in urine	*
	0,038 µmol/mmol	Nickel	Creatinine in urine	*

Components	Value	Determinant	Specimen	Sampling Time
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	0,02 mg/g	Nickel	Creatinine in urine	*
	0,038 µmol/mmol	Nickel	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)**

Material	Value	Determinant	Specimen	Sampling Time
Nickel Product	45 µg/l	Nickel	Urine	*

Components	Value	Determinant	Specimen	Sampling Time
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	45 µg/l	Nickel	Urine	*

\* - For sampling details, please see the source document.

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

**Exposure guidelines**

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0) Can be absorbed through the skin.

**8.2. Exposure controls**

**Appropriate engineering controls** Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection** If contact is likely, safety glasses with side shields are recommended.

**Skin protection**

**- Hand protection** Wear gloves to prevent metal cuts and skin abrasions during handling.

**- Other** Use personal protective equipment as required.

**Respiratory protection** In case of inadequate ventilation, use respiratory protection.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

**Hygiene measures** Observe any medical surveillance requirements. Contaminated work clothing should not be allowed out of the workplace.



**Environmental exposure controls** Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

**Physical state** Solid.

**Form** Solid.

**Colour** Grey metallic.

**Odour** None.

**Odour threshold** Not applicable.

**pH** Not applicable.

**Melting point/freezing point** 1455 °C (2651 °F) estimated / Not applicable.  
1455 °C (2651 °F)

**Initial boiling point and boiling range** Not applicable.

2730 °C (4946 °F)

**Flash point** Not applicable.

**Evaporation rate** Not applicable.

**Flammability (solid, gas)** None known.

#### Upper/lower flammability or explosive limits

**Explosive limit - lower (%)** Not applicable.

**Explosive limit - lower (%) temperature** Not applicable.

**Explosive limit – upper (%)** Not applicable.

**Explosive limit - upper (%) temperature** Not applicable.

**Vapour pressure** Not applicable.

**Vapour density** Not applicable.

**Relative density** Not applicable.

#### Solubility(ies)

**Solubility (water)** Insoluble  
Not applicable.

**Partition coefficient (n-octanol/water)** Not applicable.  
Not applicable.

**Auto-ignition temperature** Not applicable.

**Decomposition temperature** Not applicable.

**Viscosity** Not applicable.

**Explosive properties** Not explosive.

**Oxidising properties** Not oxidising.

### 9.2. Other information

**Density** 8,90 g/cm<sup>3</sup> estimated  
8,91 g/cm<sup>3</sup> estimated

**Molecular formula** Ni

**Molecular weight** 58,69 g/mol

**Specific gravity** 8,91

## SECTION 10: Stability and reactivity

**10.1. Reactivity** The product is stable and non-reactive under normal conditions of use, storage and transport.

**10.2. Chemical stability** Material is stable under normal conditions.

**10.3. Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use.

- 10.4. Conditions to avoid** Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
- 10.5. Incompatible materials** Strong acids.
- 10.6. Hazardous decomposition products** No hazardous decomposition products are known.

## SECTION 11: Toxicological information

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

### Information on likely routes of exposure

- Inhalation** Prolonged inhalation may be harmful.
- Skin contact** May cause an allergic skin reaction.
- Eye contact** Not likely, due to the form of the product.
- Ingestion** Expected to be a low ingestion hazard.

**Symptoms** May cause respiratory irritation. May cause an allergic skin reaction. Dermatitis. Rash.

### 11.1. Information on toxicological effects

- Acute toxicity** None known.
- Skin corrosion/irritation** May cause skin irritation.
- Serious eye damage/eye irritation** Not likely, due to the form of the product.
- Respiratory sensitisation** Not a respiratory sensitizer.
- Skin sensitisation** May cause an allergic skin reaction.
- Germ cell mutagenicity** Not classified.
- Carcinogenicity** Suspected of causing cancer.

#### Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

#### IARC Monographs. Overall Evaluation of Carcinogenicity

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0) 2B Possibly carcinogenic to humans.

#### Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0) Carcinogenic, Category 2.

- Reproductive toxicity** Not classified.
- Specific target organ toxicity - single exposure** Not classified.
- Specific target organ toxicity - repeated exposure** May cause damage to organs through prolonged or repeated exposure.
- Aspiration hazard** Not an aspiration hazard.
- Mixture versus substance information** No information available.
- Other information** Not available.

## SECTION 12: Ecological information

**12.1. Toxicity** Based on available data, the classification criteria are not met for hazardous to the aquatic environment.

Product	Species	Test Results
Nickel Product		
<b>Aquatic</b>		
<i>Acute</i>		
Crustacea	EC50 Water flea (Daphnia magna)	1 mg/l, 48 hours
Fish	LC50 Rainbow trout, donaldson trout (Oncorhynchus mykiss)	0,06 mg/l, 4 days

**12.2. Persistence and degradability** No data is available on the degradability of any ingredients in the mixture.

**12.3. Bioaccumulative potential** No data available.

<b>Partition coefficient n-octanol/water (log Kow)</b>	Not applicable.
<b>Bioconcentration factor (BCF)</b>	Not available.
<b>12.4. Mobility in soil</b>	No data available.
<b>12.5. Results of PBT and vPvB assessment</b>	Not a PBT or vPvB substance or mixture.
<b>12.6. Other adverse effects</b>	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 12.7. Additional information

### Estonia Dangerous substances in soil Data

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	Nickel (Ni) 150 mg/kg
	Nickel (Ni) 50 mg/kg
	Nickel (Ni) 500 mg/kg

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

14.1. - 14.6.: Not regulated as dangerous goods.

### RID

14.1. - 14.6.: Not regulated as dangerous goods.

### ADN

14.1. - 14.6.: Not regulated as dangerous goods.

### IATA

14.1. - 14.6.: Not regulated as dangerous goods.

### IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

##### Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

##### Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

##### Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

##### Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

##### Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

##### Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

**Authorisations**

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

**Restrictions on use**

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Not listed.

**Other EU regulations**

**Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

Not listed.

**National regulations**

Not available.

**15.2. Chemical safety assessment**

Not available.

**SECTION 16: Other information**

**List of abbreviations**

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

CAS: Chemical Abstract Service.

CEN: European Committee for Standardization.

IATA: International Air Transport Association.

IBC: Intermediate Bulk Container.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative, toxic.

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

VLE: Exposure Limit Value.

VME: Exposure Average Value.

vPvB: Very persistent and very bioaccumulative.

**References**

Not available.

**Information on evaluation method leading to the classification of mixture**

Not applicable.

**Training information**

Follow training instructions when handling this material.

**Further information**

Transportation Emergency

Call Chemtrec at:

US: 800.424.9300

International: 703.741.5970

Spain: 900.868.538

Switzerland: 0800.564.402

Chemtrec's toll free, mobile-enabled number in Germany – 0800 1817059

South Korea Toll-free Number – 080-880-0468

## Disclaimer

This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.

To avoid any misunderstandings or incorrect assumptions by the receiver of the safety information, it should be made clear that the supplied information is not in the form of a Safety Data Sheet (SDS), but is actually a voluntary Product Information Sheet closely following the guidelines of the Safety Data Sheet – COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 (REACH/SDS).