



SAFETY DATA SHEET

MATERION

1. Identification

Product identifier Powder G with 2-isopropyl alcohol

Other means of identification

SDS number 1TO

Materion Code 1TO

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Materion Advanced Chemicals Inc.

Address
407 N 13th Street
1316 W. St. Paul Avenue
Milwaukee, WI 53233
United States

Telephone 414.212.0257

E-mail advancedmaterials@materion.com

Contact person Noreen Atkinson

Emergency phone number Chemtrec 800.424.9300

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards
Acute toxicity, oral Category 4
Skin corrosion/irritation Category 1
Serious eye damage/eye irritation Category 1
Specific target organ toxicity, single exposure Category 3 narcotic effects

Environmental hazards Not classified.

OSHA defined hazards Combustible dust

Label elements



Signal word Warning

Hazard statement The mixture does not meet the criteria for classification.

Precautionary statement

Prevention Observe good industrial hygiene practices.

Response Wash hands after handling.

Storage Store away from incompatible materials.

Disposal Dispose of waste and residues in accordance with local authority requirements.

Hazard(s) not otherwise classified (HNOC) None known.

Supplemental information 82.17% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. 32.67% of the mixture consists of component(s) of unknown acute oral toxicity. 82.17% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 42.57% of the mixture consists of component(s) of unknown acute dermal toxicity. For further information, please contact the Product Stewardship Department at +1.800.862.4118.

3. Composition/information on ingredients

Mixtures

| Chemical name | Common name and synonyms | CAS number | % |
|--|---|------------|-------|
| Aluminum Oxide | | 1344-28-1 | |
| Lithium hydroxide | Lithium hydroxide (Li(OH)) LITHIUM HYDRATE | 1310-65-2 | |
| RM Isopropyl Alcohol (2-propanol) | | 67-63-0 | |
| Other components below reportable levels | | | 49.51 |

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

| | |
|---|--|
| Inhalation | Move to fresh air. Call a physician if symptoms develop or persist. |
| Skin contact | Wash off with soap and water. Get medical attention if irritation develops and persists. |
| Eye contact | Rinse with water. Get medical attention if irritation develops and persists. |
| Ingestion | Rinse mouth. Get medical attention if symptoms occur. |
| Most important symptoms/effects, acute and delayed | Headache. Dizziness. |
| Indication of immediate medical attention and special treatment needed | Treat symptomatically. |
| General information | Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. |

5. Fire-fighting measures

| | |
|--|---|
| Suitable extinguishing media | Alcohol resistant foam. Powder. Carbon dioxide (CO ₂). |
| Unsuitable extinguishing media | Do not use water jet as an extinguisher, as this will spread the fire. |
| Specific hazards arising from the chemical | During fire, gases hazardous to health may be formed. |
| Special protective equipment and precautions for firefighters | Self-contained breathing apparatus and full protective clothing must be worn in case of fire. |
| Fire fighting equipment/instructions | Use water spray to cool unopened containers. |
| Specific methods | Use standard firefighting procedures and consider the hazards of other involved materials. |
| General fire hazards | No unusual fire or explosion hazards noted. |

6. Accidental release measures

| | |
|--|---|
| Personal precautions, protective equipment and emergency procedures | Keep unnecessary personnel away. For personal protection, see section 8 of the SDS. |
| Methods and materials for containment and cleaning up | Stop the flow of material, if this is without risk. Following product recovery, flush area with water. For waste disposal, see section 13 of the SDS. |
| Environmental precautions | Avoid discharge into drains, water courses or onto the ground. |

7. Handling and storage

| | |
|---|---|
| Precautions for safe handling | Avoid prolonged exposure. Observe good industrial hygiene practices. |
| Conditions for safe storage, including any incompatibilities | Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS). |

8. Exposure controls/personal protection

Occupational exposure limits

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

| Components | Type | Value | Form |
|---|------|-----------------------|----------------------|
| Aluminum Oxide (CAS 1344-28-1) | PEL | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |
| RM Isopropyl Alcohol (2-propanol) (CAS 67-63-0) | PEL | 980 mg/m ³ | |
| | | 400 ppm | |

US. OSHA Table Z-3 (29 CFR 1910.1000)

| Components | Type | Value | Form |
|--------------------------------|------|----------------------|----------------------|
| Aluminum Oxide (CAS 1344-28-1) | TWA | 5 mg/m ³ | Respirable fraction. |
| | | 15 mg/m ³ | Total dust. |
| | | 50 mppcf | Total dust. |
| | | 15 mppcf | Respirable fraction. |

US. ACGIH Threshold Limit Values

| Components | Type | Value | Form |
|---|------|---------------------|----------------------|
| Aluminum Oxide (CAS 1344-28-1) | TWA | 1 mg/m ³ | Respirable fraction. |
| RM Isopropyl Alcohol (2-propanol) (CAS 67-63-0) | STEL | 400 ppm | |
| | TWA | 200 ppm | |

US. NIOSH: Pocket Guide to Chemical Hazards

| Components | Type | Value |
|---|------|------------------------|
| RM Isopropyl Alcohol (2-propanol) (CAS 67-63-0) | STEL | 1225 mg/m ³ |
| | TWA | 500 ppm |
| | | 980 mg/m ³ |
| | | 400 ppm |

US. Workplace Environmental Exposure Level (WEEL) Guides

| Components | Type | Value |
|-----------------------------------|---------|---------------------|
| Lithium hydroxide (CAS 1310-65-2) | Ceiling | 1 mg/m ³ |

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

| Components | Type | Value | Form |
|---|------|------------------------|----------------------|
| Aluminum Oxide (CAS 1344-28-1) | PEL | 5 mg/m ³ | Respirable fraction. |
| | | 10 mg/m ³ | Total dust. |
| RM Isopropyl Alcohol (2-propanol) (CAS 67-63-0) | PEL | 980 mg/m ³ | |
| | | 400 ppm | |
| | STEL | 1225 mg/m ³ | |
| | | 500 ppm | |

Biological limit values

ACGIH Biological Exposure Indices

| Components | Value | Determinant | Specimen | Sampling Time |
|---|---------|-------------|----------|---------------|
| RM Isopropyl Alcohol (2-propanol) (CAS 67-63-0) | 40 mg/l | Acetone | Urine | * |

* - For sampling details, please see the source document.

| | |
|--|---|
| Appropriate engineering controls | Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. |
| Control parameters | Follow standard monitoring procedures. |
| Individual protection measures, such as personal protective equipment | |
| Eye/face protection | Wear safety glasses with side shields (or goggles). |
| Skin protection | |
| Hand protection | Wear appropriate chemical resistant gloves. |
| Other | Wear suitable protective clothing. |
| Respiratory protection | In case of insufficient ventilation, wear suitable respiratory equipment. |
| Thermal hazards | Wear appropriate thermal protective clothing, when necessary. |
| General hygiene considerations | Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. |

9. Physical and chemical properties

Appearance

| | |
|---|----------------------------------|
| Physical state | Solid. |
| Form | Solid. |
| Color | Not available. |
| Odor | Not available. |
| Odor threshold | Not available. |
| pH | Not available. |
| Melting point/freezing point | -127.3 °F (-88.5 °C) estimated |
| Initial boiling point and boiling range | 180.5 °F (82.5 °C) estimated |
| Flash point | 53.6 °F (12.0 °C) estimated |
| Evaporation rate | Not available. |
| Flammability (solid, gas) | Not available. |
| Upper/lower flammability or explosive limits | |
| Flammability limit - lower (%) | 2.5 % estimated |
| Flammability limit - upper (%) | 12 % estimated |
| Explosive limit - lower (%) | Not available. |
| Explosive limit - upper (%) | Not available. |
| Vapor pressure | 47.47 hPa estimated |
| Vapor density | Not available. |
| Relative density | Not available. |
| Solubility(ies) | |
| Solubility (water) | Not available. |
| Partition coefficient (n-octanol/water) | Not available. |
| Auto-ignition temperature | 750.2 °F (399 °C) estimated |
| Decomposition temperature | Not available. |
| Viscosity | Not available. |
| Other information | |
| Density | 0.86 g/cm ³ estimated |

| | |
|-----------------------------|----------------|
| Explosive properties | Not explosive. |
| Oxidizing properties | Not oxidizing. |
| Specific gravity | 0.86 estimated |

10. Stability and reactivity

| | |
|---|---|
| Reactivity | The product is stable and non-reactive under normal conditions of use, storage and transport. |
| Chemical stability | Material is stable under normal conditions. |
| Possibility of hazardous reactions | No dangerous reaction known under conditions of normal use. |
| Conditions to avoid | Avoid temperatures exceeding the flash point. Contact with incompatible materials. |
| Incompatible materials | Acids. Strong oxidizing agents. Isocyanates. Chlorine. |
| Hazardous decomposition products | No hazardous decomposition products are known. |

11. Toxicological information

Information on likely routes of exposure

| | |
|---------------------|--|
| Inhalation | Prolonged inhalation may be harmful. |
| Skin contact | No adverse effects due to skin contact are expected. |
| Eye contact | Direct contact with eyes may cause temporary irritation. |
| Ingestion | Expected to be a low ingestion hazard. |

| | |
|---|----------------------|
| Symptoms related to the physical, chemical and toxicological characteristics | Headache. Dizziness. |
|---|----------------------|

Information on toxicological effects

| | |
|--|--|
| Acute toxicity | Not known. |
| Skin corrosion/irritation | Prolonged skin contact may cause temporary irritation. |
| Serious eye damage/eye irritation | Direct contact with eyes may cause temporary irritation. |
| Respiratory or skin sensitization | |
| Respiratory sensitization | Not a respiratory sensitizer. |
| Skin sensitization | This product is not expected to cause skin sensitization. |
| Germ cell mutagenicity | No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic. |
| Carcinogenicity | This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA. |

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

| | |
|---|--|
| Reproductive toxicity | This product is not expected to cause reproductive or developmental effects. |
| Specific target organ toxicity - single exposure | Not classified. |
| Specific target organ toxicity - repeated exposure | Not classified. |
| Aspiration hazard | Not an aspiration hazard. |
| Chronic effects | Prolonged inhalation may be harmful. |

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

| Product | Species | Test Results |
|---|----------------|--|
| Powder G with 2-isopropyl alcohol | | |
| Aquatic | | |
| Fish | LC50 | Fish 15475 mg/l, 96 hours estimated |
| Components | Species | Test Results |
| RM Isopropyl Alcohol (2-propanol) (CAS 67-63-0) | | |
| Aquatic | | |
| Fish | LC50 | Bluegill (Lepomis macrochirus) > 1400 mg/l, 96 hours |

* Estimates for product may be based on additional component data not shown.

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential

Partition coefficient n-octanol / water (log Kow)

RM Isopropyl Alcohol (2-propanol) 0.05

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT

UN number UN2921
UN proper shipping name Corrosive solids, flammable, n.o.s. (Lithium hydroxide)
Transport hazard class(es)
Class 8
Subsidiary risk 4.1
Label(s) 8, 4.1
Packing group II
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Special provisions IB8, IP2, IP4, T3, TP33
Packaging exceptions None
Packaging non bulk 212
Packaging bulk 242

IATA

UN number UN2921
UN proper shipping name Corrosive solid, flammable, n.o.s. (Lithium hydroxide)
Transport hazard class(es)
Class 8

Subsidiary risk 4.1
Packing group II
Environmental hazards No.
ERG Code 8S
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.
Other information


Passenger and cargo aircraft Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

UN number UN2921
UN proper shipping name CORROSIVE SOLID, FLAMMABLE, N.O.S. (Lithium hydroxide)
Transport hazard class(es)
Class 8
Subsidiary risk 4.1
Packing group II
Environmental hazards
Marine pollutant No.
EmS F-A, S-G
Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

DOT



IATA; IMDG



15. Regulatory information

US federal regulations This product is not known to be a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

RM Isopropyl Alcohol (2-propanol) (CAS 67-63-0) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories
Immediate Hazard - Yes
Delayed Hazard - No
Fire Hazard - Yes
Pressure Hazard - No
Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No

SARA 313 (TRI reporting)

| <u>Chemical name</u> | <u>CAS number</u> | <u>% by wt.</u> |
|-----------------------------------|-------------------|-----------------|
| RM Isopropyl Alcohol (2-propanol) | 67-63-0 | |

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA) Not regulated.

FEMA Priority Substances Respiratory Health and Safety in the Flavor Manufacturing Workplace

RM Isopropyl Alcohol (2-propanol) (CAS 67-63-0) Low priority

US state regulations

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

RM Isopropyl Alcohol (2-propanol) (CAS 67-63-0)

16. Other information, including date of preparation or last revision

Issue date 01-09-2017

Revision date 01-12-2018

Version # 02

Disclaimer

Materion Advanced Chemicals Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.