



# SAFETY DATA SHEET

**MATERION**

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1. Product identifier

**Trade name or designation of the mixture** Ge-As-Se-Si 14-32-47-7  
**Registration number** -  
**Document number** 2JR  
**Synonyms** None.  
**Materion Code** 2JR  
**Issue date** 18-December-2018  
**Version number** 01

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

**Company name** Materion Advanced Chemicals Inc.  
**Address** 407 N. 13th Street  
1316 W. St. Paul Avenue  
Milwaukee, WI 53233  
United States  
**Division** Milwaukee  
**Telephone** 414.212.0257  
**e-mail** advancedmaterials@materion.com  
**Contact person** Noreen Atkinson

### 1.4. Emergency telephone number

### 1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Not available.  
**Uses advised against** None known.

### 1.3. Details of the supplier of the safety data sheet

#### Supplier

**Company name** Materion Advanced Chemicals Inc.  
**Address** 407 N. 13th Street  
1316 W. St. Paul Avenue  
Milwaukee, WI 53233  
United States  
**Division** Milwaukee  
**Telephone** 414.212.0257  
**e-mail** advancedmaterials@mail  
**Contact person** Noreen Atkinson

### 1.4. Emergency telephone number

## SECTION 2: Hazards identification

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

### Classification according to Regulation (EC) No 1272/2008 as amended

#### Health hazards

Acute toxicity, oral	Category 3	H301 - Toxic if swallowed.
Acute toxicity, inhalation	Category 3	H331 - Toxic if inhaled.
Carcinogenicity	Category 1A	H350 - May cause cancer.
Specific target organ toxicity - repeated exposure	Category 2	H373 - May cause damage to organs through prolonged or repeated exposure.

## Environmental hazards

Hazardous to the aquatic environment, acute Category 1 aquatic hazard

H400 - Very toxic to aquatic life.

Hazardous to the aquatic environment, long-term aquatic hazard Category 1

H410 - Very toxic to aquatic life with long lasting effects.

## Hazard summary

Toxic if inhaled. Toxic if swallowed. May cause damage to organs through prolonged or repeated exposure. May cause cancer. Prolonged exposure may cause chronic effects. Dangerous for the environment if discharged into watercourses. Occupational exposure to the substance or mixture may cause adverse health effects. The material as sold in solid form is generally not considered hazardous. However, if the process involves grinding, melting, cutting or any other process that causes a release of dust or fumes, hazardous levels of airborne particulate could be generated.

## 2.2. Label elements

### Label according to Regulation (EC) No. 1272/2008 as amended

#### Contains:

Arsenic, Selenium

#### Hazard pictograms



#### Signal word

Danger

#### Hazard statements

H301	Toxic if swallowed.
H331	Toxic if inhaled.
H350	May cause cancer.
H373	May cause damage to organs through prolonged or repeated exposure.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

## Precautionary statements

### Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P261	Avoid breathing dust.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P273	Avoid release to the environment.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

### Response

P301 + P310	IF SWALLOWED: Immediately call a POISON CENTRE/doctor.
P330	Rinse mouth.
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P311	Call a POISON CENTRE/doctor.
P391	Collect spillage.

### Storage

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

### Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

## Supplemental label information

18 % of the mixture consists of component(s) of unknown acute oral toxicity. 97 % of the mixture consists of component(s) of unknown acute dermal toxicity. 18 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 18 % of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment. For further information, please contact the Product Stewardship Department at +1.800.862.4118.

## 2.3. Other hazards

Not a PBT or vPvB substance or mixture.

## SECTION 3: Composition/information on ingredients

### 3.2. Mixtures

## General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Selenium	47	7782-49-2 231-957-4	-	034-001-00-2	
<b>Classification:</b>	Acute Tox. 3;H301, Acute Tox. 3;H331, STOT RE 2;H373				
Arsenic	32	7440-38-2 231-148-6	-	033-001-00-X	
<b>Classification:</b>	Acute Tox. 3;H301, Acute Tox. 3;H331, Carc. 1A;H350, Aquatic Acute 1;H400, Aquatic Chronic 1;H410				
Other components below reportable levels	21 - 68				

### List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

**Composition comments** The full text for all H-statements is displayed in section 16.

## SECTION 4: First aid measures

**General information** IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

### 4.1. Description of first aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a POISON CENTRE or doctor/physician.

**Skin contact** Wash off with soap and water. Get medical attention if irritation develops and persists.

**Eye contact** Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

**Ingestion** Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting without advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

**4.2. Most important symptoms and effects, both acute and delayed** Headache. Prolonged exposure may cause chronic effects.

**4.3. Indication of any immediate medical attention and special treatment needed** Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim under observation. Symptoms may be delayed.

## SECTION 5: Firefighting measures

**General fire hazards** No unusual fire or explosion hazards noted.

### 5.1. Extinguishing media

**Suitable extinguishing media** Foam. Powder. Dry sand. Carbon dioxide (CO<sub>2</sub>).

**Unsuitable extinguishing media** Do not use water jet as an extinguisher, as this will spread the fire.

**5.2. Special hazards arising from the substance or mixture** During fire, gases hazardous to health may be formed.

### 5.3. Advice for firefighters

**Special protective equipment for firefighters** Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

**Special firefighting procedures** Move containers from fire area if you can do so without risk.

**Specific methods** Use standard firefighting procedures and consider the hazards of other involved materials.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

**For emergency responders** Keep unnecessary personnel away.

### 6.2. Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

### 6.3. Methods and material for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Absorb in vermiculite, dry sand or earth and place into containers. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers.

### 6.4. Reference to other sections

Not available.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimise dust generation and accumulation. Do not taste or swallow. Avoid breathing dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

### 7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place.

### 7.3. Specific end use(s)

Not available.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### Occupational exposure limits

##### Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
Selenium (CAS 7782-49-2)	MAK	0,1 mg/m <sup>3</sup>	Inhalable fraction.
	STEL	0,3 mg/m <sup>3</sup>	Inhalable fraction.

##### Belgium. Exposure Limit Values.

Components	Type	Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	TWA	0,2 mg/m <sup>3</sup>
Silicon (CAS 7440-21-3)	TWA	10 mg/m <sup>3</sup>

##### Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Arsenic (CAS 7440-38-2)	TWA	0,05 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	TWA	0,2 mg/m <sup>3</sup>

##### Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value	Form
Arsenic (CAS 7440-38-2)	MAC	0,1 mg/m <sup>3</sup>	

**Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09**

Components	Type	Value	Form
Selenium (CAS 7782-49-2)	MAC	0,1 mg/m <sup>3</sup>	
Silicon (CAS 7440-21-3)	STEL	4 mg/m <sup>3</sup>	Respirable dust.
		10 mg/m <sup>3</sup>	Total dust.

**Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.**

Components	Type	Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	TWA	0,2 mg/m <sup>3</sup>

**Czech Republic. OELs. Government Decree 361**

Components	Type	Value
Arsenic (CAS 7440-38-2)	Ceiling	0,4 mg/m <sup>3</sup>
	TWA	0,1 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	Ceiling	0,2 mg/m <sup>3</sup>
	TWA	0,1 mg/m <sup>3</sup>

**Denmark. Exposure Limit Values**

Components	Type	Value
Silicon (CAS 7440-21-3)	TLV	10 mg/m <sup>3</sup>

**Estonia. OELs. Occupational Exposure Limits of Hazardous Substances. (Annex of Regulation No. 293 of 18 September 2001)**

Components	Type	Value	Form
Arsenic (CAS 7440-38-2)	TWA	0,03 mg/m <sup>3</sup>	
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m <sup>3</sup>	
Silicon (CAS 7440-21-3)	TWA	5 mg/m <sup>3</sup>	Respirable dust.
		10 mg/m <sup>3</sup>	

**Finland. Workplace Exposure Limits**

Components	Type	Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	STEL	0,3 mg/m <sup>3</sup>
	TWA	0,1 mg/m <sup>3</sup>

**France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984**

Components	Type	Value
Silicon (CAS 7440-21-3)	VME	10 mg/m <sup>3</sup>

**Regulatory status:** Indicative limit (VL)

**Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)**

Components	Type	Value	Form
Selenium (CAS 7782-49-2)	TWA	0,02 mg/m <sup>3</sup>	Inhalable fraction.

**Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace**

Components	Type	Value	Form
Selenium (CAS 7782-49-2)	AGW	0,05 mg/m <sup>3</sup>	Inhalable fraction.

**Greece. OELs (Decree No. 90/1999, as amended)**

Components	Type	Value	Form
Arsenic (CAS 7440-38-2)	TWA	0,1 mg/m <sup>3</sup>	
Selenium (CAS 7782-49-2)	TWA	0,2 mg/m <sup>3</sup>	
Silicon (CAS 7440-21-3)	TWA	5 mg/m <sup>3</sup>	Respirable.
		10 mg/m <sup>3</sup>	Inhalable

**Hungary. OELs. Joint Decree on Chemical Safety of Workplaces**

Components	Type	Value
Arsenic (CAS 7440-38-2)	Ceiling	0,01 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	STEL	0,4 mg/m <sup>3</sup>
	TWA	0,1 mg/m <sup>3</sup>

**Iceland. OELs. Regulation 154/1999 on occupational exposure limits**

Components	Type	Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m <sup>3</sup>
Silicon (CAS 7440-21-3)	TWA	0,7 mg/m <sup>3</sup>
		0,5 ppm

**Ireland. Occupational Exposure Limits**

Components	Type	Value	Form
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m <sup>3</sup>	
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m <sup>3</sup>	
Silicon (CAS 7440-21-3)	TWA	4 mg/m <sup>3</sup>	Respirable dust.
		10 mg/m <sup>3</sup>	Total inhalable dust.

**Italy. Occupational Exposure Limits**

Components	Type	Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	TWA	0,2 mg/m <sup>3</sup>

**Lithuania. OELs. Limit Values for Chemical Substances, General Requirements**

Components	Type	Value
Arsenic (CAS 7440-38-2)	TWA	0,03 mg/m <sup>3</sup>
Germanium (CAS 7440-56-4)	TWA	2 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m <sup>3</sup>

**Netherlands. OELs (binding)**

Components	Type	Value
Arsenic (CAS 7440-38-2)	TWA	0,0028 mg/m <sup>3</sup>

**Norway. Administrative Norms for Contaminants in the Workplace**

Components	Type	Value
Arsenic (CAS 7440-38-2)	TLV	0,01 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	TLV	0,05 mg/m <sup>3</sup>
Silicon (CAS 7440-21-3)	TLV	10 mg/m <sup>3</sup>

**Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817**

Components	Type	Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	STEL	0,3 mg/m <sup>3</sup>
	TWA	0,1 mg/m <sup>3</sup>

**Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)**

Components	Type	Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	TWA	0,2 mg/m <sup>3</sup>

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Components	Type	Value
Arsenic (CAS 7440-38-2)	STEL	0,1 mg/m <sup>3</sup>
	TWA	0,01 mg/m <sup>3</sup>

**Romania. OELs. Protection of workers from exposure to chemical agents at the workplace**

Components	Type	Value
Germanium (CAS 7440-56-4)	STEL	5 mg/m <sup>3</sup>
	TWA	2 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	STEL	0,2 mg/m <sup>3</sup>
	TWA	0,1 mg/m <sup>3</sup>

**Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents**

Components	Type	Value	Form
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m <sup>3</sup>	
Silicon (CAS 7440-21-3)	TWA	4 mg/m <sup>3</sup>	Respirable fraction.
		10 mg/m <sup>3</sup>	Inhalable fraction.

**Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)**

Components	Type	Value	Form
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m <sup>3</sup>	Inhalable fraction.

**Spain. Occupational Exposure Limits**

Components	Type	Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m <sup>3</sup>
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m <sup>3</sup>

**Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)**

Components	Type	Value	Form
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m <sup>3</sup>	Total dust.
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m <sup>3</sup>	Total dust.

**Switzerland. SUVA Grenzwerte am Arbeitsplatz**

Components	Type	Value	Form
Selenium (CAS 7782-49-2)	STEL	0,16 mg/m <sup>3</sup>	Inhalable fraction.
	TWA	0,02 mg/m <sup>3</sup>	Inhalable fraction.
Silicon (CAS 7440-21-3)	TWA	3 mg/m <sup>3</sup>	Respirable fraction.

**UK. EH40 Workplace Exposure Limits (WELs)**

Components	Type	Value	Form
Arsenic (CAS 7440-38-2)	TWA	0,1 mg/m <sup>3</sup>	
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m <sup>3</sup>	
Silicon (CAS 7440-21-3)	TWA	4 mg/m <sup>3</sup>	Respirable dust.
		10 mg/m <sup>3</sup>	Inhalable dust.

**Biological limit values****Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)**

Components	Value	Determinant	Specimen	Sampling Time
Arsenic (CAS 7440-38-2)	70 µg/l	Arsenic	Urine	*
	0,93 µmol/l	Arsenic	Urine	*

\* - For sampling details, please see the source document.

**Czech Republic. Limit Values for Indicators of Biological Exposure Tests in Urine and Blood, Annex 2, Tables 1 and 2, Government Decree 432/2003 Sb.**

Components	Value	Determinant	Specimen	Sampling Time
Arsenic (CAS 7440-38-2)	0,075 µmol/mmol	Arsenic	Creatinine in urine	*
	0,05 mg/g	Arsenic	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV) , Social Affairs and Ministry of Health Components**

Value	Determinant	Specimen	Sampling Time
70 nmol/l	Inorganic arsenic	Urine	*

\* - For sampling details, please see the source document.

**France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 2065) Components**

Value	Determinant	Specimen	Sampling Time
0,05 mg/g	Métabolites de l'arsenic inorganique	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices**

Value	Determinant	Specimen	Sampling Time
0,13 mg/g	Arsenic	Creatinine in urine	*
0,2 µmol/mmol	Arsenic	Creatinine in urine	*
0,075 mg/g	Selenium	Creatinine in urine	*
0,11 µmol/mmol	Selenium	Creatinine in urine	*

\* - For sampling details, please see the source document.

**Spain. Biological Limit Values (VLBs), Occupational Exposure Limits for Chemical Agents, Table 4 Components**

Value	Determinant	Specimen	Sampling Time
35 µg/l	Arsénico inorgánico más metabolitos metilados como As	Urine	*

\* - For sampling details, please see the source document.

**Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)**

Value	Determinant	Specimen	Sampling Time
50 µg/l	Anorganisches Arsen und methylierte Metaboliten	Urine	*

\* - For sampling details, please see the source document.

**Recommended monitoring procedures** Follow standard monitoring procedures.

**Derived no effect levels (DNELs)** Not available.

**Predicted no effect concentrations (PNECs)** Not available.

**8.2. Exposure controls**

**Appropriate engineering controls** Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

**Individual protection measures, such as personal protective equipment**

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

**Eye/face protection** If contact is likely, safety glasses with side shields are recommended.

**Skin protection**

**- Hand protection** Wear appropriate chemical resistant gloves.

**- Other** Wear suitable protective clothing. Use of an impervious apron is recommended.

**Respiratory protection** In case of insufficient ventilation, wear suitable respiratory equipment.



<b>Thermal hazards</b>	Wear appropriate thermal protective clothing, when necessary.
<b>Hygiene measures</b>	Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
<b>Environmental exposure controls</b>	Inform appropriate managerial or supervisory personnel of all environmental releases.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

#### Appearance

<b>Physical state</b>	Solid.
<b>Form</b>	Solid.
<b>Colour</b>	Not available.
<b>Odour</b>	Not available.
<b>Odour threshold</b>	Not available.
<b>pH</b>	Not available.
<b>Melting point/freezing point</b>	180 °C (356 °F) estimated
<b>Initial boiling point and boiling range</b>	685 °C (1265 °F) estimated
<b>Flash point</b>	Not available.
<b>Evaporation rate</b>	Not available.
<b>Flammability (solid, gas)</b>	Not available.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not available.
<b>Flammability limit - upper (%)</b>	Not available.
<b>Vapour pressure</b>	4863,58 hPa estimated
<b>Vapour density</b>	Not available.
<b>Relative density</b>	Not available.
<b>Solubility(ies)</b>	
<b>Solubility (water)</b>	Not available.
<b>Partition coefficient (n-octanol/water)</b>	Not available.
<b>Auto-ignition temperature</b>	Not available.
<b>Decomposition temperature</b>	Not available.
<b>Viscosity</b>	Not available.
<b>Explosive properties</b>	Not explosive.
<b>Oxidising properties</b>	Not oxidising.

### 9.2. Other information

<b>Density</b>	4,87 g/cm <sup>3</sup> estimated
<b>Specific gravity</b>	4,87 estimated

## SECTION 10: Stability and reactivity

<b>10.1. Reactivity</b>	The product is stable and non-reactive under normal conditions of use, storage and transport.
<b>10.2. Chemical stability</b>	Material is stable under normal conditions.
<b>10.3. Possibility of hazardous reactions</b>	No dangerous reaction known under conditions of normal use.
<b>10.4. Conditions to avoid</b>	Contact with incompatible materials.
<b>10.5. Incompatible materials</b>	Acids. Strong oxidising agents. Fluorine. Chlorine.
<b>10.6. Hazardous decomposition products</b>	No hazardous decomposition products are known.

## SECTION 11: Toxicological information

<b>General information</b>	Occupational exposure to the substance or mixture may cause adverse effects.
----------------------------	--

## Information on likely routes of exposure

<b>Inhalation</b>	Toxic if inhaled.
<b>Skin contact</b>	No adverse effects due to skin contact are expected.
<b>Eye contact</b>	Direct contact with eyes may cause temporary irritation.
<b>Ingestion</b>	Toxic if swallowed.

**Symptoms** Headache.

### 11.1. Information on toxicological effects

<b>Acute toxicity</b>	Toxic if inhaled. Toxic if swallowed.
<b>Skin corrosion/irritation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Serious eye damage/eye irritation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Respiratory sensitisation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Skin sensitisation</b>	Due to partial or complete lack of data the classification is not possible.
<b>Germ cell mutagenicity</b>	Due to partial or complete lack of data the classification is not possible.
<b>Carcinogenicity</b>	May cause cancer.

### Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

### IARC Monographs. Overall Evaluation of Carcinogenicity

Arsenic (CAS 7440-38-2)	1 Carcinogenic to humans.
Selenium (CAS 7782-49-2)	3 Not classifiable as to carcinogenicity to humans.

<b>Reproductive toxicity</b>	Due to partial or complete lack of data the classification is not possible.
<b>Specific target organ toxicity - single exposure</b>	Due to partial or complete lack of data the classification is not possible.
<b>Specific target organ toxicity - repeated exposure</b>	May cause damage to organs through prolonged or repeated exposure.
<b>Aspiration hazard</b>	Due to partial or complete lack of data the classification is not possible.
<b>Mixture versus substance information</b>	No information available.
<b>Other information</b>	Not available.

## SECTION 12: Ecological information

**12.1. Toxicity** Very toxic to aquatic life with long lasting effects.

Product	Species	Test Results
Ge-As-Se-Si 14-32-47-7		
<b>Aquatic</b>		
Fish	LC50	Fish 30,9375 mg/l, 96 hours estimated
Components	Species	Test Results
Arsenic (CAS 7440-38-2)		
<b>Aquatic</b>		
Fish	LC50	Fathead minnow (Pimephales promelas) 9,9 mg/l, 96 hours

\* Estimates for product may be based on additional component data not shown.

### 12.2. Persistence and degradability

**12.3. Bioaccumulative potential** No data available.

**Partition coefficient n-octanol/water (log Kow)** Not available.

**Bioconcentration factor (BCF)** Not available.

**12.4. Mobility in soil** No data available.

**12.5. Results of PBT and vPvB assessment** Not a PBT or vPvB substance or mixture.

**12.6. Other adverse effects** No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

## 12.7. Additional information

### Estonia Dangerous substances in groundwater Data

Arsenic (CAS 7440-38-2)

TRADE SECRET INGREDIENT(S)

Selenium (CAS 7782-49-2)

TRADE SECRET INGREDIENT(S)

### Estonia Dangerous substances in soil Data

Arsenic (CAS 7440-38-2)

TRADE SECRET INGREDIENT(S)

Selenium (CAS 7782-49-2)

TRADE SECRET INGREDIENT(S)

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

<b>Residual waste</b>	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
<b>Contaminated packaging</b>	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
<b>EU waste code</b>	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
<b>Disposal methods/information</b>	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
<b>Special precautions</b>	Dispose in accordance with all applicable regulations.

## SECTION 14: Transport information

### ADR

<b>14.1. UN number</b>	UN3178
<b>14.2. UN proper shipping name</b>	Flammable solid, inorganic, n.o.s. (Silicon)
<b>14.3. Transport hazard class(es)</b>	
<b>Class</b>	4.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	4.1
<b>Hazard No. (ADR)</b>	40
<b>Tunnel restriction code</b>	E
<b>14.4. Packing group</b>	III
<b>14.5. Environmental hazards</b>	No.
<b>14.6. Special precautions for user</b>	Not available.

### RID

<b>14.1. UN number</b>	UN3178
<b>14.2. UN proper shipping name</b>	Flammable solid, inorganic, n.o.s. (Silicon)
<b>14.3. Transport hazard class(es)</b>	
<b>Class</b>	4.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	4.1
<b>14.4. Packing group</b>	III
<b>14.5. Environmental hazards</b>	No.
<b>14.6. Special precautions for user</b>	Not available.

### ADN

<b>14.1. UN number</b>	UN3178
<b>14.2. UN proper shipping name</b>	Flammable solid, inorganic, n.o.s. (Silicon)
<b>14.3. Transport hazard class(es)</b>	
<b>Class</b>	4.1
<b>Subsidiary risk</b>	-
<b>Label(s)</b>	4.1
<b>14.4. Packing group</b>	III
<b>14.5. Environmental hazards</b>	No.

**14.6. Special precautions for user** Not available.

#### IATA

**14.1. UN number** UN3178  
**14.2. UN proper shipping name** Flammable solid, inorganic, n.o.s. (Silicon)  
**14.3. Transport hazard class(es)**  
    **Class** 4.1  
    **Subsidiary risk** -  
**14.4. Packing group** III  
**14.5. Environmental hazards** No.  
**ERG Code** 3L  
**14.6. Special precautions for user** Not available.


#### Other information

**Passenger and cargo aircraft** Allowed with restrictions.  
**Cargo aircraft only** Allowed with restrictions.

#### IMDG

**14.1. UN number** UN3178  
**14.2. UN proper shipping name** FLAMMABLE SOLID, INORGANIC, N.O.S. (Silicon)  
**14.3. Transport hazard class(es)**  
    **Class** 4.1  
    **Subsidiary risk** -  
**14.4. Packing group** III  
**14.5. Environmental hazards**  
    **Marine pollutant** No.  
**EmS** F-A, S-G  
**14.6. Special precautions for user** Not available.

#### ADN; ADR; IATA; IMDG; RID



**General information** IMDG Regulated Marine Pollutant.

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### EU regulations

**Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**

Not listed.

**Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended**

Not listed.

**Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended**

Not listed.

**Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended**

Arsenic (CAS 7440-38-2)

**Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA**

Not listed.

**Authorisations**

**Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended**

Not listed.

**Restrictions on use**

**Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**

Arsenic (CAS 7440-38-2)

**Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.**

Not listed.

**Other EU regulations**

**Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended**

Arsenic (CAS 7440-38-2)

Selenium (CAS 7782-49-2)

**Other regulations**

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

**National regulations**

Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

**15.2. Chemical safety assessment**

No Chemical Safety Assessment has been carried out.

**SECTION 16: Other information**

**List of abbreviations**

Not available.

**References**

Not available.

**Information on evaluation method leading to the classification of mixture**

The classification for health and environmental hazards is derived by a combination of calculator methods and test data, if available.

**Full text of any H-statements not written out in full under Sections 2 to 15**

H301 Toxic if swallowed.

H331 Toxic if inhaled.

H350 May cause cancer.

H373 May cause damage to organs (respiratory system) through prolonged or repeated exposure.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

**Revision information**

None.

**Training information**

Follow training instructions when handling this material.

**Disclaimer**

Materion Advanced Chemicals Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.