MATERION

SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or

Ge-As-Se-In targets

designation of the mixture

Registration number

Document number 2MN **Synonyms** None. **Materion Code** 2MN

Issue date 20-March-2020

1.3. Details of the supplier of the safety data sheet

Supplier

Company name Materion Advanced Chemicals Inc.

Address 407 N. 13th Street

> 1316 W. St. Paul Avenue Milwaukee, WI 53233

United States

Division Milwaukee Telephone 414.212.0257

e-mail advancedmaterials@materion.com

Contact person Laura Hamilton

1.4. Emergency telephone

number

Version number 01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available. Uses advised against None known.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Acute toxicity, oral Category 3 H301 - Toxic if swallowed. H331 - Toxic if inhaled. Acute toxicity, inhalation Category 3 Carcinogenicity Category 1A H350 - May cause cancer. Specific target organ toxicity - repeated Category 2 H373 - May cause damage to exposure organs through prolonged or repeated exposure.

Environmental hazards

Hazardous to the aquatic environment, acute Category 1 H400 - Very toxic to aquatic life.

aquatic hazard

Hazardous to the aquatic environment, Category 1 H410 - Very toxic to aquatic life

long-term aquatic hazard with long lasting effects.

Hazard summary Toxic if inhaled. Toxic if swallowed. May cause damage to organs through prolonged or repeated

exposure. May cause cancer. Prolonged exposure may cause chronic effects. Dangerous for the environment if discharged into watercourses. Occupational exposure to the substance or mixture may cause adverse health effects. The material as sold in solid form is generally not considered hazardous. However, if the process involves grinding, melting, cutting or any other process that causes a release of dust or fumes, hazardous levels of airborne particulate could be generated.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Arsenic, Germanium, Indium, Selenium

Material name: Ge-As-Se-In targets

Hazard pictograms



Signal word Danger

Hazard statements

Toxic if swallowed. H301 Toxic if inhaled. H331 May cause cancer. H350

May cause damage to organs through prolonged or repeated exposure. H373

Very toxic to aquatic life. H400

Very toxic to aquatic life with long lasting effects. H410

Precautionary statements

Prevention

Obtain special instructions before use. P201

Do not handle until all safety precautions have been read and understood. P202

Do not breathe dust/fume/gas/mist/vapours/spray. P260

Avoid breathing dust. P261

Wash thoroughly after handling. P264

Do not eat, drink or smoke when using this product. P270 Use only outdoors or in a well-ventilated area. P271

Avoid release to the environment. P273

Wear protective gloves/protective clothing/eye protection/face protection. P280

Response

IF SWALLOWED: Immediately call a POISON CENTRE/doctor. P301 + P310

Rinse mouth. P330

IF INHALED: Remove person to fresh air and keep comfortable for breathing. P304 + P340

P311 Call a POISON CENTRE/doctor.

Collect spillage. P391

Storage

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Store locked up. P405

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label

60 % of the mixture consists of component(s) of unknown acute oral toxicity. 100 % of the information

mixture consists of component(s) of unknown acute dermal toxicity. 60 % of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 60 % of the mixture

consists of component(s) of unknown long-term hazards to the aquatic environment.

For further information, please contact the Product Stewardship Department at +1.800.862.4118.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	% CAS-No. / EC RI No.	EACH Registration No.	Index No.	Notes
Arsenic	7440-38-2 231-148-6	-	033-001-00-X	
Classification:	Acute Tox. 3;H301, Acute Tox. 3;H331, Carc. 1 Chronic 1;H410	A;H350, Aquatic Acute 1;	H400, Aquatic	
Germanium	7440-56-4	-	-	
	231-164-3			
Classification:	-			
Indium	7440-74-6	-	-	
	231-180-0			
Classification:	-			
Selenium	7782-49-2	-	034-001-00-2	
	231-957-4			
Classification:	Acute Tox. 3;H301, Acute Tox. 3;H331, STOT I	RE 2;H373		

Material name: Ge-As-Se-In targets 2MN Version #: 01 Issue date: 20-March-2020

List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice

(show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in

attendance.

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Oxygen or

artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device. Call a poison center or doctor/physician.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists. **Eye contact** Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Call a physician or poison control centre immediately. Rinse mouth. Do not induce vomiting without

advice from poison control center. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other

proper respiratory medical device.

4.2. Most important symptoms and effects, both acute and delayed

Headache. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim warm. Keep victim

under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Foam. Powder. Carbon dioxide (CO2).

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special firefighting procedures

Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of dust. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be

contained. For personal protection, see section 8 of the SDS.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental

precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into

drains, water courses or onto the ground.

Material name: Ge-As-Se-In targets SDS FU 3 / 13

2MN Version #: 01 Issue date: 20-March-2020

6.3. Methods and material for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Absorb in vermiculite, dry sand or earth and place into containers. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers.

6.4. Reference to other sections

For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimise dust generation and accumulation. Do not taste or swallow. Avoid breathing dust. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

0,1 mg/m3

0,3 mg/m3

0,1 mg/m3

SDS FU

4 / 13

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Components	Туре	Value	Form	
Indium (CAS 7440-74-6)	MAK	0,1 mg/m3	Inhalable fraction.	
	STEL	0,2 mg/m3	Inhalable fraction.	
Selenium (CAS 7782-49-2)	MAK	0,1 mg/m3	Inhalable fraction.	
	STEL	0,3 mg/m3	Inhalable fraction.	
Belgium. Exposure Limit Values.				
Components	Туре	Value		
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m3		
Indium (CAS 7440-74-6)	TWA	0,1 mg/m3		
Selenium (CAS 7782-49-2)	TWA	0,2 mg/m3		
Bulgaria. OELs. Regulation No 1	3 on protection of workers a	against risks of exposure to	chemical agents at work	
Components	Туре	Value		
Arsenic (CAS 7440-38-2)	TWA	0,05 mg/m3		
Selenium (CAS 7782-49-2)	TWA	0,2 mg/m3		
Croatia. Dangerous Substance E 13/09	xposure Limit Values in the	Workplace (ELVs), Annexes	1 and 2, Narodne Novine	
Components	Туре	Value		
Arsenic (CAS 7440-38-2)	MAC	0,1 mg/m3		
(0.0 7.40 7.40)				

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended

MAC

STEL

MAC

Components	Туре	Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m3

2MN Version #: 01 Issue date: 20-March-2020

Material name: Ge-As-Se-In targets

Indium (CAS 7440-74-6)

Selenium (CAS 7782-49-2)

Components	Туре	Value	
Selenium (CAS 7782-49-2)	TWA	0,2 mg/m3	
Czech Republic. OELs. Governme	ent Decree 361		
Components	Туре	Value	
Arsenic (CAS 7440-38-2)	Ceiling	0,4 mg/m3	
	TWA	0,1 mg/m3	
Selenium (CAS 7782-49-2)	Ceiling	0,2 mg/m3	
	TWA	0,1 mg/m3	
Denmark. Exposure Limit Values	5		
Components	Туре	Value	Form
Indium (CAS 7440-74-6)	TLV	0,1 mg/m3	Dust.
Estonia. OELs. Occupational Exp	osure Limits of Hazardous Subs	tances. (Annex of Regula	tion No. 293 of 18
September 2001)	Toma	V- I	
Components	Туре	Value	
Arsenic (CAS 7440-38-2)	TWA	0,03 mg/m3	
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m3	
Finland. Workplace Exposure Li Components	mits Type	Value	
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m3	
Indium (CAS 7440-74-6)	TWA	0,1 mg/m3	
Selenium (CAS 7782-49-2)	STEL TWA	0,3 mg/m3 0,1 mg/m3	
		, -	
Germany. DFG MAK List (advisor Compounds in the Work Area (D		vestigation of Health Haz	ards of Chemical
Components	Туре	Value	Form
Selenium (CAS 7782-49-2)	TWA	0,02 mg/m3	Inhalable fraction.
Germany. TRGS 900, Limit Value	es in the Ambient Air at the Wor	kplace	
Components	Туре	Value	Form
Indium (CAS 7440-74-6)	AGW	0,0001 mg/m3	Respirable fraction
Selenium (CAS 7782-49-2)	AGW	0,05 mg/m3	Inhalable fraction.
Greece. OELs (Decree No. 90/19	999, as amended)		
Components	Туре	Value	
Arsenic (CAS 7440-38-2)	TWA	0,1 mg/m3	
Indium (CAS 7440-74-6)	STEL	1 mg/m3	
	TWA	1 mg/m3	
Selenium (CAS 7782-49-2)	TWA	0,2 mg/m3	
Hungary. OELs. Joint Decree on Components	Chemical Safety of Workplaces Type	Value	
Arsenic (CAS 7440-38-2)	Ceiling	0,01 mg/m3	
Selenium (CAS 7782-49-2)	STEL	0,4 mg/m3	
•	TWA	0,1 mg/m3	

Indium (CAS 7440-74-6)	TWA	0,1 mg/m3	Dust.
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m3	

Value

0,01 mg/m3

Form

Material name: Ge-As-Se-In targets 2MN Version #: 01 Issue date: 20-March-2020

Components

Arsenic (CAS 7440-38-2)

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Type

TWA

Ireland. Occupational Exposure Limits Components	Туре	Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m3
Indium (CAS 7440-74-6)	STEL	0,3 mg/m3
	TWA	0,1 mg/m3
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m3
Italy. Occupational Exposure Limits Components	Туре	Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m3
Indium (CAS 7440-74-6)	TWA	0,1 mg/m3
Selenium (CAS 7782-49-2)	TWA	0,2 mg/m3
Lithuania. OELs. Limit Values for Chem Components	ical Substances, Gene Type	eral Requirements Value
Arsenic (CAS 7440-38-2)	TWA	0,03 mg/m3
Germanium (CAS 7440-56-4)	TWA	2 mg/m3
Indium (CAS 7440-74-6)	TWA	0,1 mg/m3
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m3
Netherlands. OELs (binding) Components	Туре	Value
Arsenic (CAS 7440-38-2)	TWA	0,0028 mg/m3
Norway. Administrative Norms for Cont Components		. •
Arsenic (CAS 7440-38-2)	TLV	0,01 mg/m3
Indium (CAS 7440-74-6)	TLV	0,1 mg/m3
Selenium (CAS 7782-49-2)	TLV	0,05 mg/m3
Ordinance of the Minister of Labour and and intensities of harmful health factor Components		ne 2014 on the maximum permissible concentration ment, Journal of Laws 2014, item 817 Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m3
Selenium (CAS 7782-49-2)	STEL	0,3 mg/m3
	TWA	0,1 mg/m3
Portugal. VLEs. Norm on occupational e Components	exposure to chemical a Type	agents (NP 1796) Value
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m3
Indium (CAS 7440-74-6)	TWA	0,1 mg/m3
Selenium (CAS 7782-49-2)	TWA	0,2 mg/m3
Romania. OELs. Protection of workers f	rom exposure to chen	nical agents at the workplace Value
- Arsenic (CAS 7440-38-2)	STEL	0,1 mg/m3
(3.2.1.0.00.2)	TWA	0,01 mg/m3
Germanium (CAS 7440-56-4)	STEL	5 mg/m3
	TWA	2 mg/m3
Selenium (CAS 7782-49-2)	STEL	0,2 mg/m3
	TWA	0,1 mg/m3
Slovakia. OELs. Regulation No. 300/20 Components	07 concerning protect Type	ion of health in work with chemical agents Value
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m3

Material name: Ge-As-Se-In targets
2MN Version #: 01 Issue date: 20-March-2020

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Type

Form

Value

0,1 mg/m3

0,1 mg/m3

Indium (CAS 7440-74-6)	TWA	0,1 mg/m3	Inhalable fraction.
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m3	Inhalable fraction.
Spain. Occupational Exposure Li	mits		
Components	Туре	Value	
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m3	
Indium (CAS 7440-74-6)	TWA	0,1 mg/m3	
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m3	
Sweden. OELs. Work Environme	nt Authority (AV), Occupation	onal Exposure Limit Values (AFS 2015:7)
Components	Туре	Value	Form
Arsenic (CAS 7440-38-2)	TWA	0,01 mg/m3	Total dust.
Indium (CAS 7440-74-6)	TWA	0,1 mg/m3	Total dust.
Selenium (CAS 7782-49-2)	TWA	0,1 mg/m3	Total dust.
Switzerland. SUVA Grenzwerte	am Arbeitsplatz		
Components	Туре	Value	Form
Indium (CAS 7440-74-6)	TWA	0,1 mg/m3	Inhalable fraction.
Selenium (CAS 7782-49-2)	STEL	0,16 mg/m3	Inhalable fraction.
	TWA	0,02 mg/m3	Inhalable fraction.
UK. EH40 Workplace Exposure L	imits (WELs)		
Components	Туре	Value	
Arsenic (CAS 7440-38-2)	TWA	0,1 mg/m3	
Indium (CAS 7440-74-6)	STEL	0,3 mg/m3	
		0 ppm	

Biological limit values

Selenium (CAS 7782-49-2)

Components

Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)

TWA

TWA

Components	Value	Determinant	Specimen	Sampling Time
Arsenic (CAS 7440-38-2)	70 μg/l	Arsenic	Urine	*
	0,93 umol/l	Arsenic	Urine	*

^{* -} For sampling details, please see the source document.

Czech Republic. Limit Values for Indictators of Biological Exposure Tests in Urine and Blood, Annex 2, Tables 1 and 2. Government Decree 432/2003 Sb.

Components	Value	Determinant	Specimen	Sampling Time
Arsenic (CAS 7440-38-2)	0,075 μmol/mmol	Arsenic	Creatinine in urine	*
	0,05 mg/g	Arsenic	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV), Social Affairs and Ministry of Health							
Components	Value	Determinant	Specimen	Sampling Time			
Arsenic (CAS 7440-38-2)	70 nmol/l	Inorganic	Urine	*			

^{* -} For sampling details, please see the source document.

France. Biological indicators of exposure (IBE) (National Institute for Research and Security (INRS, ND 2065)

Components	value	Determinant	Specimen	Sampling Time
Arsenic (CAS 7440-38-2)	0,05 mg/g	Métabolites de l'arsenic inorganique	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Material name: Ge-As-Se-In targets

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling Time
Arsenic (CAS 7440-38-2)	0,13 mg/g	Arsenic	Creatinine in urine	*
	0,2 µmol/mmol	Arsenic	Creatinine in urine	*
Selenium (CAS 7782-49-2)	0,075 mg/g	Selenium	Creatinine in urine	*
	0,11 µmol/mmol	Selenium	Creatinine in urine	*

^{* -} For sampling details, please see the source document.

Spain. Biological Limit Components	Values (VLBs), O Value	ccupational Exposure l Determinant	imits for Che Specimen	mical Agents, Table 4 Sampling Time	
Arsenic (CAS 7440-38-2)	35 μg/l	Arsénico inorgánico más metabolitos metilados como As	Urine	*	

^{* -} For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)								
Components	Value	Determinant	Specimen	Sampling Time				
Arsenic (CAS 7440-38-2)	50 μg/l	Anorganisches Arsen und methylierte Metaboliten	Urine	*				

^{* -} For sampling details, please see the source document.

Recommended monitoring procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective $\dot{}$

equipment

Eye/face protection

If contact is likely, safety glasses with side shields are recommended.

Skin protection

- Hand protection

Wear appropriate chemical resistant gloves.

- Other

Wear suitable protective clothing. Use of an impervious apron is recommended.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

Observe any medical surveillance requirements. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure

controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Solid. **Form** Solid.

Colour Not available. Odour Not available. **Odour threshold** Not available. Not available. pН

156,6 °C (313,88 °F) estimated Melting point/freezing point 685 °C (1265 °F) estimated Initial boiling point and

boiling range

Flash point Not available. Not available. **Evaporation rate** Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit -

Not available.

upper (%)

3039,74 hPa estimated Vapour pressure

Vapour density Not available. Not available. Relative density

Solubility(ies)

Not available. Solubility (water) **Partition coefficient** Not available.

(n-octanol/water)

Auto-ignition temperature Not available. **Decomposition temperature** Not available. **Viscosity** Not available. **Explosive properties** Not explosive. **Oxidising properties** Not oxidising.

9.2. Other information

Density 5,41 g/cm3 estimated Specific gravity 5,41 estimated

SECTION 10: Stability and reactivity

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous No dangerous reaction known under conditions of normal use.

reactions

10.4. Conditions to avoid Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with

incompatible materials.

10.5. Incompatible materials Acids. Strong oxidising agents.

10.6. Hazardous No hazardous decomposition products are known.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Toxic if inhaled.

Skin contact No adverse effects due to skin contact are expected. Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion Toxic if swallowed.

Symptoms Headache.

11.1. Information on toxicological effects

Material name: Ge-As-Se-In targets

2MN Version #: 01 Issue date: 20-March-2020

Acute toxicity Toxic if inhaled. Toxic if swallowed.

Skin corrosion/irritationDue to partial or complete lack of data the classification is not possible. **Serious eye damage/eye**Due to partial or complete lack of data the classification is not possible.

irritation

Respiratory sensitisationDue to partial or complete lack of data the classification is not possible.Skin sensitisationDue to partial or complete lack of data the classification is not possible.Germ cell mutagenicityDue to partial or complete lack of data the classification is not possible.

Carcinogenicity May cause cancer.

Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)

Not listed.

IARC Monographs. Overall Evaluation of Carcinogenicity

Arsenic (CAS 7440-38-2) 1 Carcinogenic to humans.

Selenium (CAS 7782-49-2) 3 Not classifiable as to carcinogenicity to humans.

Reproductive toxicityDue to partial or complete lack of data the classification is not possible. **Specific target organ toxicity**Due to partial or complete lack of data the classification is not possible.

- single exposure

Specific target organ toxicity

- repeated exposure

Aspiration hazard

May cause damage to organs through prolonged or repeated exposure.

Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity Very toxic to aquatic life with long lasting effects.

Product Species Test Results

Ge-As-Se-In targets

Aquatic

Fish LC50 Fish 33 mg/l, 96 hours estimated

Components Species Test Results

Arsenic (CAS 7440-38-2)

Aquatic

Fish LC50 Fathead minnow (Pimephales promelas) 9,9 mg/l, 96 hours

12.2. Persistence and

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative

potential

No data available.

Partition coefficient

n-octanol/water (log Kow)

Not available.

Bioconcentration factor (BCF) Not available. **12.4. Mobility in soil** No data available.

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effectsNo other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

12.7. Additional information

Estonia Dangerous substances in groundwater Data

Arsenic (CAS 7440-38-2)

ARSENIC (AS) 100 ug/l

ARSENIC (AS) 5 ug/l

Selenium (CAS 7782-49-2)

Selenium (Se) 5 ug/l

Selenium (Se) 50 ug/l

Estonia Dangerous substances in soil Data

Arsenic (CAS 7440-38-2)

Arsenic (CAS 7440-38-2)

ARSENIC (AS) 20 mg/kg

ARSENIC (AS) 30 mg/kg

ARSENIC (AS) 50 mg/kg

Selenium (CAS 7782-49-2)

Selenium (Se) 1 mg/kg

Selenium (Se) 20 mg/kg

Material name: Ge-As-Se-In targets
2MN Version #: 01 Issue date: 20-March-2020

SDS EU 10 / 13

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow this **Disposal** methods/information

material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with

chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. UN number UN3077

14.2. UN proper shipping Environmentally hazardous substance, solid, n.o.s.

name

14.3. Transport hazard class(es)

9 **Subsidiary risk** Label(s) 14.4. Packing group III 14.5. Environmental Yes

hazards

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

ADN

14.1. - 14.6.: Not regulated as dangerous goods.


IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

RID



Marine pollutant



General information

IMDG Regulated Marine Pollutant.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Arsenic (CAS 7440-38-2)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Arsenic (CAS 7440-38-2)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Arsenic (CAS 7440-38-2) Selenium (CAS 7782-49-2)

Other regulations The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP

Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC)

No 1907/2006, as amended.

National regulations According to Directive 92/85/EEC as amended, pregnant women should not work with the product,

if there is the least risk of exposure.

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation on the protection of workers from the risks of exposure to carcinogens and mutagens at

work, in accordance with Directive 2004/37/EC, as amended.

15.2. Chemical safety

assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

Not available. List of abbreviations References Not available.

Training information Follow training instructions when handling this material.

Material name: Ge-As-Se-In targets SDS FU

Disclaimer

Materion Advanced Chemicals Inc. cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.

Material name: Ge-As-Se-In targets
2MN Version #: 01 Issue date: 20-March-2020