



MATERIAL SAFETY DATA SHEET

MATERION

1. Chemical product and company identification

A. Product name Aluminum Beryllium Master Alloy

B. Recommended use and Limitations on use

Recommended use Industrial uses: Uses of substances as such or in preparations at industrial sites
Offshore industries
Manufacture of basic metals, including alloys
Manufacture of fabricated metal products, except machinery and equipment
Manufacture of computer, electronic and optical products, electrical equipment
General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment
Electricity, steam, gas water supply and sewage treatment
Scientific research and development
Other: Manufacture of medical and defense equipment

Limitations on use Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Consumer uses: Private households (= general public = consumers)

C. Supplier information

Company name Materion Brush Inc.
Address 6070 Parkland Boulevard
Mayfield Heights OH 44124
United States

Email ehs@materion.com

Emergency telephone number +1.216.383.4019

MSDS number A03

2. Hazards identification

A. Hazard category/Classification

Physical hazards Not classified.
Health hazards Sensitization, skin Category 1
Carcinogenicity Category 1B
Specific target organ toxicity, repeated exposure (inhalation) Category 1 (Respiratory system)
Environmental hazards Hazardous to the aquatic environment, long-term hazard Category 2

B. Warning label items including precautionary statement

• Pictogram



• Signal word Danger

• Hazard statement

H301 Toxic if swallowed.
H330 Fatal if inhaled.
H317 May cause an allergic skin reaction.
H335 May cause respiratory irritation.
H350i May cause cancer by inhalation.
H360Fd May damage fertility. Suspected of damaging the unborn child.
H372 Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.

• Precautionary statement

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

P302 + P350	If on skin: Wash with plenty of water.
P304 + P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308 + P311	If exposed or concerned: Call a poison center/doctor.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P342 + P311	If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
P363	Wash contaminated clothing before reuse.

Storage

P405	Store locked up.
------	------------------

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

C. Other hazards not included in the hazard category criteria (e.g. dust explosion hazard) None known.

Supplemental information For further information, please contact the Product Stewardship Department at +1.216.383.4019.

3. Composition/information on ingredients

Chemical identity	Common and alternative names	CAS number	ID number	Content in percent (%)
Aluminum		7429-90-5	KE-00881	77.1 - 98.6
Beryllium		7440-41-7	KE-02829	0.1 - 11.0
Silicon		7440-21-3	KE-31029	0 - 9
Zinc		7440-66-6	KE-35518	0 - 8
Copper		7440-50-8	KE-08896	0 - 2.7
Magnesium		7439-95-4	KE-22673	0.5 - 1.5
Iron		7439-89-6	KE-21059	0 - 0.65
Nickel		7440-02-0	KE-25818	0 - 0.5

4. First aid measures

A. In case of eye contact	Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention if symptoms persist.
B. In case of skin contact	Take off contaminated clothing and wash before reuse. Thoroughly wash skin cuts or wounds to remove all particulate debris from the wound. Seek medical attention for wounds that cannot be thoroughly cleansed. Treat skin cuts and wounds with standard first aid practices such as cleansing, disinfecting and covering to prevent wound infection and contamination before continuing work. Obtain medical help for persistent irritation. Material accidentally implanted or lodged under the skin must be removed.
C. In case of inhalation	If symptoms develop move victim to fresh air. For breathing difficulties, oxygen may be necessary. Breathing difficulty caused by inhalation of particulate requires immediate removal to fresh air. If breathing has stopped, perform artificial respiration and obtain medical help.
D. In case of swallowing	If swallowed, seek medical advice immediately and show this container or label. Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person.

E. Note to physician

Treatment of Chronic Beryllium Disease: There is no known treatment which will cure chronic beryllium disease. Prednisone or other corticosteroids are the most specific treatment currently available. They are directed at suppressing the immunological reaction and can be effective in diminishing signs and symptoms of chronic beryllium disease. In cases where steroid therapy has had only partial or minimal effectiveness, other immunosuppressive agents, such as cyclophosphamide, cyclosporine, or methotrexate, have been used. These latter agents remain investigational. Further, in view of the potential side effects of all the immunosuppressive medications, including steroids such as prednisone, they should be used only under the direct care of a physician. In general, these medications should be reserved for cases with significant symptoms and/or significant loss of lung function. Other symptomatic treatment, such as oxygen, inhaled steroids or bronchodilators, may be prescribed by some physicians and can be effective in selected cases.

The decision about when and with what medication to treat is a judgment situation for individual physicians. For the most part, treatment is reserved for those persons with symptoms and measurable loss of lung function. The value of starting oral steroid treatment, before signs or symptoms are evident, remains a medically unresolved issue.

The effects of continued low exposure to beryllium are unknown for individuals who are sensitized to beryllium or who have a diagnosis of chronic beryllium disease. It is generally recommended that persons who are sensitized to beryllium or who have CBD terminate their occupational exposure to beryllium.

General advice

If exposed or concerned: get medical attention/advice. Get medical attention if symptoms occur. Wash contaminated clothing before reuse. As supplied, there is no immediate medical risk with beryllium products in article form. First aid measures provided are related to particulate containing beryllium.

5. Fire-fighting measures

A. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media

The product is non-combustible. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media

Do not use water to extinguish fires around operations involving molten metal due to the potential for steam explosions.

B. Specific hazards arising from the chemical (example: hazardous combustion products)

Not available.

C. Specific methods of fire-fighting

Special protective equipment for firefighters

Firefighters should wear full protective clothing including self contained breathing apparatus. Wear suitable protective equipment.

Special fire fighting procedures

Move containers from fire area if you can do so without risk. Water runoff can cause environmental damage.

Specific methods

Pressure-demand self-contained breathing apparatus must be worn by firefighters or any other persons potentially exposed to the particulate released during or after a fire.

6. Accidental release measures

A. Personal precautions, protective equipment and emergency measures

In solid form this material poses no special clean-up problems. Wear appropriate protective equipment and clothing during clean-up.

B. Environmental precautions

Avoid release to the environment. In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

C. Methods and materials for containment and cleaning up

Clean up in accordance with all applicable regulations.

7. Handling and storage

A. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Do not breathe dust/fume. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection. Wash thoroughly after handling. When using, do not eat, drink or smoke. Contaminated work clothing must not be allowed out of the workplace.

**B. Conditions for safe storage
(including any incompatibilities)**

Keep locked-up. Avoid contact with acids and alkalis. Avoid contact with oxidizing agents.

8. Exposure controls/personal protection

A. Exposure limit values, biological limit values, etc

Korea. OELs. Standards for Exposure to Chemical Substances and Physically Hazardous Factors

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	5 mg/m3	Welding fume.
		5 mg/m3	Pyrophoric powder.
		2 mg/m3	
		10 mg/m3	Dust.
Beryllium (CAS 7440-41-7)	STEL	0.01 mg/m3	
	TWA	0.002 mg/m3	
Copper (CAS 7440-50-8)	STEL	2 mg/m3	Dust and mist.
	TWA	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
Nickel (CAS 7440-02-0)	TWA	1 mg/m3	
Silicon (CAS 7440-21-3)	TWA	10 mg/m3	

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Beryllium (CAS 7440-41-7)	TWA	0.00005 mg/m3	Inhalable fraction.
Nickel (CAS 7440-02-0)	TWA	1.5 mg/m3	Inhalable fraction.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Exposure guidelines

Korea OELs: Skin designation

Beryllium (CAS 7440-41-7)

Substance can be absorbed through membrane, eye and skin and can cause whole body effects (It does not mean skin irritant).

B. Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Whenever possible, the use of local exhaust ventilation or other engineering controls is the preferred method of controlling exposure to airborne particulate. Where utilized, exhaust inlets to the ventilation system must be positioned as close as possible to the source of airborne generation. Avoid disruption of the airflow in the area of a local exhaust inlet by equipment such as a man-cooling fan. Check ventilation equipment regularly to ensure it is functioning properly. Provide training on the use and operation of ventilation to all users. Use qualified professionals to design and install ventilation systems.

C. Personal protective equipment

• Respiratory protection

When airborne exposures exceed or have the potential to exceed the occupational exposure limits, approved respirators must be used as specified by an Industrial Hygienist or other qualified professional. Respirator users must be medically evaluated to determine if they are physically capable of wearing a respirator. Quantitative and/or qualitative fit testing and respirator training must be satisfactorily completed by all personnel prior to respirator use. Users of tight fitting respirators must be clean shaven on those areas of the face where the respirator seal contacts the face. Use pressure-demand airline respirators when performing jobs with high potential exposures such as changing filters in a baghouse air cleaning device.

• Eye protection

Wear approved safety glasses, goggles, face shield and/or welder's helmet when risk of eye injury is present, particularly during operations that generate dust, mist or fume.

• Hand protection

Wear gloves to prevent contact with particulate or solutions. Wear gloves to prevent metal cuts and skin abrasions during handling.

• Body protection

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment. Protective overgarments or work clothing must be worn by persons who may become contaminated with particulate during activities. Skin contact with this material may cause, in some sensitive individuals, an allergic dermal response. Particulate that becomes lodged under the skin has the potential to induce sensitization and skin lesions.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

A. Appearance

Physical state	Solid.
Form	Various shapes.
Color	Silver.

B. Odor Not applicable.

C. Odor threshold Not applicable.

D. pH Not applicable.

E. Melting point/freezing point

Melting point	1030 - 1850 °F (554.44 - 1010 °C) estimated
Freezing point	787.15 °F (419.53 °C) estimated

F. Boiling point, initial boiling point, and boiling range Not applicable.

G. Flash point Not applicable.

H. Evaporation rate Not applicable.

I. Flammability (solid, gas) Not applicable.

J. Upper/lower limit on flammability or explosive limits

Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.

K. Vapor pressure 9.09 hPa estimated

L. Solubility

Solubility (water)	Not applicable.
Solubility (other)	Not applicable.

M. Vapor density Not applicable.

N. Specific gravity 3.02 estimated

O. n-octanol/water partition coefficient Not available.

P. Auto-ignition temperature Not applicable.

Q. Decomposition temperature Not applicable.

R. Viscosity Not applicable.

S. Molecular weight Not available.

Other data

Density	0.09 - 0.10 lb/in ³
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.
Relative density	Not applicable.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

A. Stability and hazardous reaction potential

Stability	Material is stable under normal conditions.
Hazardous reaction potential	Hazardous polymerization does not occur.

B. Conditions to avoid (e.g. static discharge, shock or vibration, etc) Avoid dust formation. Contact with acids. Contact with alkalis.

C. Incompatible materials Strong acids, alkalies and oxidizing agents.

D. Hazardous decomposition products No hazardous decomposition products are known.

11. Toxicological information

A. Information on likely routes of exposure

- **Respiratory organs** May cause sensitization by inhalation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause damage to organs (respiratory system) through prolonged or repeated exposure.
- **Skin** May cause an allergic skin reaction.
- **Eyes** Harmful in contact with eyes.
- **Mouth** Toxic if swallowed.

B. Information on health hazards

- **Acute toxicity (list all possible routes of exposure)** May cause allergic skin reaction.
- **Corrosivity or irritation to the skin** Not likely, due to the form of the product.
- **Serious eye damage/eye irritation** Harmful in contact with eyes.
- **Respiratory sensitization** May cause damage to organs (respiratory system) through prolonged or repeated exposure.
- **Skin sensitization** May cause an allergic skin reaction.
- **Carcinogenic properties /Carcinogenicity** Cancer hazard.

IARC Monographs. Overall Evaluation of Carcinogenicity

Beryllium (CAS 7440-41-7)

1 Carcinogenic to humans.

Nickel (CAS 7440-02-0)

2B Possibly carcinogenic to humans.

- **Mutagenic properties /Mutagenicity** Due to lack of data the classification is not possible.
- **Reproductive toxicity** Not classified.
- **Specific target organ toxicity - single exposure** May cause allergy or asthma symptoms or breathing difficulties if inhaled.
- **Specific target organ toxicity - repeated exposure** May cause damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.
- **Aspiration hazard** Due to lack of data the classification is not possible.

12. Ecological information

- A. **Ecotoxicity** No data available.
- B. **Persistence/degradability** No data is available on the degradability of this product.
- C. **Bioaccumulative potential** Not available.
- D. **Mobility in soil** Not available.
- E. **Other adverse effects** Not available.

13. Disposal considerations

- A. **Method of disposal** Material should be recycled if possible. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.
- B. **Disposal considerations (including disposal of contaminated containers or packaging)** Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

IATA

- A. **UN number** Not applicable.
- B. **UN proper shipping name** Not applicable.

C. Transport hazard class(es)

Class Not applicable.

Subsidiary risk -

D. Packing group Not applicable.

E. Environmental hazards No.

F. Special precautions for user Not applicable.

IMDG

A. UN number Not applicable.

B. UN proper shipping name Not applicable.

C. Transport hazard class(es)

Class Not applicable.

Subsidiary risk -

D. Packing group Not applicable.

E. Environmental hazards

Marine pollutant No.

EmS Not applicable.

F. Special precautions for user Not applicable.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

15. Regulatory information**A. Restrictions under the Industrial Safety and Health Law****Harmful Substances Prohibited from Manufacturing**

Not regulated.

Harmful Substances Requiring Permission for Manufacture or Use

Beryllium (CAS 7440-41-7)

Controlled Hazardous Substances

Aluminum (CAS 7429-90-5)

Copper (CAS 7440-50-8)

Zinc (CAS 7440-66-6)

Nickel (CAS 7440-02-0)

Harmful Substances Requiring Special Medical Examination

Aluminum (CAS 7429-90-5)

Beryllium (CAS 7440-41-7)

Copper (CAS 7440-50-8)

Workplace Environmental Monitoring Harmful Materials

Aluminum (CAS 7429-90-5)

Beryllium (CAS 7440-41-7)

Copper (CAS 7440-50-8)

Occupational Exposure Limit

Aluminum (CAS 7429-90-5)

Beryllium (CAS 7440-41-7)

Copper (CAS 7440-50-8)

Nickel (CAS 7440-02-0)

Silicon (CAS 7440-21-3)

B. Restrictions under the Chemicals Control Law (Previously Toxic Chemicals Control Law)**Accidental Release Prevention Substances**

Not regulated.

Observational Chemicals

Not regulated.

C. Restrictions under the Dangerous Substance Safety Management Act

D. Restrictions under the Wastes Control Act

Halogenated Materials in Waste Organic Solvents

Not regulated.

Hazardous Substances

Not regulated

E. Restrictions under other foreign or domestic laws

Clean Air Conservation Act

Air Pollutants

Aluminum (CAS 7429-90-5)

Beryllium (CAS 7440-41-7)

Copper (CAS 7440-50-8)

Iron (CAS 7439-89-6)

Nickel (CAS 7440-02-0)

Zinc (CAS 7440-66-6)

Specific Air Pollutants

Beryllium (CAS 7440-41-7)

Nickel (CAS 7440-02-0)

Act on the Registration and Evaluation of Chemicals

Banned Toxic Chemicals

Not regulated.

Designated Existing Chemicals Subject to Registration (PEC) (MoE No. 2015-92)

Not listed.

Restricted Chemical Substances

Not regulated.

Toxic Chemicals

Not regulated.

Further information

This material safety data sheet was prepared in accordance with Article 41 of the Industrial Safety and Health Law.

Inventory status

Country(s) or region	Inventory name	On inventory (yes/no)*
Korea	Existing Chemicals List (ECL)	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)
A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

A. Source of information Not available.

B. Issue date 02-03-2017

C. Number of revisions and date of most recent revision Not applicable.

Other information Corrected health hazard classifications.

Further information Transportation Emergency
Call Chemtrec at:
Domestic: 800.424.9300
International: 703.527.3887

Disclaimer This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.