


MATERION

SAFETY DATA SHEET

1. Identification of the product

GHS product identifier	Beryllium Oxide Ceramic Product
Other means of identification	
Common name(s), synonym(s)	Beryllium Oxide, Beryllia, Thermalox® 995, BW 1000®, BW3250®, Thermalox® CR
SDS number	C10
Recommended use of the chemical and restrictions on use	
Recommended use	Manufacture of computer, electronic and optical products, electrical equipment
Recommended restrictions	Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Casting, grinding or polishing of beryllium-containing alloys by artists; Casting, grinding or polishing of beryllium-containing alloys for dental crowns, appliances or prosthetics; Casting, grinding or polishing of beryllium-containing alloys for jewelry. Consumer uses: Private households (= general public = consumers)

Suppliers details

Company name	Materion Brush Inc.
Address	6070 Parkland Boulevard Mayfield Heights, OH 44124 United States
Telephone	+1.216.383.4019
Website	www.materion.com
E-mail	ehs@materion.com
Contact person	Theodore Knudson
Emergency phone number	+1.216.383.4019

2. Hazard identification

Classification of the substance or mixture

Physical hazards	Not classified.	
Health hazards	Carcinogenicity	Category 1
	Specific target organ toxicity, repeated exposure	Category 1 (Respiratory system)
Environmental hazards	Not classified.	

GHS label elements, including precautionary statements



Signal word	Danger
Hazard statement	
H350	May cause cancer by inhalation.
H372	Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.
Precautionary statement	
Prevention	
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume.

P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing must not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P285	In case of inadequate ventilation wear respiratory protection.

Response

P302 + P350	If on skin: Wash with plenty of water.
P304 + P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308 + P311	If exposed or concerned: Call a poison center/doctor.
P363	Wash contaminated clothing before reuse.

Storage

P405	Store locked up.
------	------------------

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Other hazards which do not result in classification

None known.

Supplemental information

Exposure to the elements listed in Section 3 by inhalation, ingestion, and skin contact can occur when melting, casting, gross handling, pickling, chemical cleaning, heat treating, abrasive cutting, welding, grinding, sanding, polishing, milling, crushing, or otherwise heating or abrading the surface of this material in a manner which generates particulate.

For further information, please contact the Product Stewardship Department at +1.216.383.4019.

3. Composition/information on ingredients**Substances**

Chemical identity	Common name(s), synonym(s)	CAS number and other unique identifiers	Concentration
Beryllium Oxide Ceramic Product	Beryllium Oxide, Beryllia, Thermalox® 995, BW 1000®, BW3250®, Thermalox® CR		100

4. First-aid measures**Description of necessary first-aid measures**

Inhalation	If symptoms develop move victim to fresh air. For breathing difficulties, oxygen may be necessary. Breathing difficulty caused by inhalation of particulate requires immediate removal to fresh air. If breathing has stopped, perform artificial respiration and obtain medical help.
Skin contact	Take off contaminated clothing and wash before reuse. Thoroughly wash skin cuts or wounds to remove all particulate debris from the wound. Seek medical attention for wounds that cannot be thoroughly cleansed. Treat skin cuts and wounds with standard first aid practices such as cleansing, disinfecting and covering to prevent wound infection and contamination before continuing work. Obtain medical help for persistent irritation. Material accidentally implanted or lodged under the skin must be removed.
Eye contact	Immediately flush eyes with plenty of water for at least 15 minutes, lifting lower and upper eyelids occasionally. Get medical attention if symptoms persist.
Ingestion	If swallowed, seek medical advice immediately and show this container or label. Induce vomiting immediately as directed by medical personnel. Never give anything by mouth to an unconscious person.

Most important symptoms/effects, acute and delayed

The beryllium oxide in the product is not known to cause acute health effects. Inhaling particulate containing beryllium oxide can cause a serious, chronic lung disease called Chronic Beryllium Disease (CBD) in some individuals. Inhaling particulate containing beryllium oxide can cause a serious, chronic lung disease called Chronic Beryllium Disease (CBD) in some individuals.

Indication of immediate medical attention and special treatment needed	Treatment of Chronic Beryllium Disease: There is no known treatment which will cure chronic beryllium disease. Prednisone or other corticosteroids are the most specific treatment currently available. They are directed at suppressing the immunological reaction and can be effective in diminishing signs and symptoms of chronic beryllium disease. In cases where steroid therapy has had only partial or minimal effectiveness, other immunosuppressive agents, such as cyclophosphamide, cyclosporine, or methotrexate, have been used. In view of the potential side effects of all the immunosuppressive medications, including steroids such as prednisone, they should be used only under the direct care of a physician. Other treatment, such as oxygen, inhaled steroids or bronchodilators, may be prescribed by some physicians and can be effective in selected cases. In general, treatment is reserved for cases with significant symptoms and/or significant loss of lung function. The decision about when and with what medication to treat is a judgment situation for individual physicians.
General information	In their 2014 official statement on the Diagnosis and Management of Beryllium Sensitivity and Chronic Beryllium Disease, the American Thoracic Society states that "it seems prudent for workers with BeS to avoid all future occupational exposure to beryllium." If exposed or concerned: get medical attention/advice. Get medical attention if symptoms occur. Wash contaminated clothing before reuse. As supplied, there is no immediate medical risk with beryllium oxide ceramic products in article form. First aid measures provided are related to particulate containing beryllium oxide.
5. Fire-fighting measures	
Suitable extinguishing media	The product is non-combustible. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Unsuitable extinguishing media	Do not use water to extinguish fires around operations involving molten metal due to the potential for steam explosions.
Specific hazards arising from the chemical	Not applicable.
Special protective actions for firefighters	Firefighters should wear full protective clothing including self contained breathing apparatus. Wear suitable protective equipment.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk. Water runoff can cause environmental damage.
Specific methods	Pressure-demand self-contained breathing apparatus must be worn by firefighters or any other persons potentially exposed to the particulate released during or after a fire.
6. Accidental release measures	
Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	In solid form this material poses no special clean-up problems. Wear appropriate protective equipment and clothing during clean-up.
For emergency responders	Not available.
Environmental precautions	Avoid release to the environment. In the event of a spill or accidental release, notify relevant authorities in accordance with all applicable regulations. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.
Methods and materials for containment and cleaning up	Clean up in accordance with all applicable regulations.
Other issues relating to spills and releases	Clean up in accordance with all applicable regulations.
7. Handling and storage	
Precautions to ensure safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Do not breathe dust/fume. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection. Wash thoroughly after handling. When using, do not eat, drink or smoke. Contaminated work clothing must not be allowed out of the workplace.
Conditions for safe storage, including any incompatibilities	Keep locked-up. Avoid contact with acids and alkalis. Avoid contact with oxidizing agents.

8. Exposure controls/personal protection

Control parameters

Occupational exposure limits

No exposure limits noted for ingredient(s).

Biological limit values

No biological exposure limits noted for the ingredient(s).

Control banding approach

Not available.

Appropriate engineering controls

VENTILATION: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Ensure adequate ventilation, especially in confined areas.

Whenever possible, the use of local exhaust ventilation or other engineering controls is the preferred method of controlling exposure to airborne particulate. Where utilized, exhaust inlets to the ventilation system must be positioned as close as possible to the source of airborne generation. Avoid disruption of the airflow in the area of a local exhaust inlet by equipment such as a man-cooling fan. Check ventilation equipment regularly to ensure it is functioning properly. Provide training on the use and operation of ventilation to all users. Use qualified professionals to design and install ventilation systems.

WET METHODS: Machining operations are usually performed under a liquid lubricant/coolant flood which assists in reducing airborne particulate. However, the cycling through of machine coolant containing finely divided particulate in suspension can result in the concentration building to a point where the particulate may become airborne during use. Certain processes such as sanding and grinding may require complete hooded containment and local exhaust ventilation. Prevent coolant from splashing onto floor areas, external structures or operators' clothing. Utilize a coolant filtering system to remove particulate from the coolant.

WORK PRACTICES: Develop work practices and procedures that prevent particulate from coming in contact with worker skin, hair, or personal clothing. If work practices and/or procedures are ineffective in controlling airborne exposure or visual particulate from deposition on skin, hair, or clothing, provide appropriate cleaning/washing facilities. Procedures should be written that clearly communicate the facility's requirements for protective clothing and personal hygiene. These clothing and personal hygiene requirements help keep particulate from being spread to non-production areas or from being taken home by the worker. Never use compressed air to clean work clothing or other surfaces.

Fabrication processes may leave a residue of particulate on the surface of parts, products or equipment that could result in employee exposure during subsequent material handling activities. As necessary, clean loose particulate from parts between processing steps. As a standard hygiene practice, wash hands before eating or smoking.

HOUSEKEEPING: Use vacuum and wet cleaning methods for particulate removal from surfaces. Be certain to de-energize electrical systems, as necessary, before beginning wet cleaning. Use vacuum cleaners with high efficiency particulate air (HEPA). Do not use compressed air, brooms, or conventional vacuum cleaners to remove particulate from surfaces as this activity can result in elevated exposures to airborne particulate. Follow the manufacturer's instructions when performing maintenance on HEPA filtered vacuums used to clean hazardous materials.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear approved safety glasses, goggles, face shield and/or welder's helmet when risk of eye injury is present, particularly during operations that generate dust, mist or fume.

Skin protection

Hand protection

Wear gloves to prevent contact with particulate or solutions. Wear gloves to prevent metal cuts and skin abrasions during handling.

Other	Protective overgarments or work clothing must be worn by persons who may become contaminated with particulate during activities. Skin contact with this material may cause, in some sensitive individuals, an allergic dermal response. Particulate that becomes lodged under the skin has the potential to induce sensitization and skin lesions.
Respiratory protection	When airborne exposures exceed or have the potential to exceed the occupational exposure limits, approved respirators must be used as specified by an Industrial Hygienist or other qualified professional. Respirator users must be medically evaluated to determine if they are physically capable of wearing a respirator. Quantitative and/or qualitative fit testing and respirator training must be satisfactorily completed by all personnel prior to respirator use. Users of tight fitting respirators must be clean shaven on those areas of the face where the respirator seal contacts the face. Use pressure-demand airline respirators when performing jobs with high potential exposures such as changing filters in a baghouse air cleaning device.
Thermal hazards	Not applicable.
General hygiene considerations	Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Solid Various shapes.
Color	White.
Odor	Not applicable.
Odor threshold	Not applicable.
pH	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	6.67 kPa at 25°C estimated
Vapor density	Not applicable.
Relative density	Not applicable.
Solubility(ies)	
Solubility (water)	Not applicable.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.
Other information	
Specific gravity	1.85 estimated

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
-------------------	---

Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Avoid dust formation. Contact with acids. Contact with alkalis.
Incompatible materials	Strong acids, alkalies and oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs (respiratory system) through prolonged or repeated exposure.
Skin contact	Not likely, due to the form of the product.
Eye contact	Not likely, due to the form of the product.
Ingestion	Not likely, due to the form of the product.

Symptoms Respiratory disorder.

Information on toxicological effects

Acute toxicity	Based on available data, the classification criteria are not met.
Skin corrosion/irritation	Not likely, due to the form of the product.
Serious eye damage/eye irritation	Not likely, due to the form of the product.
Respiratory or skin sensitization	
Respiratory sensitization	May cause damage to organs (respiratory system) through prolonged or repeated exposure.
Skin sensitization	Not a skin sensitizer.
Germ cell mutagenicity	Due to lack of data the classification is not possible.
Carcinogenicity	Cancer hazard.
Reproductive toxicity	Not classified.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	May cause damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.
Aspiration hazard	Due to lack of data the classification is not possible.
Other information	Symptoms may be delayed.

12. Ecological information

Ecotoxicity	No ecotoxicity data noted for the ingredient(s).
Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	Not available.
Mobility in soil	Not available.
Other adverse effects	Not available.

13. Disposal considerations

Disposal methods

Disposal instructions	Material should be recycled if possible. Disposal recommendations are based on material as supplied. Disposal must be in accordance with current applicable laws and regulations, and material characteristics at time of disposal.
Local disposal regulations	Not available.
Waste from residues / unused products	Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or disposal. Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport information

ANTT

Not regulated as dangerous goods.

DOT

Not regulated as dangerous goods.

SCT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

IMDG

Not regulated as dangerous goods.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code Not available.

15. Regulatory information

National regulations

Colombia. Chemical Precursors (Law 67 of 1993, Tables I and II)

Not regulated.

Ecuador. Precursors (Narcotic and Psychotropic Substances Law, Annex IV)

Not regulated.

International regulations

Montreal Protocol

Not applicable.

Stockholm Convention

Not applicable.

Rotterdam Convention

Not applicable.

Kyoto protocol

Not applicable.

Basel Convention

Not applicable.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	No
Canada	Domestic Substances List (DSL)	No
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	No
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	No
New Zealand	New Zealand Inventory	No
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	No

Country(s) or region	Inventory name	On inventory (yes/no)*
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	No

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other information

List of abbreviations	Not available.
Further information	Transportation Emergency Call Chemtrec at: Domestic: 800.424.9300 International: 703.527.3887
Disclaimer	This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.
Other information	Revised information in Section 2. Revised information in Section 4. Revised information in Section 8. Revised information in Section 11.