



SAFETY DATA SHEET

MATERION

1. Identification

Product identifier Metallized Alumina Ceramic

Other means of identification

SDS number C22

Synonyms Aluminum Oxide, Alumina, Al₂O₃, Durox AL, Durox UHP

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Materion Brush Inc.

Address 6070 Parkland Boulevard
Mayfield Heights, OH 44124
United States

Telephone 1.800.862.4118

Website www.materion.com

E-mail ehs@materion.com

Contact person Theodore Knudson

Emergency phone number 1.800.862.4118

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards

Sensitization, respiratory	Category 1
Sensitization, skin	Category 1
Carcinogenicity	Category 1A
Reproductive toxicity	Category 2
Specific target organ toxicity, single exposure	Category 1
Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
Specific target organ toxicity, repeated exposure	Category 2 (Respiratory system)

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause an allergic skin reaction. May cause cancer. Suspected of damaging fertility or the unborn child by ingestion. Causes damage to organs through prolonged or repeated exposure. May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. Wear respiratory protection.

Response	If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a poison center/doctor.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	For further information, please contact the Product Stewardship Department at +1.800.862.4118.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Molybdenum		7439-98-7	0 - 10
Nickel		7440-02-0	0 - 10
Silica		14808-60-7	0 - 4
Manganese		7439-96-5	0 - 2
Titanium		7440-32-6	0 - 2
Tungsten		7440-33-7	0 - 2
Gold		7440-57-5	0 - 1

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Do not rub eyes. Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Dusts may irritate the respiratory tract, skin and eyes. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
General information	If exposed or concerned: get medical attention/advice. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO ₂).
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not breathe dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up

Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Stop the flow of material, if this is without risk. Collect dust using a vacuum cleaner equipped with HEPA filter.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Minimize dust generation and accumulation. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal.

Never return spills to original containers for re-use.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Provide appropriate exhaust ventilation at places where dust is formed. Do not breathe dust. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Pregnant or breastfeeding women must not handle this product. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container. Store in a well-ventilated place.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Manganese (CAS 7439-96-5)	Ceiling	5 mg/m ³	Fume.
Molybdenum (CAS 7439-98-7)	PEL	15 mg/m ³	Total dust.
Nickel (CAS 7440-02-0)	PEL	1 mg/m ³	
Silica (CAS 14808-60-7)	PEL	0.05 mg/m ³	Respirable dust.

US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Silica (CAS 14808-60-7)	TWA	0.1 mg/m ³	Respirable.
		2.4 mppcf	Respirable.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Manganese (CAS 7439-96-5)	TWA	0.1 mg/m ³	Inhalable fraction.
		0.02 mg/m ³	Respirable fraction.
Molybdenum (CAS 7439-98-7)	TWA	3 mg/m ³	Respirable fraction.
		10 mg/m ³	Inhalable fraction.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Nickel (CAS 7440-02-0)	TWA	1.5 mg/m ³	Inhalable fraction.
Silica (CAS 14808-60-7)	TWA	0.025 mg/m ³	Respirable fraction.
Tungsten (CAS 7440-33-7)	TWA	3 mg/m ³	Respirable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Manganese (CAS 7439-96-5)	STEL	3 mg/m ³	Fume.
	TWA	1 mg/m ³	Fume.
Nickel (CAS 7440-02-0)	TWA	0.015 mg/m ³	
Silica (CAS 14808-60-7)	TWA	0.05 mg/m ³	Respirable dust.
Tungsten (CAS 7440-33-7)	STEL	10 mg/m ³	
	TWA	5 mg/m ³	

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

Components	Type	Value	Form
Manganese (CAS 7439-96-5)	PEL	0.2 mg/m ³	
		0.2 mg/m ³	Fume.
	STEL	3 mg/m ³	Fume.
Molybdenum (CAS 7439-98-7)	PEL	3 mg/m ³	Respirable fraction.
		10 mg/m ³	Total dust.
Nickel (CAS 7440-02-0)	PEL	0.5 mg/m ³	
Silica (CAS 14808-60-7)	PEL	0.05 mg/m ³	Respirable dust.
Tungsten (CAS 7440-33-7)	PEL	5 mg/m ³	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposures below the recommended exposure limits.

Individual protection measures, such as personal protective equipment**Eye/face protection**

Wear approved safety glasses, goggles, face shield and/or welder's helmet when risk of eye injury is present, particularly during operations that generate dust, mist or fume.

Skin protection**Hand protection**

Wear gloves to prevent contact with particulate or solutions. Wear gloves to prevent metal cuts and skin abrasions during handling.

Other

Protective overgarments or work clothing must be worn by persons who may become contaminated with particulate during activities.

Respiratory protection

When airborne exposures exceed or have the potential to exceed the occupational exposure limits, approved respirators must be used as specified by an Industrial Hygienist or other qualified professional. Respirator users must be medically evaluated to determine if they are physically capable of wearing a respirator. Quantitative and/or qualitative fit testing and respirator training must be satisfactorily completed by all personnel prior to respirator use. Users of tight fitting respirators must be clean shaven on those areas of the face where the respirator seal contacts the face. Use pressure-demand airline respirators when performing jobs with high potential exposures such as changing filters in a baghouse air cleaning device.

Thermal hazards	Not applicable.
General hygiene considerations	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Solid. Various shapes.
Color	White. Off-white. Grey. Gold.
Odor	None.
Odor threshold	Not applicable.
pH	Not applicable.
Melting point/freezing point	3722 °F (2050 °C) estimated / Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	None known.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not applicable.
Explosive limit - lower (%) temperature	Not applicable.
Explosive limit - upper (%)	Not applicable.
Explosive limit - upper (%) temperature	Not applicable.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	Not applicable.
Solubility(ies)	
Solubility (water)	Insoluble.
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.
Other information	
Density	3.95 g/cm ³ estimated
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Chlorine.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. Dust may irritate respiratory system.
Skin contact	Dust or powder may irritate the skin. May cause an allergic skin reaction.
Eye contact	Dust may irritate the eyes.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics Dusts may irritate the respiratory tract, skin and eyes. May cause an allergic skin reaction. Dermatitis. Rash.

Information on toxicological effects

Acute toxicity	May cause an allergic skin reaction.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

Nickel (CAS 7440-02-0)	2B Possibly carcinogenic to humans.
Silica (CAS 14808-60-7)	1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Silica (CAS 14808-60-7)	Cancer
-------------------------	--------

US. National Toxicology Program (NTP) Report on Carcinogens

Nickel (CAS 7440-02-0)	Known To Be Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.
Silica (CAS 14808-60-7)	Known To Be Human Carcinogen.

Reproductive toxicity	May damage fertility or the unborn child.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful. Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species		Test Results
Metallized Alumina Ceramic			
Aquatic			
Crustacea	EC50	Daphnia	2000 mg/l, 48 hours estimated
Fish	LC50	Fish	897.9192 mg/l, 96 hours estimated

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	No data available.
Mobility in soil	No data available.
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Nickel (CAS 7440-02-0) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Silica (CAS 14808-60-7) Cancer
lung effects
immune system effects
kidney effects

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous chemical No (Exempt)

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.
Manganese	7439-96-5	0 - 2
Nickel	7440-02-0	0 - 10

