



PRODUCT INFORMATION SHEET

MATERION

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	Nickel Aluminum Targets
Registration number	-
Document number	G36
Synonyms	None.
Issue date	08-February-2019
Version number	03
Revision date	23-August-2021
Supersedes date	12-February-2021

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Manufacture of computer, electronic and optical products, electrical equipment Scientific research and development Manufacturing of Metal Parts
Uses advised against	Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Consumer uses: Private households (= general public = consumers)

1.3. Details of the supplier of the product information sheet

Supplier

Company name	Materion Advanced Materials
Address	6070 Parkland Boulevard United States
Division	
Telephone	1.216.383.4019
e-mail	ehs@materion.com
Contact person	Theodore Knudson

1.4. Emergency telephone number

See Section 16.

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.
Carcinogenicity	Category 2	H351 - Suspected of causing cancer.
Specific target organ toxicity - repeated exposure	Category 1 (Respiratory system)	H372 - Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.

Hazard summary

May cause an allergic skin reaction. Suspected of causing cancer. Causes damage to organs through prolonged or repeated exposure.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Aluminium, NICKEL POWDER; [PARTICLE DIAMETER < 1MM]

Hazard pictograms



Signal word Danger

Hazard statements

H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H372	Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.

Precautionary statements

Prevention

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P264	Wash thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Response

P302 + P350	If on skin: Wash with plenty of water.
P304 + P340	If inhaled: Remove person to fresh air and keep comfortable for breathing.
P308 + P313	If exposed or concerned: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.

Storage

P405	Store locked up.
------	------------------

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Supplemental label information

For further information, please contact the Product Stewardship Department at +1.216.383.4019.

2.3. Other hazards

Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
NICKEL POWDER; [PARTICLE DIAMETER < 1MM]	80 - 98	7440-02-0 231-111-4	01-2119438727-29-0049	028-002-00-7	
Classification: Skin Sens. 1;H317, STOT SE 3;H335, Carc. 2;H351, STOT RE 2;H373					7,S
Aluminium	2 - 20	7429-90-5 231-072-3	01-2119529243-45-0056	013-002-00-1	
Classification: -					T

SECTION 4: First aid measures

General information

If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison centre or doctor/physician if you feel unwell.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction. May cause respiratory irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing media Powder. Dry sand.

Unsuitable extinguishing media Carbon dioxide (CO₂).

5.2. Special hazards arising from the substance or mixture None known.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear suitable protective equipment.

Special firefighting procedures Move containers from fire area if you can do so without risk.

Specific methods Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Keep unnecessary personnel away. For personal protection, see section 8 of the PIS.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the PIS.

6.2. Environmental precautions Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Stop the flow of material, if this is without risk. For waste disposal, see section 13 of the PIS.

6.4. Reference to other sections For personal protection, see section 8. For waste disposal, see section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Do not handle until all safety precautions have been read and understood. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities Store locked up. Store away from incompatible materials (see Section 10 of the PIS).

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	MAK	5 mg/m ³	Respirable fraction.
		10 mg/m ³	Inhalable fraction.
	STEL	20 mg/m ³	Inhalable fraction.
		10 mg/m ³	Respirable fraction.

Austria. TRK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	STEL	2 mg/m ³	Inhalable dust.
	TWA	0,5 mg/m ³	Inhalable dust.

Belgium. Exposure Limit Values

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m ³	

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	2 mg/m ³	
		10 mg/m ³	Dust.
		1,5 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,05 mg/m ³	

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	MAC	4 mg/m ³	Respirable dust.
		10 mg/m ³	Total dust.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	MAC	0,5 mg/m ³	

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m ³	

Czech Republic. OELs. Government Decree 361

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	10 mg/m ³	Dust.
	Ceiling	1 mg/m ³	Aerosol, inhalable.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m ³	Aerosol, inhalable.

Denmark. Exposure Limit Values

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TLV	5 mg/m ³	Dust and fume.
		5 mg/m ³	Fume.
		2 mg/m ³	Respirable dust and/or fume.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TLV	0,05 mg/m ³	Dust.

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	4 mg/m ³	Fine dust, respiratory fraction
		10 mg/m ³	Total dust.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m ³	

Finland. Workplace Exposure Limits

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1,5 mg/m ³	Welding fume.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,01 mg/m ³	Respirable.

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	VME	5 mg/m3	Dust.
Regulatory status: Indicative limit (VL)			
		5 mg/m3	Welding fume.
Regulatory status: Indicative limit (VL)			
		10 mg/m3	
Regulatory status: Indicative limit (VL)			
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	VME	1 mg/m3	
Regulatory status: Indicative limit (VL)			

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	4 mg/m3	Inhalable dust.
		1,5 mg/m3	Respirable dust.

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	AGW	10 mg/m3	Inhalable fraction.
		1,25 mg/m3	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	AGW	0,03 mg/m3	Inhalable fraction.
		0,006 mg/m3	Respirable fraction.

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m3	Inhalable
		10 mg/m3	Welding fume.
		10 mg/m3	Pyrophoric powder.
		10 mg/m3	Respirable.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m3	

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	6 mg/m3	Respirable.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	Ceiling	0,1 mg/m3	

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	STEL	10 mg/m3	Dust.
	TWA	5 mg/m3	Dust.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,05 mg/m3	Dust.

Ireland. Occupational Exposure Limits

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 ppm	Respirable dust.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m3	

Italy. Occupational Exposure Limits Components

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1,5 mg/m ³	Inhalable fraction.

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
Aluminium (CAS 7429-90-5)	TWA	2 mg/m ³
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,05 mg/m ³

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m ³	Inhalable fraction.
		2 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m ³	

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TLV	5 mg/m ³	Welding fume.
		5 mg/m ³	Pyrophoric powder.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TLV	0,05 mg/m ³	

Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	2,5 mg/m ³	Inhalable fraction.
		1,2 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,25 mg/m ³	

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1,5 mg/m ³	Inhalable fraction.

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	STEL	3 mg/m ³	Fume.
		10 mg/m ³	Dust.
	TWA	3 mg/m ³	Dust.
		1 mg/m ³	Fume.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	STEL	0,5 mg/m ³	
	TWA	0,1 mg/m ³	

Slovakia. OELs for carcinogens and mutagens. Regulation No. 46/2002 on carcinogenic and mutagenic substances

Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,05 mg/m ³	Inhalable fraction.

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	4 mg/m ³	Inhalable fraction.
		1,5 mg/m ³	Respirable fraction.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	10 mg/m ³	Inhalable fraction.
		1,25 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,006 mg/m ³	Respirable fraction.

Spain. Occupational Exposure Limits

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m ³	Welding fume.
		10 mg/m ³	Dust.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m ³	

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m ³	Total dust.
		2 mg/m ³	Respirable dust.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m ³	Total dust.

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	3 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m ³	Inhalable fraction.

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	4 mg/m ³	Respirable dust.
		10 mg/m ³	Inhalable dust.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m ³	

Biological limit values**Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)**

Components	Value	Determinant	Specimen	Sampling Time
Aluminium (CAS 7429-90-5)	200 mg/l	Aluminium	Urine	*

* - For sampling details, please see the source document.

Czech Republic. Limit Values for Indicators of Biological Exposure Tests in Urine and Blood, Annex 2, Tables 1 and 2, Government Decree 432/2003 Sb.

Components	Value	Determinant	Specimen	Sampling Time
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	0,077 µmol/mmol	Nickel	Creatinine in urine	*
	0,04 mg/g	Nickel	Creatinine in urine	*

* - For sampling details, please see the source document.

Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV) , Social Affairs and Ministry of Health Components

Components	Value	Determinant	Specimen	Sampling Time
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	0,1 umol/l	Nickel	Urine	*

* - For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling Time
Aluminium (CAS 7429-90-5)	50 µg/g	Aluminium	Urine	*

* - For sampling details, please see the source document.

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling Time
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	0,02 mg/g	Nickel	Creatinine in urine	*

	0,038 µmol/mmol	Nickel	Creatinine in urine	*
--	-----------------	--------	---------------------	---

* - For sampling details, please see the source document.

Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2

Components	Value	Determinant	Specimen	Sampling Time
Aluminium (CAS 7429-90-5)	60 µg/g	Aluminium	Creatinine in urine	*

* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling Time
Aluminium (CAS 7429-90-5)	60 µg/g	Aluminium	Creatinine in urine	*

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	45 µg/l	Nickel	Urine	*
---	---------	--------	-------	---

* - For sampling details, please see the source document.

Recommended monitoring procedures Follow standard monitoring procedures.

Derived no effect levels (DNELs) Not available.

Predicted no effect concentrations (PNECs) Not available.

Exposure guidelines

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

- **Hand protection** Wear gloves to prevent metal cuts and skin abrasions during handling.

- **Other** Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Observe any medical surveillance requirements. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.
Environmental exposure controls	Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Solid.
Form	Particulate.
Colour	Light grey.
Odour	None.
Odour threshold	Not applicable.
pH	Not applicable.
Melting point/freezing point	660 °C (1220 °F) estimated / Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	None known.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not applicable.
Explosive limit - lower (%) temperature	Not applicable.
Explosive limit – upper (%)	Not applicable.
Explosive limit - upper (%) temperature	Not applicable.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	Not applicable.
Solubility(ies)	
Solubility (water)	Insoluble.
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.

9.2. Other information

Density	7,85 g/cm ³ estimated
----------------	----------------------------------

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. Contact with incompatible materials.
10.5. Incompatible materials	Strong acids.
10.6. Hazardous decomposition products	No hazardous decomposition products are known.

SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.
Information on likely routes of exposure	
Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Not likely, due to the form of the product.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	May cause an allergic skin reaction.
11.1. Information on toxicological effects	
Acute toxicity	Not known.
Skin corrosion/irritation	Not relevant, due to the form of the product.
Serious eye damage/eye irritation	Not likely, due to the form of the product.
Respiratory sensitisation	Not a respiratory sensitizer.
Skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Not classified.
Carcinogenicity	Suspected of causing cancer.
Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)	
	Not listed.
IARC Monographs. Overall Evaluation of Carcinogenicity	
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	2B Possibly carcinogenic to humans.
Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)	
Aluminium (CAS 7429-90-5)	Carcinogenic, Category 1A
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	Carcinogenic, Category 2.
Reproductive toxicity	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	Causes damage to organs through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Mixture versus substance information	Not applicable.
Other information	Not available.

SECTION 12: Ecological information

12.1. Toxicity Based on available data, the classification criteria are not met for hazardous to the aquatic environment.

Product	Species	Test Results
Nickel Aluminum Targets		
Aquatic		
<i>Acute</i>		
Fish	LC50 Fish	0,0612 mg/l, 4 days estimated
Components	Species	Test Results
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)		
Aquatic		
<i>Acute</i>		
Fish	LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0,06 mg/l, 4 days

12.2. Persistence and degradability No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential	No data available.
Partition coefficient n-octanol/water (log Kow)	Not available.
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.
12.6. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

12.7. Additional information

Estonia Dangerous substances in soil Data

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	Nickel (Ni) 150 mg/kg
	Nickel (Ni) 50 mg/kg
	Nickel (Ni) 500 mg/kg

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN3178
14.2. UN proper shipping name	FLAMMABLE SOLID, INORGANIC, N.O.S.
14.3. Transport hazard class(es)	
Class	4.1
Subsidiary risk	-
Label(s)	4.1
Hazard No. (ADR)	40
Tunnel restriction code	E
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Not available.

RID

14.1. UN number	UN3178
14.2. UN proper shipping name	FLAMMABLE SOLID, INORGANIC, N.O.S.
14.3. Transport hazard class(es)	
Class	4.1
Subsidiary risk	-
Label(s)	4.1
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN3178
------------------------	--------

14.2. UN proper shipping name FLAMMABLE SOLID, INORGANIC, N.O.S.

14.3. Transport hazard class(es)

Class 4.1

Subsidiary risk -

Label(s) 4.1

14.4. Packing group III

14.5. Environmental hazards No.

14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

14.1. UN number UN3178

14.2. UN proper shipping name Flammable solid, inorganic, n.o.s.

14.3. Transport hazard class(es)

Class 4.1

Subsidiary risk -

14.4. Packing group III

14.5. Environmental hazards No.

ERG Code 3L

14.6. Special precautions for user Not available.

Other information

Passenger and cargo aircraft Allowed with restrictions.

Cargo aircraft only Allowed with restrictions.

IMDG

14.1. UN number UN3178

14.2. UN proper shipping name FLAMMABLE SOLID, INORGANIC, N.O.S.

14.3. Transport hazard class(es)

Class 4.1

Subsidiary risk -

14.4. Packing group III


14.5. Environmental hazards

Marine pollutant No.

EmS F-A, S-G

14.6. Special precautions for user Not available.

ADN; ADR; IATA; IMDG; RID



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Aluminium (CAS 7429-90-5)

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Aluminium (CAS 7429-90-5)

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended.

National regulations

According to Directive 92/85/EEC as amended, pregnant women should not work with the product, if there is the least risk of exposure.

Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended. Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

Not available.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculator methods and test data, if available.

Training information

Follow training instructions when handling this material.

Further information

Transportation Emergency
Call Chemtrec at:
International: 703.741.5970
Spain: 900.868.538
Switzerland: 0800.564.402

Disclaimer

Materion Advanced Materials cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use.

To avoid any misunderstandings or incorrect assumptions by the receiver of the safety information, it should be made clear that the supplied information is not in the form of a Safety Data Sheet (SDS), but is actually a voluntary Product Information Sheet closely following the guidelines of the Safety Data Sheet – COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 (REACH/SDS).

Other information

Revised information in Section 16.