



SAFETY DATA SHEET

MATERION

1. Identification

Product identifier C18000

Other means of identification

SDS number L03

Synonyms Copper Alloy

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Materion Brush Inc.

Address 6070 Parkland Boulevard
Mayfield Heights, OH 44124
United States

Telephone 1.800.862.4118

Website www.materion.com

E-mail ehs@materion.com

Contact person Theodore Knudson

Emergency phone number 1.800.862.4118

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Sensitization, skin Category 1
Carcinogenicity Category 2
Specific target organ toxicity, repeated exposure Category 1 (Respiratory system)

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause an allergic skin reaction. Suspected of causing cancer. Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.

Precautionary statement

Prevention Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Contaminated work clothing must not be allowed out of the workplace. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory protection.

Response If on skin: Wash with plenty of water. If exposed or concerned: Get medical advice/attention. If skin irritation or rash occurs: Get medical advice/attention. Wash contaminated clothing before reuse. Wash contaminated clothing before reuse.

Storage Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC) None known.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Copper		7440-50-8	95.5 - 97.4
Nickel		7440-02-0	2 - 3
Silicon		7440-21-3	0.4 - 0.8
Chromium		7440-47-3	0.1 - 0.6

4. First-aid measures

Inhalation	Move to fresh air. Call a physician if symptoms develop or persist.
Skin contact	Wash off with soap and water. Get medical attention if irritation develops and persists.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
Most important symptoms/effects, acute and delayed	Exposure may cause temporary irritation, redness, or discomfort.
Indication of immediate medical attention and special treatment needed	Treat symptomatically.
General information	Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

5. Fire-fighting measures

Suitable extinguishing media	Powder. Dry sand.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
Specific hazards arising from the chemical	None known.
Special protective equipment and precautions for firefighters	Wear suitable protective equipment.
Fire fighting equipment/instructions	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away.
Methods and materials for containment and cleaning up	Stop the flow of material, if this is without risk. Following product recovery, flush area with water.
Environmental precautions	Collect spillage. Prevent further leakage or spillage if safe to do so.

7. Handling and storage

Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation. Avoid breathing dust/fume/gas/mist/vapors/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up.

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	PEL	1 mg/m3	
Copper (CAS 7440-50-8)	PEL	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
Nickel (CAS 7440-02-0)	PEL	1 mg/m3	
Silicon (CAS 7440-21-3)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.

US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0.5 mg/m3	Inhalable fraction.
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
		0.2 mg/m3	Fume.
Nickel (CAS 7440-02-0)	TWA	1.5 mg/m3	Inhalable fraction.

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	TWA	0.5 mg/m3	
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
Nickel (CAS 7440-02-0)	TWA	0.015 mg/m3	
Silicon (CAS 7440-21-3)	TWA	5 mg/m3	Respirable.
		10 mg/m3	Total

US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

Components	Type	Value	Form
Chromium (CAS 7440-47-3)	PEL	0.5 mg/m3	
Copper (CAS 7440-50-8)	PEL	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
Nickel (CAS 7440-02-0)	PEL	0.5 mg/m3	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station.

Individual protection measures, such as personal protective equipment

Eye/face protection Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear gloves to prevent metal cuts and skin abrasions during handling.

Other Wear suitable protective clothing.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking.

9. Physical and chemical properties

Appearance

Physical state	Solid.
Form	Various shapes.
Color	Red
Odor	None.
Odor threshold	Not applicable.
pH	Not applicable.
Melting point/freezing point	1981.4 °F (1083 °C) estimated / Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	None known.
Upper/lower flammability or explosive limits	
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	Not applicable.
Vapor density	Not applicable.
Relative density	Not applicable.
Solubility(ies)	
Solubility (water)	Insoluble.
Partition coefficient (n-octanol/water)	Not applicable.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.
Other information	
Density	8.88 g/cm ³ estimated
Explosive properties	Not explosive.
Oxidizing properties	Not oxidizing.

10. Stability and reactivity

Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Strong oxidizing agents.
Hazardous decomposition products	No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Not likely, due to the form of the product.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics	May cause an allergic skin reaction.
Information on toxicological effects	
Acute toxicity	May cause an allergic skin reaction.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Not likely, due to the form of the product.
Respiratory or skin sensitization	
Respiratory sensitization	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitization	May cause an allergic skin reaction.
Germ cell mutagenicity	No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.
Carcinogenicity	Suspected of causing cancer.
IARC Monographs. Overall Evaluation of Carcinogenicity	
Chromium (CAS 7440-47-3)	3 Not classifiable as to carcinogenicity to humans.
Nickel (CAS 7440-02-0)	2B Possibly carcinogenic to humans.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	
Not listed.	
US. National Toxicology Program (NTP) Report on Carcinogens	
Nickel (CAS 7440-02-0)	Known To Be Human Carcinogen. Reasonably Anticipated to be a Human Carcinogen.
Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Not classified.
Specific target organ toxicity - repeated exposure	May cause damage to organs (respiratory system) through prolonged or repeated exposure.
Aspiration hazard	Not an aspiration hazard.
Chronic effects	Prolonged exposure may cause chronic effects.

12. Ecological information

Ecotoxicity

Product		Species	Test Results
C18000			
Aquatic			
<i>Acute</i>			
Fish	LC50	Fish	0.0333 mg/l, 96 hours estimated
Components		Species	Test Results
Copper (CAS 7440-50-8)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Blue crab (<i>Callinectes sapidus</i>)	0.0031 mg/l
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	0.0219 - 0.0446 mg/l, 96 hours

Components	Species	Test Results
Nickel (CAS 7440-02-0)		
Aquatic		
<i>Acute</i>		
Fish	LC50 Rainbow trout,donaldson trout (Oncorhynchus mykiss)	0.06 mg/l, 4 days

* Estimates for product may be based on additional component data not shown.

Persistence and degradability	No data is available on the degradability of this product.
Bioaccumulative potential	Not available.
Mobility in soil	Not available.
Other adverse effects	Not available.

13. Disposal considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Local disposal regulations	Dispose in accordance with all applicable regulations.
Hazardous waste code	The waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

14. Transport information

DOT	Not regulated as dangerous goods.
IATA	Not regulated as dangerous goods.
IMDG	Not regulated as dangerous goods.

15. Regulatory information

US federal regulations	All components are on the U.S. EPA TSCA Inventory List. This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200.
Toxic Substances Control Act (TSCA)	
TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4)	
Chromium (CAS 7440-47-3)	Listed.
Copper (CAS 7440-50-8)	Listed.
Nickel (CAS 7440-02-0)	Listed.
SARA 304 Emergency release notification	Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)	Not listed.

