

PRODUCT INFORMATION SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	Aluminum Silicon Alloy
Registration number	-
Document number	L64
Synonyms	AMC4632, AMC4632E, AMC4631, AMC4630
Issue date	27-August-2019
Version number	02
Revision date	04-May-2021

1.3. Details of the supplier of the product information sheet

Supplier

Company name Materion Aerospace Metals Composites
Address 1 R A E Road, Farnborough
Hampshire GU14 6XE
UK

Division

Telephone +1.216.383.4019
e-mail ehs@materion.com
Contact person Theodore Knudson

1.4. Emergency telephone number +1.216.383.4019

Supersedes date 27-August-2019

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Industrial uses: Uses of substances as such or in preparations at industrial sites
Manufacture of basic metals, including alloys
Manufacture of computer, electronic and optical products, electrical equipment
General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment
Electricity, steam, gas water supply and sewage treatment
Scientific research and development
Other: Manufacture of medical and defense equipment

Uses advised against Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
Consumer uses: Private households (= general public = consumers)

1.3. Details of the supplier of the safety data sheet

Supplier

Company name Materion Aerospace Metals Composites
Address 1 R A E Road, Farnborough
Hampshire GU14 6XE
UK

Division

Telephone +1.216.383.4019
e-mail ehs@materion.com
Contact person Theodore Knudson

1.4. Emergency telephone number +1.216.383.4019

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin sensitisation Category 1 H317 - May cause an allergic skin reaction.

Carcinogenicity

Category 2

H351 - Suspected of causing cancer.

Specific target organ toxicity - repeated exposure

Category 1 (Respiratory system)

H372 - Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.

Hazard summary Not available.**2.2. Label elements****Label according to Regulation (EC) No. 1272/2008 as amended****Contains:** Aluminium, COPPER FLAKES (COATED WITH ALIPHATIC ACID), Iron, magnesium, powder or turnings, NICKEL POWDER; [PARTICLE DIAMETER < 1MM], Silicon**Hazard pictograms****Signal word** Danger**Hazard statements**

H317 May cause an allergic skin reaction.
 H351 Suspected of causing cancer.
 H372 Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.

Precautionary statements**Prevention**

P201 Obtain special instructions before use.
 P202 Do not handle until all safety precautions have been read and understood.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P264 Wash thoroughly after handling.
 P270 Do not eat, drink or smoke when using this product.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P273 Avoid release to the environment.
 P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P302 + P350 If on skin: Wash with plenty of water.
 P308 + P313 If exposed or concerned: Get medical advice/attention.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.
 P363 Wash contaminated clothing before reuse.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

For further information, please contact the Product Stewardship Department at +1.216.383.4019.

2.3. Other hazards None known.**SECTION 3: Composition/information on ingredients****3.2. Mixtures****General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Aluminium	71 - 87	7429-90-5 231-072-3	-	013-002-00-1	
Classification: Aquatic Acute 1;H400, Aquatic Chronic 1;H410					T
Silicon	9 - 24	7440-21-3 231-130-8	-	-	
Classification: -					
COPPER FLAKES (COATED WITH ALIPHATIC ACID)	1,8 - 2,2	7440-50-8 231-159-6	01-2119480154-42-0080	-	
Classification: -					

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Iron	1,6 - 2	7439-89-6 231-096-4	-	-	
Classification: STOT RE 1;H372					
NICKEL POWDER; [PARTICLE DIAMETER < 1MM]	0,7 - 1,1	7440-02-0 231-111-4	01-2119438727-29-0049	028-002-00-7	
Classification: Skin Sens. 1;H317, STOT SE 3;H335, Carc. 2;H351, STOT RE 2;H373					7,S
magnesium, powder or turnings	0,5 - 0,7	7439-95-4 231-104-6	-	-	
Classification: Flam. Sol. 1;H228, Self-heat. 2;H252, Water-React. 2;H261					T

SECTION 4: First aid measures

General information If exposed or concerned: get medical attention/advice. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Wash off with soap and water. Get medical attention if irritation develops and persists.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing media Powder. Dry sand.

Unsuitable extinguishing media Water. Do not use water jet as an extinguisher, as this will spread the fire. Carbon dioxide (CO₂).

5.2. Special hazards arising from the substance or mixture

Not available.

5.3. Advice for firefighters

Special protective equipment for firefighters Wear suitable protective equipment. Pressure-demand self-contained breathing apparatus must be worn by firefighters or any other persons potentially exposed to the particulate released during or after a fire.

Special firefighting procedures Water runoff can cause environmental damage.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel As supplied, this product poses no special release issues.

For emergency responders As supplied, this product poses no special release issues. Keep unnecessary personnel away.

6.2. Environmental precautions

Avoid release to the environment. Contact local authorities in case of spillage to drain/aquatic environment. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Collect spillage. Prevent product from entering drains. Prevent entry into waterways, sewer, basements or confined areas.

6.4. Reference to other sections

For personal protection, see section 8 of the PIS. For waste disposal, see section 13 of the PIS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not taste or swallow. Avoid contact with skin. Avoid contact with eyes. Avoid prolonged exposure. Use personal protective equipment as required. When using, do not eat, drink or smoke. Wash hands thoroughly after handling. Use appropriate container to avoid environmental contamination. Do not empty into drains. Wear suitable gloves.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Use appropriate container to avoid environmental contamination. Keep container tightly closed. Store in a cool, dry place out of direct sunlight. Store in a dry place. Keep out of the reach of children.

7.3. Specific end use(s)

Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m ³	Inhalable fraction.
		2 mg/m ³	Respirable fraction.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	1 mg/m ³	Inhalable fraction.
		0,2 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m ³	

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Wear approved safety glasses, goggles, face shield and/or welder's helmet when risk of eye injury is present, particularly during operations that generate dust, mist or fume.

Skin protection

- Hand protection

Wear gloves to prevent contact with particulate or solutions. Wear gloves to prevent metal cuts and skin abrasions during handling.

- Other

Protective overgarments or work clothing must be worn by persons who may become contaminated with particulate during activities.

Respiratory protection

When airborne exposures exceed or have the potential to exceed the occupational exposure limits, approved respirators must be used as specified by an Industrial Hygienist or other qualified professional. Respirator users must be medically evaluated to determine if they are physically capable of wearing a respirator. Quantitative and/or qualitative fit testing and respirator training must be satisfactorily completed by all personnel prior to respirator use. Users of tight fitting respirators must be clean shaven on those areas of the face where the respirator seal contacts the face. Use pressure-demand airline respirators when performing jobs with high potential exposures such as changing filters in a baghouse air cleaning device.

Thermal hazards

Not applicable.

Hygiene measures

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls

Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION 9: Physical and chemical properties**9.1. Information on basic physical and chemical properties****Appearance**

Physical state	Solid.
Form	Solid.
Colour	Silver. Grey metallic.

Odour None.**Odour threshold** Not applicable.**pH** Not applicable.**Melting point/freezing point** > 548 °C (> 1018,4 °F) estimated / Not applicable.**Initial boiling point and boiling range** Not applicable.**Flash point** Not applicable.**Evaporation rate** Not applicable.**Flammability (solid, gas)** None known.**Upper/lower flammability or explosive limits****Flammability limit - lower (%)** Not applicable.**Flammability limit - upper (%)** Not applicable.**Explosive limit - lower (%)** Not applicable.**Explosive limit – upper (%)** Not applicable.**Vapour pressure** Not applicable.**Vapour density** Not applicable.**Relative density** Not applicable.**Solubility(ies)****Solubility (water)** Insoluble**Partition coefficient (n-octanol/water)** Not applicable.**Auto-ignition temperature** Not applicable.**Decomposition temperature** Not applicable.**Viscosity** Not applicable.**Explosive properties** Not explosive.**Oxidising properties** Not oxidising.**9.2. Other information****Density** 2,80 g/cm³ estimated**Specific gravity** 2,8 estimated**SECTION 10: Stability and reactivity****10.1. Reactivity** Not available.**10.2. Chemical stability** Material is stable under normal conditions.**10.3. Possibility of hazardous reactions** No dangerous reaction known under conditions of normal use.**10.4. Conditions to avoid** Contact with incompatible materials.**10.5. Incompatible materials** Strong oxidising agents.**10.6. Hazardous decomposition products** No hazardous decomposition products are known.**SECTION 11: Toxicological information****General information** Occupational exposure to the substance or mixture may cause adverse effects.**Information on likely routes of exposure****Inhalation** Prolonged inhalation may be harmful.

Skin contact No adverse effects due to skin contact are expected.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms Direct contact with eyes may cause temporary irritation.

11.1. Information on toxicological effects

Acute toxicity Not applicable.

Skin corrosion/irritation Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye irritation Direct contact with eyes may cause temporary irritation.

Respiratory sensitisation Not a respiratory sensitizer.

Skin sensitisation This product is not expected to cause skin sensitisation.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

IARC Monographs. Overall Evaluation of Carcinogenicity

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0) 2B Possibly carcinogenic to humans.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity - single exposure Not classified.

Specific target organ toxicity - repeated exposure Causes damage to organs () through prolonged or repeated exposure by inhalation.

Aspiration hazard Not an aspiration hazard.

Mixture versus substance information No information available.

Other information Not available.

SECTION 12: Ecological information

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Product	Species	Test Results
---------	---------	--------------

Aluminum Silicon Alloy

Aquatic

Acute

Fish	LC50	Fish	1,475 mg/l, 96 hours estimated
------	------	------	--------------------------------

Components

Species

Test Results

COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)

Aquatic

Acute

Crustacea	EC50	Blue crab (<i>Callinectes sapidus</i>)	0,0031 mg/l
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>)	0,0219 - 0,0446 mg/l, 96 hours

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)

Aquatic

Acute

Fish	LC50	Rainbow trout, donaldson trout (<i>Oncorhynchus mykiss</i>)	0,06 mg/l, 4 days
------	------	---	-------------------

* Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability No data is available on the degradability of this product.

12.3. Bioaccumulative potential No data available.

Partition coefficient n-octanol/water (log Kow) Not available.

Bioconcentration factor (BCF) Not available.

12.4. Mobility in soil	No data available.
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.
12.6. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Aluminium (CAS 7429-90-5)
 COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)
 NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Aluminium (CAS 7429-90-5)

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Aluminium (CAS 7429-90-5)

COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)

magnesium, powder or turnings (CAS 7439-95-4)

Other regulations

The product is classified and labelled in accordance with EC directives or respective national laws. Pregnant women should not work with the product, if there is the least risk of exposure.

National regulations

Follow national regulation for work with chemical agents. Young people under 18 years old are not allowed to work with this product according to EU Directive 94/33/EC on the protection of young people at work, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

Not available.

References

Not available.

Information on evaluation method leading to the classification of mixture

Not available.

Full text of any H-statements not written out in full under Sections 2 to 15

H228 Flammable solid.

H252 Self-heating in large quantities; may catch fire.

H261 In contact with water releases flammable gases.

H317 May cause an allergic skin reaction.

H335 May cause respiratory irritation.

H351 Suspected of causing cancer.

H372 Causes damage to organs through prolonged or repeated exposure by inhalation.

H373 May cause damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

Revision information

None.

Training information

Not available.

Disclaimer

This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.

To avoid any misunderstandings or incorrect assumptions by the receiver of the safety information, it should be made clear that the supplied information is not in the form of a Safety Data Sheet (SDS), but is actually a voluntary Product Information Sheet closely following the guidelines of the Safety Data Sheet – COMMISSION REGULATION (EU) No 453/2010 of 20 May 2010 (REACH/SDS).