MATERION

PRODUCT INFORMATION SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or

Amorphous Alloy LM-601

designation of the mixture

Registration number Document number N04 **Synonyms** None.

28-March-2016 **Issue date**

Version number 02

Revision date 19-February-2018 Supersedes date 28-March-2016

1.3. Details of the supplier of the product information sheet

Supplier

Company name Materion Brush Inc. **Address** 6070 Parkland Boulevard

Mayfield Heights, OH 44124

United States

Division

Telephone 1.216.383.4019 e-mail ehs@materion.com Theodore Knudson **Contact person** 1.4. Emergency telephone 1.216.383.4019

number

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Not available. None known. Uses advised against

1.3. Details of the supplier of the product information sheet

Supplier

Company name Materion Brush Inc. **Address** 6070 Parkland Boulevard

Mayfield Heights, OH 44124

United States

Division

Telephone 1.216.383.4019 ehs@materion.com e-mail Contact person Theodore Knudson 1.4. Emergency telephone

1.216.383.4019

number

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin sensitisation Category 1 H317 - May cause an allergic skin

reaction.

Carcinogenicity Category 2 H351 - Suspected of causing

cancer.

Specific target organ toxicity - repeated

exposure

Category 1 (Respiratory system)

(respiratory system) through prolonged or repeated exposure by

H372 - Causes damage to organs

inhalation.

Hazard summary Prolonged exposure may cause chronic effects.

Material name: Amorphous Alloy LM-601 PIS BELGIUM 2007 Version #: 02 Revision date: 22-July-2019 Print date: 22-July-2019 1/8

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Aluminium, Copper, Nickel, Zirconium

Hazard pictograms



Signal word Danger

Hazard statements

H317 May cause an allergic skin reaction. H351 Suspected of causing cancer.

H372 Causes damage to organs (respiratory system) through prolonged or repeated exposure by

inhalation.

Precautionary statements

Prevention

P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash hands thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P285 In case of inadequate ventilation wear respiratory protection.

Response

P308 + P313 If exposed or concerned: Get medical advice/attention.

P341 If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for

breathing.

P342 + P311 If experiencing respiratory symptoms: Call a poison centre/doctor.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label

information

For further information, please contact the Product Stewardship Department at +1.216.383.4019.

2.3. Other hazards None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

ilerai illiorillation				
Chemical name	%	CAS-No. / EC No.	REACH Registration No. Index N	lo. Notes
Zirconium	55 - 71	7440-67-7 231-176-9	- 040-002-0	00-9
Classification:			eat. 1;H251, Water-React. 2;H261, Skin 19, STOT SE 3;H335, STOT RE 1;H372	Irrit. T
Copper	25 - 35	7440-50-8 231-159-6	01-2119480154-42-0080 -	
Classification:	-			
Aluminium	2 - 5	7429-90-5 231-072-3	01-2119529243-45-0056 013-002-0	00-1
Classification:	-			Т
Nickel	2 - 5	7440-02-0 231-111-4	01-2119438727-29-0049 028-002-0	00-7
Classification:	Skin Sens. 1;H317, STO	T SE 3;H335, Carc.	2;H351, STOT RE 2;H373	7,S

SECTION 4: First aid measures

General information IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice

(show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

Material name: Amorphous Alloy LM-601

2007 Version #: 02 Revision date: 22-July-2019 Print date: 22-July-2019 2 / 8

4.1. Description of first aid measures

Inhalation Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON

CENTRE or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema

or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both

acute and delayed

May cause respiratory irritation. Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing

media

Dry powder. Dry sand.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or

mixture

During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special firefighting procedures

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency

personnel

Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation.

Local authorities should be advised if significant spillages cannot be contained.

For emergency responders

Keep unnecessary personnel away.

6.2. Environmental

precautions

Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or

supervisory personnel of all environmental releases.

6.3. Methods and material for containment and cleaning up

Stop the flow of material, if this is without risk. Prevent product from entering drains. Following

product recovery, flush area with water.

6.4. Reference to other

sections

Not available.

SECTION 7: Handling and storage

7.1. Precautions for safe

handling

Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Store locked up. Store in original tightly closed container.

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Material name: Amorphous Alloy LM-601 PIS BELGIUM Print date: 22-July-2019 3/8

2007 Version #: 02 Revision date: 22-July-2019

Occupational exposure limits

Belgium. Exposure Limit Values.

Components	Туре	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
		0,2 mg/m3	Fume.
Nickel (CAS 7440-02-0)	TWA	1 mg/m3	
Zirconium (CAS 7440-67-7)	STEL	10 mg/m3	
	TWA	5 mg/m3	

Biological limit values Recommended monitoring procedures

No biological exposure limits noted for the ingredient(s).

VENTILATION: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Whenever possible, the use of local exhaust ventilation or other engineering controls is the preferred method of controlling exposure to airborne particulate. Where utilized, exhaust inlets to the ventilation system must be positioned as close as possible to the source of airborne generation. Avoid disruption of the airflow in the area of a local exhaust inlet by equipment such as a man-cooling fan. Check ventilation equipment regularly to ensure it is functioning properly. Provide training on the use and operation of ventilation to all users. Use qualified professionals to design and install ventilation systems.

Derived no effect levels (DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information

Personal protection equipment should be chosen according to the CEN standards and in discussion

with the supplier of the personal protective equipment.

Eye/face protection

Wear approved safety glasses, goggles, face shield and/or welder's helmet when risk of eye injury

is present, particularly during operations that generate dust, mist or fume.

Skin protection

- Hand protection

Wear gloves to prevent contact with particulate or solutions. Wear gloves to prevent metal cuts and

skin abrasions during handling.

- Other

Protective overgarments or work clothing must be worn by persons who may become contaminated with particulate during activities.

Respiratory protection

When airborne exposures exceed or have the potential to exceed the occupational exposure limits, approved respirators must be used as specified by an Industrial Hygienist or other qualified professional. Respirator users must be medically evaluated to determine if they are physically capable of wearing a respirator. Quantitative and/or qualitative fit testing and respirator training must be satisfactorily completed by all personnel prior to respirator use. Users of tight fitting respirators must be clean shaven on those areas of the face where the respirator seal contacts the face. Use pressure-demand airline respirators when performing jobs with high potential exposures such as changing filters in a baghouse air cleaning device.

Thermal hazards Not applicable.

Hygiene measures

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure

Inform appropriate managerial or supervisory personnel of all environmental releases.

controls

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state Solid.

Material name: Amorphous Alloy LM-601 2007 Version #: 02 Revision date: 22-July-2019 Print date: 22-July-2019 4/8

PIS BELGIUM

Form Various shapes.

Colour Metallic.

Odour Not applicable.
Odour threshold Not applicable.
pH Not applicable.

Melting point/freezing point 848,89 - 898,89 °C (1560 - 1650 °F) / Not applicable.

Initial boiling point and

boiling range

Not applicable.

Flash point Not applicable.

Evaporation rate Not applicable.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower Not applicable.

(%)

Flammability limit -

upper (%)

Not applicable.

Explosive limit - lower (

%)

Not applicable.

Explosive limit – upper

(%)

Not applicable.

Vapour pressure0,26 hPa estimatedVapour densityNot applicable.Relative densityNot applicable.

Solubility(ies)

Solubility (water)Not applicable.Solubility (other)Not applicable.Partition coefficientNot available.

(n-octanol/water)

Auto-ignition temperature

Decomposition temperature

Viscosity

Explosive properties

Oxidising properties

Not applicable.

Not applicable.

Not explosive.

Not oxidising.

9.2. Other information

Density 8,24 g/cm3 estimated **Specific gravity** 8,24 estimated

SECTION 10: Stability and reactivity

10.1. Reactivity Not available.
10.2. Chemical stability Not available.
10.3. Possibility of hazardous Not available.

reactions

10.4. Conditions to avoid Contact with incompatible materials.

10.5. Incompatible materials Not available.

10.6. Hazardous Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.

decomposition products

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation May cause irritation to the respiratory system. Prolonged inhalation may be harmful.

Skin contact May cause an allergic skin reaction.

Eye contact Direct contact with eyes may cause temporary irritation.

Ingestion May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of

occupational exposure.

Material name: Amorphous Alloy LM-601

2007 Version #: 02 Revision date: 22-July-2019 Print date: 22-July-2019 5 / 8

Symptoms

May cause respiratory irritation. Coughing. Discomfort in the chest. Shortness of breath. May cause

an allergic skin reaction. Dermatitis. Rash.

11.1. Information on toxicological effects

Acute toxicity May cause an allergic skin reaction. May cause respiratory irritation. Skin corrosion/irritation Due to partial or complete lack of data the classification is not possible. Serious eye damage/eye Due to partial or complete lack of data the classification is not possible.

irritation

Respiratory sensitisation Due to partial or complete lack of data the classification is not possible. May cause allergy or

asthma symptoms or breathing difficulties if inhaled.

May cause an allergic skin reaction. Skin sensitisation

Germ cell mutagenicity Due to partial or complete lack of data the classification is not possible.

Carcinogenicity Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Nickel (CAS 7440-02-0) 2B Possibly carcinogenic to humans. Reproductive toxicity Due to partial or complete lack of data the classification is not possible.

Specific target organ toxicity May cause respiratory irritation.

- single exposure

Specific target organ toxicity - repeated exposure

May cause damage to organs through prolonged or repeated exposure.

Aspiration hazard Due to partial or complete lack of data the classification is not possible.

Mixture versus substance

information

No information available.

Other information Not available.

SECTION 12: Ecological information

No toxicity data noted for the ingredient(s). 12.1. Toxicity

Product Species		Species	Test Results	
Amorphous Alloy LM-601				
Aquatic				
Crustacea	EC50	Daphnia	0,4963 mg/l, 48 hours estimated	
Fish	LC50	Fish	6,4593 mg/l, 96 hours estimated	

^{*} Estimates for product may be based on additional component data not shown.

12.2. Persistence and

degradability

Not available.

12.3. Bioaccumulative

potential

Not available.

Partition coefficient

Not available.

n-octanol/water (log Kow)

Bioconcentration factor (BCF) Not available. 12.4. Mobility in soil Not available.

12.5. Results of PBT and

vPvB assessment

Not a PBT or vPvB substance or mixture.

12.6. Other adverse effects Not available.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some product

residues. This material and its container must be disposed of in a safe manner (see: Disposal

instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

EU waste code The Waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Disposal Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

methods/information contents/container in accordance with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

Material name: Amorphous Alloy LM-601 PIS BELGIUM Print date: 22-July-2019

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Aluminium (CAS 7429-90-5) Copper (CAS 7440-50-8) Nickel (CAS 7440-02-0)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Nickel (CAS 7440-02-0) Zirconium (CAS 7440-67-7)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Aluminium (CAS 7429-90-5) Copper (CAS 7440-50-8) Zirconium (CAS 7440-67-7)

National regulations Follow national regulation for work with chemical agents.

15.2. Chemical safety

assessment

Not available.

SECTION 16: Other information

Material name: Amorphous Alloy LM-601

List of abbreviations Not available. References Not available.

Print date: 22-July-2019 7/8

2007 Version #: 02 Revision date: 22-July-2019 **Training information**

Disclaimer

Follow training instructions when handling this material.

This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and

regulations.

Other information

Revised information in Section 2.

Material name: Amorphous Alloy LM-601

2007 Version #: 02 Revision date: 22-July-2019 Print date: 22-July-2019

8 / 8