



PRODUCT INFORMATION SHEET

MATERION

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	Amorphous Alloy LM-601
Registration number	-
Document number	N04
Synonyms	None.
Issue date	28-March-2016
Version number	04
Revision date	25-May-2021
Supersedes date	25-January-2021

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Manufacture of computer, electronic and optical products, electrical equipment Scientific research and development Other: Manufacture of medical and defense equipment
Uses advised against	Professional uses: Public domain (administration, education, entertainment, services, craftsmen) Consumer uses: Private households (= general public = consumers)

1.3. Details of the supplier of the product information sheet

Supplier

Company name	Materion Corporation
Address	6070 Parkland Boulevard Mayfield Heights, OH 44124 United States
Division	
Telephone	1.216.383.4019
e-mail	ehs@materion.com
Contact person	Theodore Knudson

1.4. Emergency telephone number 1.216.383.4019

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.
Carcinogenicity	Category 2	H351 - Suspected of causing cancer.
Specific target organ toxicity - repeated exposure	Category 1 (Respiratory system)	H372 - Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.

Environmental hazards

Hazardous to the aquatic environment, acute aquatic hazard	Category 1
Hazardous to the aquatic environment, long-term aquatic hazard	Category 1

Hazard summary Prolonged exposure may cause chronic effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains: Aluminium, COPPER FLAKES (COATED WITH ALIPHATIC ACID), NICKEL POWDER; [PARTICLE DIAMETER < 1MM], ZIRCONIUM POWDER, DRY (NON PYROPHORIC)

Hazard pictograms



Signal word

Danger

Hazard statements

H317 May cause an allergic skin reaction.
H351 Suspected of causing cancer.
H372 Causes damage to organs (respiratory system) through prolonged or repeated exposure by inhalation.

Precautionary statements

Prevention

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P260 Do not breathe dust/fume/gas/mist/vapours/spray.
P264 Wash hands thoroughly after handling.
P270 Do not eat, drink or smoke when using this product.
P280 Wear protective gloves/protective clothing/eye protection/face protection.
P285 In case of inadequate ventilation wear respiratory protection.

Response

P308 + P313 If exposed or concerned: Get medical advice/attention.
P341 If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing.
P342 + P311 If experiencing respiratory symptoms: Call a poison centre/doctor.

Storage

P405 Store locked up.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information

For further information, please contact the Product Stewardship Department at +1.216.383.4019.

2.3. Other hazards

None known.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
ZIRCONIUM POWDER, DRY (NON PYROPHORIC)	55 - 71	7440-67-7 231-176-9	-	040-002-00-9	
		Classification: Flam. Sol. 2;H228, Pyr. Sol. 1;H250, Self-heat. 1;H251, Water-React. 2;H261, Skin Irrit. 2;H315, Skin Sens. 1;H317, Eye Irrit. 2;H319, STOT SE 3;H335, STOT RE 1;H372			T
COPPER FLAKES (COATED WITH ALIPHATIC ACID)	25 - 35	7440-50-8 231-159-6	01-2119480154-42-0080	-	
		Classification: -			
Aluminium	2 - 5	7429-90-5 231-072-3	01-2119529243-45-0056	013-002-00-1	
		Classification: -			T
NICKEL POWDER; [PARTICLE DIAMETER < 1MM]	2 - 5	7440-02-0 231-111-4	01-2119438727-29-0049	028-002-00-7	
		Classification: Skin Sens. 1;H317, STOT SE 3;H335, Carc. 2;H351, STOT RE 2;H373			7,S

SECTION 4: First aid measures

General information

If exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation

Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTRE or doctor/physician if you feel unwell.

Skin contact	Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions.
Eye contact	Rinse with water. Get medical attention if irritation develops and persists.
Ingestion	Rinse mouth. Get medical attention if symptoms occur.
4.2. Most important symptoms and effects, both acute and delayed	May cause respiratory irritation. Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.
4.3. Indication of any immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards	No unusual fire or explosion hazards noted.
5.1. Extinguishing media	
Suitable extinguishing media	Dry powder. Dry sand.
Unsuitable extinguishing media	Do not use water jet as an extinguisher, as this will spread the fire.
5.2. Special hazards arising from the substance or mixture	During fire, gases hazardous to health may be formed.
5.3. Advice for firefighters	
Special protective equipment for firefighters	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
Special firefighting procedures	Move containers from fire area if you can do so without risk.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures	
For non-emergency personnel	Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.
For emergency responders	Keep unnecessary personnel away.
6.2. Environmental precautions	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.
6.3. Methods and material for containment and cleaning up	Stop the flow of material, if this is without risk. Prevent product from entering drains. Following product recovery, flush area with water.
6.4. Reference to other sections	Not available.

SECTION 7: Handling and storage

7.1. Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Provide adequate ventilation. Avoid breathing dust/fume/gas/mist/vapours/spray. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Should be handled in closed systems, if possible. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.
7.2. Conditions for safe storage, including any incompatibilities	Store locked up. Store in original tightly closed container.
7.3. Specific end use(s)	Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	MAK	5 mg/m ³	Respirable fraction.
		10 mg/m ³	Inhalable fraction.

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	STEL	20 mg/m ³	Inhalable fraction.
		10 mg/m ³	Respirable fraction.
	MAK	1 mg/m ³	Inhalable fraction.
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)		0,1 mg/m ³	Fume and respirable dust.
	STEL	4 mg/m ³	Inhalable fraction.
	MAK	0,4 mg/m ³ 5 mg/m ³	Fume and respirable dust. Inhalable fraction.

Austria. TRK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	STEL	2 mg/m ³	Inhalable dust.
	TWA	0,5 mg/m ³	Inhalable dust.

Belgium. Exposure Limit Values

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m ³	Respirable fraction.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	1 mg/m ³	Dust and mist.
		0,2 mg/m ³	Fume.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m ³	
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	STEL	10 mg/m ³	
	TWA	5 mg/m ³	

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	2 mg/m ³	
		10 mg/m ³	Dust.
		1,5 mg/m ³	Respirable fraction.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	0,1 mg/m ³	
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,05 mg/m ³	

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	MAC	4 mg/m ³	Respirable dust.
		10 mg/m ³	Total dust.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	MAC	1 mg/m ³	
		0,2 mg/m ³	Dust and fume.
	STEL	2 mg/m ³	
		2 mg/m ³	Dust and fume.

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	MAC	0,5 mg/m ³	
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	MAC	5 mg/m ³	
	STEL	10 mg/m ³	

Cyprus. OELs. Control of factory atmosphere and dangerous substances in factories regulation, PI 311/73, as amended.

Components	Type	Value	Form
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	0,2 mg/m ³	Fume.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m ³	
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	TWA	5 mg/m ³	

Czech Republic. OELs. Government Decree 361

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	10 mg/m ³	Dust.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	Ceiling	2 mg/m ³	Dust.
		0,2 mg/m ³	Fume.
	TWA	1 mg/m ³	Dust.
		0,1 mg/m ³	Fume.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	Ceiling	1 mg/m ³	Aerosol, inhalable.
	TWA	0,5 mg/m ³	Aerosol, inhalable.

Denmark. Exposure Limit Values

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TLV	5 mg/m ³	Fume.
		5 mg/m ³	Dust and fume.
		2 mg/m ³	Respirable dust and/or fume.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TLV	1 mg/m ³	Dust.
		0,1 mg/m ³	Fume.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TLV	0,05 mg/m ³	Dust.

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	4 mg/m ³	Fine dust, respiratory fraction
		10 mg/m ³	Total dust.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	1 mg/m ³	Total dust.
		0,2 mg/m ³	Fine dust.

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m ³	

Finland. Workplace Exposure Limits

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1,5 mg/m ³	Welding fume.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	0,1 mg/m ³	Respirable dust and/or fume.
		0,02 mg/m ³	Respirable.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,01 mg/m ³	Respirable.
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	TWA	1 mg/m ³	

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	VME	5 mg/m ³	Dust.
Regulatory status: Indicative limit (VL)		5 mg/m ³	Welding fume.
Regulatory status: Indicative limit (VL)		10 mg/m ³	
Regulatory status: Indicative limit (VL)			
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	VLE	2 mg/m ³	Dust.
Regulatory status: Indicative limit (VL)			
	VME	1 mg/m ³	Dust.
Regulatory status: Indicative limit (VL)			
		0,2 mg/m ³	Fume.
Regulatory status: Indicative limit (VL)			
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	VME	1 mg/m ³	
Regulatory status: Indicative limit (VL)			

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	4 mg/m ³	Inhalable dust.
		1,5 mg/m ³	Respirable dust.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	0,01 mg/m ³	Respirable fraction.

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	AGW	10 mg/m ³	Inhalable fraction.
		1,25 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	AGW	0,03 mg/m ³	Inhalable fraction.
		0,006 mg/m ³	Respirable fraction.

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace Components

Components	Type	Value	Form
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	AGW	1 mg/m ³	Inhalable fraction.

Greece. OELs (Decree No. 90/1999, as amended) Components

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m ³	Inhalable
		10 mg/m ³	Welding fume.
		10 mg/m ³	Pyrophoric powder.
		10 mg/m ³	Respirable.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	STEL	2 mg/m ³	Dust.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m ³	Dust.
		0,2 mg/m ³	Fume.
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	STEL	10 mg/m ³	
		TWA	5 mg/m ³

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces Components

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	6 mg/m ³	Respirable.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	STEL	4 mg/m ³	
		0,4 mg/m ³	Smoke.
		1 mg/m ³	
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,1 mg/m ³	Smoke.
		0,1 mg/m ³	
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	Ceiling	0,1 mg/m ³	
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	STEL	20 mg/m ³	
		TWA	5 mg/m ³

Iceland. OELs. Regulation 154/1999 on occupational exposure limits Components

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	STEL	10 mg/m ³	Dust.
		TWA	5 mg/m ³
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	1 mg/m ³	Total dust.
		0,1 mg/m ³	Respirable dust.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,05 mg/m ³	Dust.
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	TWA	5 mg/m ³	

Ireland. Occupational Exposure Limits Components

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 ppm	Respirable dust.

Ireland. Occupational Exposure Limits

Components	Type	Value	Form
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	1 mg/m ³	Dust and mist.
		0,2 mg/m ³	Fume.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m ³	

Italy. Occupational Exposure Limits Components

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m ³	Respirable fraction.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	1 mg/m ³	Dust and mist.
		0,2 mg/m ³	Fume.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1,5 mg/m ³	Inhalable fraction.
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	STEL	10 mg/m ³	
	TWA	5 mg/m ³	

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
Aluminium (CAS 7429-90-5)	TWA	2 mg/m ³
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	STEL	1 mg/m ³
	TWA	0,5 mg/m ³
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,05 mg/m ³

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m ³	Inhalable fraction.
		2 mg/m ³	Respirable fraction.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	1 mg/m ³	Inhalable fraction.
		0,2 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m ³	
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	TWA	6 mg/m ³	

Netherlands. OELs (binding)

Components	Type	Value	Form
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	0,1 mg/m ³	Inhalable fraction.

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TLV	5 mg/m ³	Pyrophoric powder.
		5 mg/m ³	Welding fume.

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value	Form
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TLV	1 mg/m ³	Dust.
		0,1 mg/m ³	Fume.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TLV	0,05 mg/m ³	

Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	2,5 mg/m ³	Inhalable fraction.
		1,2 mg/m ³	Respirable fraction.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	0,2 mg/m ³	
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,25 mg/m ³	
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	STEL	10 mg/m ³	
	TWA	5 mg/m ³	

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	1 mg/m ³	Respirable fraction.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	1 mg/m ³	Dust and mist.
		0,2 mg/m ³	Fume.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1,5 mg/m ³	Inhalable fraction.
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	STEL	10 mg/m ³	
	TWA	5 mg/m ³	

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	STEL	3 mg/m ³	Fume.
		10 mg/m ³	Dust.
	TWA	3 mg/m ³	Dust.
		1 mg/m ³	Fume.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	STEL	1,5 mg/m ³	Dust.
	TWA	0,2 mg/m ³	Fume.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	STEL	0,5 mg/m ³	Dust.
	TWA	0,1 mg/m ³	
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	STEL	10 mg/m ³	
	TWA	5 mg/m ³	

Slovakia. OELs for carcinogens and mutagens. Regulation No. 46/2002 on carcinogenic and mutagenic substances

Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,05 mg/m ³	Inhalable fraction.

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	4 mg/m ³	Inhalable fraction.
		1,5 mg/m ³	Respirable fraction.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	1 mg/m ³	Inhalable fraction.
		0,2 mg/m ³	Respirable fume.
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	TWA	1 mg/m ³	

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	10 mg/m ³	Inhalable fraction.
		1,25 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,006 mg/m ³	Respirable fraction.
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	TWA	1 mg/m ³	Inhalable fraction.

Spain. Occupational Exposure Limits

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m ³	Welding fume.
		10 mg/m ³	Dust.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	0,1 mg/m ³	Respirable fraction.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m ³	
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	STEL	10 mg/m ³	
	TWA	5 mg/m ³	

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	5 mg/m ³	Total dust.
		2 mg/m ³	Respirable dust.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	TWA	0,01 mg/m ³	Respirable dust.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m ³	Total dust.

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	3 mg/m ³	Respirable fraction.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	STEL	0,2 mg/m ³	Inhalable fraction.
	TWA	0,1 mg/m ³	Inhalable fraction.

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value	Form
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	0,5 mg/m3	Inhalable fraction.
ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)	TWA	5 mg/m3	Inhalable fraction.

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	Form
Aluminium (CAS 7429-90-5)	TWA	4 mg/m3	Respirable dust.
		10 mg/m3	Inhalable dust.
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	STEL	2 mg/m3	Inhalable dusts and mists.
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	TWA	1 mg/m3	Inhalable dusts and mists.
		0,2 mg/m3	Fume.
		0,5 mg/m3	

Biological limit values**Croatia. BLV. Dangerous Substance Exposure Limit Values at Workplace, Annexes 4 (as amended)**

Components	Value	Determinant	Specimen	Sampling Time
Aluminium (CAS 7429-90-5)	200 mg/l	Aluminium	Urine	*

* - For sampling details, please see the source document.

Czech Republic. Limit Values for Indicators of Biological Exposure Tests in Urine and Blood, Annex 2, Tables 1 and 2, Government Decree 432/2003 Sb.

Components	Value	Determinant	Specimen	Sampling Time
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	0,077 µmol/mmol	Nickel	Creatinine in urine	*
	0,04 mg/g	Nickel	Creatinine in urine	*

* - For sampling details, please see the source document.

Finland. HTP-arvot, App 2., Biological Limit Values, (BRA/BGV) , Social Affairs and Ministry of Health

Components	Value	Determinant	Specimen	Sampling Time
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	0,1 µmol/l	Nickel	Urine	*

* - For sampling details, please see the source document.

Germany. TRGS 903, BAT List (Biological Limit Values)

Components	Value	Determinant	Specimen	Sampling Time
Aluminium (CAS 7429-90-5)	50 µg/g	Aluminium	Urine	*

* - For sampling details, please see the source document.

Hungary. Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices

Components	Value	Determinant	Specimen	Sampling Time
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	0,02 mg/g	Nickel	Creatinine in urine	*
	0,038 µmol/mmol	Nickel	Creatinine in urine	*

* - For sampling details, please see the source document.

Slovakia. BLVs (Biological Limit Value). Regulation no. 355/2006 concerning protection of workers exposed to chemical agents, Annex 2

Components	Value	Determinant	Specimen	Sampling Time
Aluminium (CAS 7429-90-5)	60 µg/g	Aluminium	Creatinine in urine	*

* - For sampling details, please see the source document.

Switzerland. BAT-Werte (Biological Limit Values in the Workplace as per SUVA)

Components	Value	Determinant	Specimen	Sampling Time
Aluminium (CAS 7429-90-5)	60 µg/g	Aluminium	Creatinine in urine	*
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	45 µg/l	Nickel	Urine	*

* - For sampling details, please see the source document.

Recommended monitoring procedures

VENTILATION: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Whenever possible, the use of local exhaust ventilation or other engineering controls is the preferred method of controlling exposure to airborne particulate. Where utilized, exhaust inlets to the ventilation system must be positioned as close as possible to the source of airborne generation. Avoid disruption of the airflow in the area of a local exhaust inlet by equipment such as a man-cooling fan. Check ventilation equipment regularly to ensure it is functioning properly. Provide training on the use and operation of ventilation to all users. Use qualified professionals to design and install ventilation systems.

Derived no effect levels (DNELs)

Not available.

Predicted no effect concentrations (PNECs)

Not available.

Exposure guidelines

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)

Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information

Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Wear approved safety glasses, goggles, face shield and/or welder's helmet when risk of eye injury is present, particularly during operations that generate dust, mist or fume.

Skin protection

- Hand protection

Wear gloves to prevent contact with particulate or solutions. Wear gloves to prevent metal cuts and skin abrasions during handling.

- Other

Protective overgarments or work clothing must be worn by persons who may become contaminated with particulate during activities.

Respiratory protection

When airborne exposures exceed or have the potential to exceed the occupational exposure limits, approved respirators must be used as specified by an Industrial Hygienist or other qualified professional. Respirator users must be medically evaluated to determine if they are physically capable of wearing a respirator. Quantitative and/or qualitative fit testing and respirator training must be satisfactorily completed by all personnel prior to respirator use. Users of tight fitting respirators must be clean shaven on those areas of the face where the respirator seal contacts the face. Use pressure-demand airline respirators when performing jobs with high potential exposures such as changing filters in a baghouse air cleaning device.

Thermal hazards

Not applicable.

Hygiene measures Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Environmental exposure controls Inform appropriate managerial or supervisory personnel of all environmental releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Solid.
Form	Various shapes.
Colour	Metallic.
Odour	Not applicable.
Odour threshold	Not applicable.
pH	Not applicable.
Melting point/freezing point	848,89 - 898,89 °C (1560 - 1650 °F) / Not applicable.
Initial boiling point and boiling range	Not applicable.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not applicable.
Flammability limit - upper (%)	Not applicable.
Explosive limit - lower (%)	Not applicable.
Explosive limit – upper (%)	Not applicable.

Vapour pressure 0,26 hPa estimated

Vapour density Not applicable.

Relative density Not applicable.

Solubility(ies)

Solubility (water) Not applicable.

Solubility (other) Not applicable.

Partition coefficient (n-octanol/water) Not available.

Auto-ignition temperature Not applicable.

Decomposition temperature Not applicable.

Viscosity Not applicable.

Explosive properties Not explosive.

Oxidising properties Not oxidising.

9.2. Other information

Density 8,24 g/cm³ estimated

Specific gravity 8,24 estimated

SECTION 10: Stability and reactivity

10.1. Reactivity Not available.

10.2. Chemical stability Not available.

10.3. Possibility of hazardous reactions Not available.

10.4. Conditions to avoid Contact with incompatible materials.

10.5. Incompatible materials Not available.

10.6. Hazardous decomposition products Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.

SECTION 11: Toxicological information

General information	Occupational exposure to the substance or mixture may cause adverse effects.
Information on likely routes of exposure	
Inhalation	May cause irritation to the respiratory system. Prolonged inhalation may be harmful.
Skin contact	May cause an allergic skin reaction.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.
Symptoms	May cause respiratory irritation. Coughing. Discomfort in the chest. Shortness of breath. May cause an allergic skin reaction. Dermatitis. Rash.
11.1. Information on toxicological effects	
Acute toxicity	May cause an allergic skin reaction. May cause respiratory irritation.
Skin corrosion/irritation	Due to partial or complete lack of data the classification is not possible.
Serious eye damage/eye irritation	Due to partial or complete lack of data the classification is not possible.
Respiratory sensitisation	Due to partial or complete lack of data the classification is not possible. May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin sensitisation	May cause an allergic skin reaction.
Germ cell mutagenicity	Due to partial or complete lack of data the classification is not possible.
Carcinogenicity	Suspected of causing cancer.
Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)	
	Not listed.
IARC Monographs. Overall Evaluation of Carcinogenicity	
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	2B Possibly carcinogenic to humans.
Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)	
Aluminium (CAS 7429-90-5)	Carcinogenic, Category 1A
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	Carcinogenic, Category 2.
Reproductive toxicity	Due to partial or complete lack of data the classification is not possible.
Specific target organ toxicity - single exposure	May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard	Due to partial or complete lack of data the classification is not possible.
Mixture versus substance information	No information available.
Other information	Not available.

SECTION 12: Ecological information

12.1. Toxicity

Product	Species		Test Results
Amorphous Alloy LM-601			
Aquatic			
Crustacea	EC50	Daphnia	0,4963 mg/l, 48 hours
Fish	LC50	Fish	6,4593 mg/l, 96 hours
<i>Acute</i>			
Fish	LC50	Fish	0,0913 mg/l, 96 hours estimated
Components	Species		Test Results
COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)			
Aquatic			
<i>Acute</i>			
Crustacea	EC50	Blue crab (<i>Callinectes sapidus</i>)	0,0031 mg/l

Components	Species	Test Results
Fish	LC50	Fathead minnow (<i>Pimephales promelas</i>) 0,0219 - 0,0446 mg/l, 96 hours
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)		
Aquatic		
<i>Acute</i>		
Fish	LC50	Rainbow trout,donaldson trout (Oncorhynchus mykiss) 0,06 mg/l, 4 days

* Estimates for product may be based on additional component data not shown.

12.2. Persistence and degradability	Not available.
12.3. Bioaccumulative potential	Not available.
Partition coefficient n-octanol/water (log Kow)	Not available.
Bioconcentration factor (BCF)	Not available.
12.4. Mobility in soil	Not available.
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.
12.6. Other adverse effects	Not available.
12.7. Additional information	

Estonia Dangerous substances in soil Data

COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)	Copper (Cu) 100 mg/kg
	Copper (Cu) 150 mg/kg
	Copper (Cu) 500 mg/kg
NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)	Nickel (Ni) 150 mg/kg
	Nickel (Ni) 50 mg/kg
	Nickel (Ni) 500 mg/kg

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. - 14.6.: Not regulated as dangerous goods.

RID

14.1. - 14.6.: Not regulated as dangerous goods.

ADN

14.1. - 14.6.: Not regulated as dangerous goods.

IATA

14.1. - 14.6.: Not regulated as dangerous goods.

IMDG

14.1. - 14.6.: Not regulated as dangerous goods.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

Material name: Amorphous Alloy LM-601

2007 Version #: 04

Revision date: 25-May-2021

Print date: 25-May-2021

PIS EU

15 / 16

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended

Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended

Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended

Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended

Aluminium (CAS 7429-90-5)

COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA

Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

NICKEL POWDER; [PARTICLE DIAMETER < 1MM] (CAS 7440-02-0)

ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Aluminium (CAS 7429-90-5)

COPPER FLAKES (COATED WITH ALIPHATIC ACID) (CAS 7440-50-8)

ZIRCONIUM POWDER, DRY (NON PYROPHORIC) (CAS 7440-67-7)

National regulations

Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment

Not available.

SECTION 16: Other information

List of abbreviations

Not available.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculator methods and test data, if available.

Training information

Follow training instructions when handling this material.

Further information

Transportation Emergency
Call Chemtrec at:
International: 703.741.5970
Spain: 900.868.538
Switzerland: 0800.564.402

Disclaimer

This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.

Other information

Revised information in Section 16.