# MATERION

# SAFETY DATA SHEET

#### 1. Identification

Product identifier Amorphous Alloy LM-601

Other means of identification

SDS number N04

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Materion Brush Inc.

Address 6070 Parkland Boulevard
Mayfield Heights, OH 44124

**United States** 

Telephone 1.800.862.4118

Website www.materion.com
E-mail ehs@materion.com
Contact person Theodore Knudson
Emergency phone number 1.800.862.4118

2. Hazard(s) identification

Physical hazards Not classified.

Health hazardsSensitization, skinCategory 1

Carcinogenicity Category 2

Specific target organ toxicity, repeated

exposure

Environmental hazards Not classified.

OSHA defined hazards Not classified.

Label elements



Signal word Danger

Hazard statement May cause an allergic skin reaction. May cause cancer. Causes damage to organs (respiratory

system) through prolonged or repeated exposure by inhalation.

Precautionary statement

**Prevention** Obtain special instructions before use. Do not handle until all safety precautions have been read

and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. In case of inadequate ventilation wear respiratory

Category 1 (Respiratory system)

protection.

None known.

**Response** If exposed or concerned: Get medical advice/attention. If breathing is difficult, remove victim to

fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory

symptoms: Call a poison center/doctor.

Storage Store locked up.

**Disposal** Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

**Supplemental information** For further information, please contact the Product Stewardship Department at +1.800.862.4118.

Material name: Amorphous Alloy LM-601

SDS US

1598 Version #: 04 Revision date: 01-24-2019 Issue date: 05-31-2015

# 3. Composition/information on ingredients

#### **Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Zirconium		7440-67-7	55 - 71
Copper		7440-50-8	25 - 35
Aluminum		7429-90-5	2 - 5
Nickel		7440-02-0	2 - 5

#### 4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water. Get medical attention if irritation develops and persists.

Rinse mouth. Get medical attention if symptoms occur. Ingestion

Most important

symptoms/effects, acute and

delaved

May cause an allergic skin reaction.

Indication of immediate medical attention and special treatment

needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

General information If exposed or concerned: get medical attention/advice. If you feel unwell, seek medical advice

(show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

#### 5. Fire-fighting measures

Suitable extinguishing media

Dry powder. Dry sand.

Unsuitable extinguishing media

Do not use water as an extinguisher.

Specific hazards arising from

the chemical

None known.

Special protective equipment

and precautions for firefighters

Use protective equipment appropriate for surrounding materials.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards No unusual fire or explosion hazards noted.

#### Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear appropriate protective equipment and clothing during clean-up. For personal protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up Stop the flow of material, if this is without risk. For waste disposal, see section 13 of the SDS.

**Environmental precautions** 

Prevent further leakage or spillage if safe to do so.

## Handling and storage

Precautions for safe handling

Do not handle until all safety precautions have been read and understood. Wash hands thoroughly after handling. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities Store locked up. Store away from incompatible materials (see Section 10 of the SDS).

Material name: Amorphous Alloy LM-601

# 8. Exposure controls/personal protection

# Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	Form
Aluminum (CAS 7429-90-5)	PEL	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
Copper (CAS 7440-50-8)	PEL	1 mg/m3	Dust and mist.
		0.1 mg/m3	Fume.
Nickel (CAS 7440-02-0)	PEL	1 mg/m3	
US. OSHA Table Z-3 (29 CFR 1	910.1000)		
Components	Туре	Value	Form
Aluminum (CAS 7429-90-5)	TWA	5 mg/m3	Respirable fraction.
		15 mg/m3	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
US. ACGIH Threshold Limit Valu	Jes		
Components	Туре	Value	Form
Aluminum (CAS 7429-90-5)	TWA	1 mg/m3	Respirable fraction.
Copper (CAS 7440-50-8)	TWA	1 mg/m3	Dust and mist.
		0.2 mg/m3	Fume.
Nickel (CAS 7440-02-0)	TWA	1.5 mg/m3	Inhalable fraction.
Zirconium (CAS 7440-67-7)	STEL	10 mg/m3	
,	TWA	F / 2	
	1 4 4 / 1	5 mg/m3	
US. NIOSH: Pocket Guide to Ch		5 mg/m3	
US. NIOSH: Pocket Guide to Ch Components		s mg/ms  Value	Form
	nemical Hazards		Form Respirable.
Components	nemical Hazards Type	Value	
Components	nemical Hazards Type	Value 5 mg/m3	Respirable.
Components	nemical Hazards Type	Value 5 mg/m3	Respirable. Welding fume or
Components	nemical Hazards Type	Value 5 mg/m3 5 mg/m3	Respirable. Welding fume or pyrophoric powder.
Components  Aluminum (CAS 7429-90-5)	nemical Hazards Type TWA	Value 5 mg/m3 5 mg/m3 10 mg/m3	Respirable. Welding fume or pyrophoric powder. Total
Components  Aluminum (CAS 7429-90-5)	nemical Hazards Type TWA	Value 5 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3	Respirable. Welding fume or pyrophoric powder. Total Dust and mist.
Components  Aluminum (CAS 7429-90-5)  Copper (CAS 7440-50-8)	Type TWA	Value 5 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 0.1 mg/m3	Respirable. Welding fume or pyrophoric powder. Total Dust and mist.
Components  Aluminum (CAS 7429-90-5)  Copper (CAS 7440-50-8)  Nickel (CAS 7440-02-0)	Type TWA TWA	Value 5 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 0.1 mg/m3 0.015 mg/m3	Respirable. Welding fume or pyrophoric powder. Total Dust and mist.
Components  Aluminum (CAS 7429-90-5)  Copper (CAS 7440-50-8)  Nickel (CAS 7440-02-0)  Zirconium (CAS 7440-67-7)	TWA TWA TWA STEL	Value 5 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 0.1 mg/m3 0.015 mg/m3 10 mg/m3 5 mg/m3	Respirable. Welding fume or pyrophoric powder. Total Dust and mist.
Components  Aluminum (CAS 7429-90-5)  Copper (CAS 7440-50-8)  Nickel (CAS 7440-02-0)  Zirconium (CAS 7440-67-7)	Type TWA  TWA  TWA  TWA  STEL  TWA	Value 5 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 0.1 mg/m3 0.015 mg/m3 10 mg/m3 5 mg/m3	Respirable. Welding fume or pyrophoric powder. Total Dust and mist.
Components  Aluminum (CAS 7429-90-5)  Copper (CAS 7440-50-8)  Nickel (CAS 7440-02-0)  Zirconium (CAS 7440-67-7)  US. California Code of Regulation	Type TWA TWA TWA STEL TWA Ons, Title 8, Section 5155. Airborne 6	Value 5 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 0.1 mg/m3 0.015 mg/m3 10 mg/m3 5 mg/m3	Respirable. Welding fume or pyrophoric powder. Total Dust and mist. Fume.
Components  Aluminum (CAS 7429-90-5)  Copper (CAS 7440-50-8)  Nickel (CAS 7440-02-0)  Zirconium (CAS 7440-67-7)  US. California Code of Regulation	Type TWA TWA TWA STEL TWA Ons, Title 8, Section 5155. Airborne 6	Value 5 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 0.1 mg/m3 0.015 mg/m3 10 mg/m3 5 mg/m3 Contaminants Value	Respirable. Welding fume or pyrophoric powder. Total Dust and mist. Fume.
Components  Aluminum (CAS 7429-90-5)  Copper (CAS 7440-50-8)  Nickel (CAS 7440-02-0)  Zirconium (CAS 7440-67-7)  US. California Code of Regulation	Type TWA TWA TWA STEL TWA Ons, Title 8, Section 5155. Airborne 6	Value 5 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 0.1 mg/m3 0.015 mg/m3 10 mg/m3 5 mg/m3  Contaminants Value 5 mg/m3	Respirable. Welding fume or pyrophoric powder. Total Dust and mist. Fume.  Form Respirable fraction.
Components  Aluminum (CAS 7429-90-5)  Copper (CAS 7440-50-8)  Nickel (CAS 7440-02-0)  Zirconium (CAS 7440-67-7)  US. California Code of Regulation	Type TWA TWA TWA STEL TWA Ons, Title 8, Section 5155. Airborne 6	Value 5 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 0.1 mg/m3 0.015 mg/m3 10 mg/m3 5 mg/m3  Contaminants  Value 5 mg/m3 5 mg/m3	Respirable. Welding fume or pyrophoric powder. Total Dust and mist. Fume.  Form  Respirable fraction. Pyrophoric powder.
Components  Aluminum (CAS 7429-90-5)  Copper (CAS 7440-50-8)  Nickel (CAS 7440-02-0)  Zirconium (CAS 7440-67-7)  US. California Code of Regulation	Type TWA TWA TWA STEL TWA Ons, Title 8, Section 5155. Airborne 6	Value  5 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 0.1 mg/m3 0.015 mg/m3 10 mg/m3 5 mg/m3  Contaminants  Value  5 mg/m3 5 mg/m3 5 mg/m3 5 mg/m3	Respirable. Welding fume or pyrophoric powder. Total Dust and mist. Fume.  Form  Respirable fraction. Pyrophoric powder. Welding fume.
Components  Aluminum (CAS 7429-90-5)  Copper (CAS 7440-50-8)  Nickel (CAS 7440-02-0)  Zirconium (CAS 7440-67-7)  US. California Code of Regulation Components  Aluminum (CAS 7429-90-5)	Type TWA TWA TWA STEL TWA Ons, Title 8, Section 5155. Airborne of Type PEL	Value  5 mg/m3 5 mg/m3 10 mg/m3 1 mg/m3 0.1 mg/m3 0.015 mg/m3 10 mg/m3 5 mg/m3  5 mg/m3 5 mg/m3 5 mg/m3 10 mg/m3	Respirable. Welding fume or pyrophoric powder. Total Dust and mist. Fume.  Form  Respirable fraction. Pyrophoric powder. Welding fume. Total dust.

Appropriate engineering controls Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates

should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

Eye/face protection If contact is likely, safety glasses with side shields are recommended.

Skin protection

**Hand protection** Wear gloves to prevent metal cuts and skin abrasions during handling.

Other Wear suitable protective equipment.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

**Thermal hazards** Not applicable. Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Always observe good personal hygiene measures, such as washing after handling the material

and before eating, drinking, and/or smoking.

# 9. Physical and chemical properties

**Appearance** 

Physical state Solid.

Form Various shapes.

Color Metallic.

Odor None.

Odor threshold Not applicable. pH Not applicable.

Melting point/freezing point 1560 - 1650 °F (848.89 - 898.89 °C) / Not applicable.

Initial boiling point and boiling

range

Not applicable.

Flash point Not applicable.

Evaporation rate Not applicable.

Flammability (solid, gas) None known.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not applicable.

Explosive limit - upper (%) Not applicable.

Vapor pressure 0.26 hPa estimated
Vapor density Not applicable.

Relative density Not applicable.

Solubility(ies)

Solubility (water) Insoluble.

Solubility (other) Not applicable.

Partition coefficient Not applicable.

(n-octanol/water)

Auto-ignition temperature Not applicable.

Decomposition temperature Not applicable.

Viscosity Not applicable.

Other information

**Density** 8.24 g/cm3 estimated

**Explosive properties** Not explosive. **Oxidizing properties** Not oxidizing.

# 10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

**Incompatible materials** Strong oxidizing agents.

Hazardous decomposition

products

Irritating and/or toxic fumes and gases may be emitted upon the product's decomposition.

## 11. Toxicological information

#### Information on likely routes of exposure

InhalationProlonged inhalation may be harmful.Skin contactMay cause an allergic skin reaction.Eye contactNot likely, due to the form of the product.IngestionExpected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics

May cause an allergic skin reaction.

Information on toxicological effects

Acute toxicity None known.

**Skin corrosion/irritation** Prolonged skin contact may cause temporary irritation.

Serious eye damage/eye

irritation

Not likely, due to the form of the product.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

**Skin sensitization** May cause an allergic skin reaction.

Germ cell mutagenicity Not classified.

**Carcinogenicity** Suspected of causing cancer.

IARC Monographs. Overall Evaluation of Carcinogenicity

Nickel (CAS 7440-02-0) 2B Possibly carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

#### US. National Toxicology Program (NTP) Report on Carcinogens

Nickel (CAS 7440-02-0) Known To Be Human Carcinogen.

Reasonably Anticipated to be a Human Carcinogen.

Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified. Not classified.

Specific target organ toxicity -

repeated exposure

May cause damage to organs (respiratory system) through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Prolonged exposure may cause chronic effects.

#### 12. Ecological information

**Ecotoxicity** No ecotoxicity data noted for the ingredient(s).

Persistence and degradability No data is available on the degradability of this product.

Bioaccumulative potential Not available.

Mobility in soil Not available.

Other adverse effects Not available.

Material name: Amorphous Alloy LM-601

SDS US

1598 Version #: 04 Revision date: 01-24-2019 Issue date: 05-31-2015

# 13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations**Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

## 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

#### 15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

All components are on the U.S. EPA TSCA Inventory List.

**Toxic Substances Control Act (TSCA)** 

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Copper (CAS 7440-50-8) Listed. Nickel (CAS 7440-02-0) Listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

No (Exempt)

chemical

SARA 313 (TRI reporting)

Chemical name	CAS number	% by wt.	
Aluminum	7429-90-5	2 - 5	
Copper	7440-50-8	25 - 35	
Nickel	7440-02-0	2 - 5	

#### Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Nickel (CAS 7440-02-0)

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act (SDWA)

Contains component(s) regulated under the Safe Drinking Water Act.

US state regulations



California Proposition 65

WARNING: This product can expose you to Nickel, which is known to the State of California to cause cancer.

For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Nickel (CAS 7440-02-0) Listed: October 1, 1989

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd.

Aluminum (CAS 7429-90-5) Copper (CAS 7440-50-8) Nickel (CAS 7440-02-0)

# 16. Other information, including date of preparation or last revision

05-31-2015 Issue date Revision date 01-24-2019

Version # 04

Disclaimer Materion Brush Inc. cannot anticipate all conditions under which this information and its product, or

> the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to

assume liability for loss, injury, damage or expense due to improper use.

Other information Revised information in Section 4.

> Revised information in Section 5. Revised information in Section 6. Revised information in Section 8. Revised information in Section 9. Revised information in Section 11. Revised information in Section 15.

Material name: Amorphous Alloy LM-601

SDS US