



# SAFETY DATA SHEET

**MATERION**

## 1. Identification

<b>Product identifier</b>	<b>SupremEX® Mechanically Alloyed Aluminum/Silicon Carbide Metal Matrix Composite (MA - AA2xxx/SiC MMC) Powder</b>	
<b>Other means of identification</b>		
SDS number	N05	
Synonyms	SupremEX®, 215XK, 217XF, 217XG, 225XE, 230XE, 2009/SiC/15p, 2124A/SiC/15p, 2124A/SiC/17p, 2124A/SiC/25p, 2124A/SiC/30p or any 2000 series Aluminum Alloy with Silicon Carbide reinforcement	
<b>Manufacturer/Importer/Supplier/Distributor information</b>		
<b>Manufacturer</b>		
Company name	Materion Brush Inc.	
Address	6070 Parkland Boulevard Mayfield Heights, OH 44124 United States	
Telephone	1.800.862.4118	
Website	www.materion.com	
E-mail	ehs@materion.com	
Contact person	Theodore Knudson	
Emergency phone number	1.800.862.4118	

## 2. Hazard(s) identification

<b>Physical hazards</b>	Not classified.	
<b>Health hazards</b>	Acute toxicity, oral	Category 4
	Acute toxicity, inhalation	Category 3
<b>Environmental hazards</b>	Not classified.	
<b>OSHA defined hazards</b>	Not classified.	
<b>Label elements</b>		
Hazard symbol	None.	
Signal word	None.	
Hazard statement	Not available.	
<b>Precautionary statement</b>		
Prevention	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection.	
Response	If exposed or concerned: Get medical advice/attention.	
Storage	Store locked up.	
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.	
<b>Hazard(s) not otherwise classified (HNOC)</b>	None known.	
<b>Supplemental information</b>	For further information, please contact the Product Stewardship Department at +1.800.862.4118.	

## 3. Composition/information on ingredients

**Mixtures**

Chemical name	Common name and synonyms	CAS number	%
Aluminum		7429-90-5	67 - 83
Silicon Carbide		409-21-2	17 - 33
Copper		7440-50-8	2.5 - 3.6
Magnesium		7439-95-4	0.8 - 1.3

#### 4. First-aid measures

<b>Inhalation</b>	Move to fresh air. Call a physician if symptoms develop or persist.
<b>Skin contact</b>	Wash off with soap and water. Get medical attention if irritation develops and persists.
<b>Eye contact</b>	Rinse with water. Get medical attention if irritation develops and persists.
<b>Ingestion</b>	Rinse mouth. Get medical attention if symptoms occur.
<b>Most important symptoms/effects, acute and delayed</b>	Prolonged exposure may cause chronic effects.
<b>Indication of immediate medical attention and special treatment needed</b>	Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.
<b>General information</b>	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

#### 5. Fire-fighting measures

<b>Suitable extinguishing media</b>	Powder. Dry sand.
<b>Unsuitable extinguishing media</b>	Do not use water jet as an extinguisher, as this will spread the fire. Carbon dioxide (CO <sub>2</sub> ).
<b>Specific hazards arising from the chemical</b>	During fire, gases hazardous to health may be formed.
<b>Special protective equipment and precautions for firefighters</b>	Self-contained breathing apparatus and full protective clothing must be worn in case of fire.
<b>Fire fighting equipment/instructions</b>	Move containers from fire area if you can do so without risk.
<b>Specific methods</b>	Use standard firefighting procedures and consider the hazards of other involved materials.
<b>General fire hazards</b>	No unusual fire or explosion hazards noted.

#### 6. Accidental release measures

<b>Personal precautions, protective equipment and emergency procedures</b>	Wear appropriate protective equipment and clothing during clean-up. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained.
<b>Methods and materials for containment and cleaning up</b>	Not available.
<b>Environmental precautions</b>	Avoid release to the environment. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground. Inform appropriate managerial or supervisory personnel of all environmental releases.

#### 7. Handling and storage

<b>Precautions for safe handling</b>	Not available.
<b>Conditions for safe storage, including any incompatibilities</b>	Store in original tightly closed container.

## 8. Exposure controls/personal protection

### Occupational exposure limits

#### US. OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	PEL	5 mg/m <sup>3</sup>	Respirable fraction.
		15 mg/m <sup>3</sup>	Total dust.
Copper (CAS 7440-50-8)	PEL	1 mg/m <sup>3</sup>	Dust and mist.
		0.1 mg/m <sup>3</sup>	Fume.
Silicon Carbide (CAS 409-21-2)	PEL	5 mg/m <sup>3</sup>	Respirable fraction.
		15 mg/m <sup>3</sup>	Total dust.

#### US. OSHA Table Z-3 (29 CFR 1910.1000)

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	5 mg/m <sup>3</sup>	Respirable fraction.
		15 mg/m <sup>3</sup>	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.
Silicon Carbide (CAS 409-21-2)	TWA	5 mg/m <sup>3</sup>	Respirable fraction.
		15 mg/m <sup>3</sup>	Total dust.
		50 mppcf	Total dust.
		15 mppcf	Respirable fraction.

#### US. ACGIH Threshold Limit Values

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	1 mg/m <sup>3</sup>	Respirable fraction.
Copper (CAS 7440-50-8)	TWA	1 mg/m <sup>3</sup>	Dust and mist.
		0.2 mg/m <sup>3</sup>	Fume.
Silicon Carbide (CAS 409-21-2)	TWA	0.1 fibers/cm <sup>3</sup>	Fiber.
		3 mg/m <sup>3</sup>	Respirable fraction.
		10 mg/m <sup>3</sup>	Inhalable fraction.

#### US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	TWA	5 mg/m <sup>3</sup>	Welding fume or pyrophoric powder.
		5 mg/m <sup>3</sup>	Respirable.
		10 mg/m <sup>3</sup>	Total
Copper (CAS 7440-50-8)	TWA	1 mg/m <sup>3</sup>	Dust and mist.
		0.1 mg/m <sup>3</sup>	Fume.
Silicon Carbide (CAS 409-21-2)	TWA	5 mg/m <sup>3</sup>	Respirable.
		10 mg/m <sup>3</sup>	Total

#### US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants

Components	Type	Value	Form
Aluminum (CAS 7429-90-5)	PEL	5 mg/m <sup>3</sup>	Respirable fraction.
		5 mg/m <sup>3</sup>	Welding fume.
		5 mg/m <sup>3</sup>	Pyrophoric powder.

**US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants**

Components	Type	Value	Form
Copper (CAS 7440-50-8)	PEL	10 mg/m <sup>3</sup>	Total dust.
		1 mg/m <sup>3</sup>	Dust and mist.
Silicon Carbide (CAS 409-21-2)	PEL	0.1 mg/m <sup>3</sup>	Fume.
		5 mg/m <sup>3</sup>	Respirable fraction.
		10 mg/m <sup>3</sup>	Total dust.

<b>Biological limit values</b>	No biological exposure limits noted for the ingredient(s).
<b>Appropriate engineering controls</b>	Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.
<b>Individual protection measures, such as personal protective equipment</b>	
<b>Eye/face protection</b>	Wear approved safety glasses, goggles, face shield and/or welder's helmet when risk of eye injury is present, particularly during operations that generate dust, mist or fume.
<b>Skin protection</b>	
<b>Hand protection</b>	Wear gloves to prevent contact with particulate or solutions. Wear gloves to prevent metal cuts and skin abrasions during handling.
<b>Other</b>	Protective overgarments or work clothing must be worn by persons who may become contaminated with particulate during activities.
<b>Respiratory protection</b>	When airborne exposures exceed or have the potential to exceed the occupational exposure limits, approved respirators must be used as specified by an Industrial Hygienist or other qualified professional. Respirator users must be medically evaluated to determine if they are physically capable of wearing a respirator. Quantitative and/or qualitative fit testing and respirator training must be satisfactorily completed by all personnel prior to respirator use. Users of tight fitting respirators must be clean shaven on those areas of the face where the respirator seal contacts the face. Use pressure-demand airline respirators when performing jobs with high potential exposures such as changing filters in a baghouse air cleaning device.
<b>Thermal hazards</b>	Not applicable.
<b>General hygiene considerations</b>	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking.

**9. Physical and chemical properties**

**Appearance**

<b>Physical state</b>	Solid.
<b>Form</b>	Various shapes.
<b>Color</b>	Grey.
<b>Odor</b>	Not applicable.
<b>Odor threshold</b>	Not applicable.
<b>pH</b>	Not applicable.
<b>Melting point/freezing point</b>	936 - 1180 °F (502.22 - 637.78 °C) / Not applicable.
<b>Initial boiling point and boiling range</b>	Not applicable.
<b>Flash point</b>	Not applicable.
<b>Evaporation rate</b>	Not applicable.
<b>Flammability (solid, gas)</b>	Not applicable.
<b>Upper/lower flammability or explosive limits</b>	
<b>Flammability limit - lower (%)</b>	Not applicable.

Flammability limit - upper (%)	Not applicable.
Explosive limit - lower (%)	Not applicable.
Explosive limit - upper (%)	Not applicable.
Vapor pressure	3282.87 hPa estimated
Vapor density	Not applicable.
Relative density	Not applicable.
Solubility(ies)	
Solubility (water)	Not applicable.
Solubility (other)	Not applicable.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not applicable.
Decomposition temperature	Not applicable.
Viscosity	Not applicable.
Other information	
Density	3.03 g/cm <sup>3</sup> estimated
Explosive properties	Not explosive.
Flammability class	Not applicable.
Oxidizing properties	Not oxidizing.
Specific gravity	3.03 estimated

## 10. Stability and reactivity

Reactivity	Not available.
Chemical stability	Not available.
Possibility of hazardous reactions	Not available.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	Not available.
Hazardous decomposition products	Not available.

## 11. Toxicological information

### Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	No adverse effects due to skin contact are expected.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and toxicological characteristics  
Direct contact with eyes may cause temporary irritation.

### Information on toxicological effects

Acute toxicity	Not available.
Skin corrosion/irritation	Prolonged skin contact may cause temporary irritation.
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.
Respiratory or skin sensitization	
Respiratory sensitization	Not a respiratory sensitizer.
Skin sensitization	This product is not expected to cause skin sensitization.

**Germ cell mutagenicity** No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

## **Carcinogenicity**

### **IARC Monographs. Overall Evaluation of Carcinogenicity**

Silicon Carbide (CAS 409-21-2) 2A Probably carcinogenic to humans.

### **OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

Not regulated.

### **US. National Toxicology Program (NTP) Report on Carcinogens**

Not listed.

**Reproductive toxicity** This product is not expected to cause reproductive or developmental effects.

**Specific target organ toxicity - single exposure** Not classified.

**Specific target organ toxicity - repeated exposure** Causes damage to organs through prolonged or repeated exposure.

**Aspiration hazard** Not an aspiration hazard.

**Chronic effects** Causes damage to organs through prolonged or repeated exposure. Prolonged inhalation may be harmful.

## **12. Ecological information**

**Ecotoxicity** No ecotoxicity data noted for the ingredient(s).

**Persistence and degradability** Not available.

**Bioaccumulative potential** Not available.

**Mobility in soil** Not available.

**Other adverse effects** Not available.

## **13. Disposal considerations**

**Disposal instructions** Collect and reclaim or dispose in sealed containers at licensed waste disposal site.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

**Hazardous waste code** The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

**Waste from residues / unused products** Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

**Contaminated packaging** Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## **14. Transport information**

### **DOT**

Not regulated as dangerous goods.

### **IATA**

Not regulated as dangerous goods.

### **IMDG**

Not regulated as dangerous goods.

## **15. Regulatory information**

**US federal regulations** All components are on the U.S. EPA TSCA Inventory List.

### **Toxic Substances Control Act (TSCA)**

**TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)**

Not regulated.

**CERCLA Hazardous Substance List (40 CFR 302.4)**

Copper (CAS 7440-50-8) Listed.

**SARA 304 Emergency release notification**

Not regulated.

**OSHA Specifically Regulated Substances (29 CFR 1910.1001-1052)**

Not regulated.

**Superfund Amendments and Reauthorization Act of 1986 (SARA)**

**SARA 302 Extremely hazardous substance**

Not listed.

**SARA 311/312 Hazardous chemical** Yes

**Classified hazard categories** Acute toxicity (any route of exposure)

**SARA 313 (TRI reporting)**

Chemical name	CAS number	% by wt.
Aluminum	7429-90-5	67 - 83
Copper	7440-50-8	2.5 - 3.6

**Other federal regulations**

**Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List**

Not regulated.

**Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)**

Not regulated.

**Safe Drinking Water Act (SDWA)** Not regulated.

**US state regulations**

**California Proposition 65**

**US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))**

- Aluminum (CAS 7429-90-5)
- Copper (CAS 7440-50-8)
- Silicon Carbide (CAS 409-21-2)

**16. Other information, including date of preparation or last revision**

**Issue date** 03-04-2016

**Revision date** 01-09-2020

**Version #** 05

**Disclaimer** This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.

**Other information** Date change.