

SAFETY DATA SHEET

1. Identification

Product identifier	Antimony Oxide, Sb2O3	
Other means of identification SDS number	1BO	
Materion Code	1BO	
CAS number	1309-64-4	
Synonyms	Antimony and its compounds: antimony(III) ox	ide, dust (as Sb) * ANTIMONIOUS OXIDE
Manufacturer/Importer/Supplier/D Manufacturer	istributor information	
Company name Address	Materion Electronic Materials 6070 Parkland Blvd Mayfield Heights, Ohio 44124 United States	
Telephone	1.216.383.4019	
E-mail	Materion-PS@materion.com	
Contact person	Product Stewardship Director	
Emergency phone number	See Section 16	
2. Hazard(s) identification		
Physical hazards	Not classified.	
Health hazards	Acute toxicity, oral	Category 4
	Acute toxicity, inhalation	Category 4
	Skin corrosion/irritation	Category 1
	Serious eye damage/eye irritation	Category 1
	Carcinogenicity	Category 1
	Specific target organ toxicity, repeated exposure	Category 1
Environmental hazards	Hazardous to the aquatic environment, acute hazard	Category 3
	Hazardous to the aquatic environment, long-term hazard	Category 2
OSHA defined hazards	Not classified.	
Label elements		
Signal word	Danger	

Hazard statement

Harmful if swallowed. May cause cancer. Harmful if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage. Harmful if inhaled. May cause cancer. Causes damage to organs through prolonged or repeated exposure. Harmful to aquatic life. Toxic to aquatic life with long lasting effects.

Precautionary statement	
Prevention	Obtain special instructions before use. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Do not breathe dust. Wash thoroughly after handling. Do not eat, drink or smoke when using this product. Use only outdoors or in a well-ventilated area. Avoid release to the environment. Wear protective gloves/protective clothing/eye protection/face protection.
Response	Rinse mouth. If swallowed: Rinse mouth. Do NOT induce vomiting. If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. If inhaled: Remove person to fresh air and keep comfortable for breathing. Immediately call a poison center/doctor. If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Collect spillage.
Storage	Store locked up.
Disposal	Dispose of contents/container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	None known.
Supplemental information	For further information, please contact the Product Stewardship Department at +1.800.862.4118.

3. Composition/information on ingredients

Substances

Chemical name	Common name and synonyms	CAS number	%
Antimony oxide	Antimony and its compounds:	1309-64-4	100
	antimony(III) oxide, dust (as Sb)		
	ANTIMONIOUS OXIDE		

*Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures	
Inhalation	Move to fresh air. Oxygen or artificial respiration if needed. Do not use mouth-to-mouth method if victim inhaled the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Call a physician or poison control center immediately.
Skin contact	Take off immediately all contaminated clothing. Take off immediately all contaminated clothing. Rinse skin with water/shower. Call a physician or poison control center immediately. Chemical burns must be treated by a physician. For minor skin contact, avoid spreading material on unaffected skin. Wash contaminated clothing before reuse.
Eye contact	Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician or poison control center immediately.
Ingestion	Call a physician or poison control center immediately. Rinse mouth. Do not induce vomiting. If vomiting occurs, keep head low so that stomach content doesn't get into the lungs. Do not use mouth-to-mouth method if victim ingested the substance. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.
Most important symptoms/effects, acute and delayed	May cause temporary blindness and severe eye damage. Burning pain and severe corrosive skin damage. Causes serious eye damage. Corrosive effects. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Prolonged exposure may cause chronic effects.
Indication of immediate medical attention and special treatment needed	Provide general supportive measures and treat symptomatically. Chemical burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call an ambulance. Continue flushing during transport to hospital. Keep victim warm. Keep victim under observation. Symptoms may be delayed.
General information	IF exposed or concerned: Get medical advice/attention. If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Unsuitable extinguishing media	Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). None known.
Specific hazards arising from the chemical	During fire, gases hazardous to health may be formed.
Special protective equipment and precautions for firefighters	Wear suitable protective equipment.
Fire fighting equipment/instructions	Use water spray to cool unopened containers. Water runoff can cause environmental damage.
Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures	Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate personal protective equipment. Do not breathe dust. Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.
Methods and materials for containment and cleaning up	Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). Collect dust using a vacuum cleaner equipped with HEPA filter. Prevent entry into waterways, sewer, basements or confined areas. Stop the flow of material, if this is without risk.
	Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.
	Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.
	Never return spills to original containers for re-use. Put material in suitable, covered, labeled containers. For waste disposal, see section 13 of the SDS.
Environmental precautions	Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Do not contaminate water. Avoid discharge into drains, water courses or onto the ground.
7. Handling and storage	
Precautions for safe handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Minimize dust generation and accumulation. Do not breathe dust. Do not get in eyes, on skin, or on clothing. Do not taste or swallow. Do not get this material on clothing. Avoid prolonged exposure. When using, do not eat, drink or smoke. Should be handled in closed systems, if possible. Use only outdoors or in a well-ventilated area. Wear appropriate personal protective equipment. Wash hands thoroughly after handling. Avoid release to the environment. Do not empty into drains. Observe good industrial hygiene practices.
Conditions for safe storage, including any incompatibilities	Store locked up. Store in a cool, dry place out of direct sunlight. Store in tightly closed container. Store in a well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

US. OSHA Table Z-1 Permissible Exposure Limits (PEL) for Air Contaminants (29 CFR 1910.1000)			
Material	Туре	Value	
Antimony oxide (CAS 1309-64-4)	PEL	0.5 mg/m3	

propriate engineering controlsGood general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposure below the recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product.ividual protection Hand protection Wear eye/face protection. Chemical resistant gloves.Wear appropriate chemical resistant gloves.OtherWear appropriate chemical resistant clothing. Use of an impervious apron is recommended. We protective gloves.Respiratory protectionUse a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical resistant with organic vapor cartridge, full facepiece, dust and mist filter.Thermal hazardsWear appropriate thermal protective clothing, when necessary.	Material	Туре	Value
Material Type Value Antimony oxide (CAS 1309-64-4) IDLH 50 mg/m3 US, NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Material Type Value Antimony oxide (CAS 1309-64-4) Type Value US, SulfSh: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Material Type Value Antimony oxide (CAS 1309-64-4) US california Code of Regulations, Title 8, Saction 5155. Airborne Contaminants Material Type Value Antimony oxide (CAS 1309-64-4) No biological exposure limits noted for the ingredient(s). Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering measures are not sufficient to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels below the Occupational Exposure limit (OCEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposure below the recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product. Vidual protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant gloves. Other Wear appropriate chemical respirator if there is a ri		TWA	0.5 mg/m3
Antimony oxide (CAS IDLH 50 mg/m3 1309-64-4) US, NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Material Type Value Antimony oxide (CAS TWA 0.5 mg/m3 1309-64-4) US, California Code of Regulations, Title 8, Section 5155. Airborne Contaminants Material Type Value Antimony oxide (CAS PEL 0.5 mg/m3 1309-64-4) US, California Code of Regulations, Title 8, Section 5155. Airborne Contaminants Material Type Value Antimony oxide (CAS PEL 0.5 mg/m3 1309-64-4) Rogical limit values No biological exposure limits noted for the ingredient(s). propriate engineering controls Good general venilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposure below the recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product. Notical protection measures, such as personal protection. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter. Skin protection Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant gloves. Reepiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dustfume at levels exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter. Thermal hazards Wear appropriate thermal protective clothing, when necessary. Observe any medical surveillance requirements. Do not get in eyes. Do not get this material on contact with skin. Do not get this material on cothing. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the mater	NIOSH. Immediately Dangero	us to Life or Health (IDLH) Values, as a	amended
1309-64-4) US, NIOSH: Pocket Guide to Chemical Hazards Recommended Exposure Limits (REL) Material Type Antimory oxide (CAS TWA 1309-64-4) 0.5 mg/m3 US, California Code of Regulations, Title 8, Section 5155. Airborne Contaminants Material Type Value Antimony oxide (CAS PEL 1309-64-4) 0.5 mg/m3 US, California Code of Regulations, Title 8, Section 5155. Airborne Contaminants Material Type Value Antimony oxide (CAS PEL 0.5 mg/m3 1309-64-4) No biological exposure limits noted for the ingredient(s). propriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering measures are not sufficient to maintain airborne levels below recommended exposure limits. If exposure Limit (OEL), suitable respiratory protection must be worn. If material is groound, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposure below the recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product. Vidual protection measures, such as personal protective equipment Eye/face protection Wear appropriate	Material	Туре	Value
Material Type Value Antimony oxide (CAS 1309-64-4) TWA 0.5 mg/m3 US. California Code of Regulations, Title 8, Section 5155. Alrborne Contaminants Material Type Value Antimony oxide (CAS 1309-64-4) PEL 0.5 mg/m3 logical limit values propriate engineering controls No biological exposure limits noted for the ingredient(s). Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. The xposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to kee pexposure below the recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product. Vidual protection Hand protection Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. We protective gloves. Respiratory protection Use a NIOSH/MSHA approved respirator with organic vapor cartridge, full facepiece, dust and mist filter. Thermal hazards Wear appr		IDLH	50 mg/m3
1309-64-4) US. California Code of Regulations, Title 8, Section 5155. Airborne Contaminants Material Type Value Antimony oxide (CAS 1309-64-4) 0.5 mg/m3 logical limit values No biological exposure limits noted for the ingredient(s). propriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain concentrations of dust particulates below teorouscure limits. If exposure limits have not been established, maintain concentration must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposure below the recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product. vidual protection Wear eye/face protective equipment Eye/face protection Wear eye/face protective equipment Hand protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. We protective gloves. Respiratory protection Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical respirator with organic vapor cartridge, f		-	
MaterialTypeValueAntimony oxide (CAS 1309-64-4)PEL0.5 mg/m3logical limit valuesNo biological exposure limits noted for the ingredient(s).propriate engineering controlsGood general ventilation should be used. Ventilation rates should be matched to conditions. If appicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain oncentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposure below the recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product.ividual protection Hand protection Hand protectionWear appropriate chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter.Skin protection Hand protectionWear appropriate chemical resistant gloves.OtherWear appropriate chemical resistant clothing. Use of an impervious apron is recommended. We protective gloves.Respiratory protectionUse a NIOSH/MSHA approved respirator with organic vapor cartridge, full facepiece, dust and mist filter.Thermal hazards neral hygiene considerationsObserve any medical surveillance requirements. Do not get this material in contact with skin. Do not get this material on clothing, keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and contact with skin. Do not get this material on clothing, weap eaven gradie auting a		TWA	0.5 mg/m3
Antimory oxide (CAS PEL 0.5 mg/m3 Jage-64-4) No biological exposure limits noted for the ingredient(s). propriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposure below the recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product. ividual protection Wear eye/face protection. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter. Skin protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant gloves. Other Use a NIOSH/MSHA approved respirator with organic vapor cartridge, full facepiece, dust and mist filter. Thermal hazards Wear appropriate thermal protective clothing, when necessary. Observe any medical surveillance requirements. Do not get in syst. Such as material in contact with skin. Do not get this material on clothing, Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handl	US. California Code of Regula	ations, Title 8, Section 5155. Airborne C	contaminants
1309-64-4) No biological exposure limits noted for the ingredient(s). propriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worm. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposure below the recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product. ividual protection measures, such as personal protective equipment Eye/face protection Wear eye/face protection. Chemical resistant gloves. Other Other Wear appropriate chemical resistant gloves. Other Use a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical resistant vith organic vapor cartridge, full facepiece, dust and mist filter. Thermal hazards Wear appropriate thermal protective clothing, when necessary. Observe any medical surveillance requirements. Do not get this material in contact with skin. Do not get this material on clothing. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and befor eating, drinking, and/or s	Material	Туре	Value
propriate engineering controls Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposure below the recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product. ividual protection measures, such as personal protective equipment Eye/face protection Wear eye/face protection. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter. Skin protection Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant gloves. Vear appropriate chemical respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter. Thermal hazards Wear appropriate thermal protective clothing, when necessary. Observe any medical surveillance requirements. Do not get this material in contact with skin. Do not get this material on clothing. Keep away from food and drink. Always observe good personal hygiene measures, such as washing affer handling the material and befer eating, drinking		PEL	0.5 mg/m3
applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. If engineering measures are not sufficient to maintain concentrations of dust particulates below the Occupational Exposure Limit (OEL), suitable respiratory protection must be worn. If material is ground, cut, or used in any operation which may generate dusts, use appropriate local exhaust ventilation to keep exposure below the recommended exposure limits. Eye wash facilities and emergency shower must be available when handling this product. ividual protection wear eye/face protection. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter. Skin protection Wear appropriate chemical resistant gloves. Wear appropriate chemical resistant gloves. Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Wear protection Use a NIOSH/MSHA approved respirator with organic vapor cartridge, full facepiece, dust and mist filter. Thermal hazards Wear appropriate thermal protective clothing, when necessary. neral hygiene considerations Observe any medical surveillance requirements. Do not get this material in contact with skin. Do not get this material on clothing. Keep away from food and drink. Always observe	ological limit values	No biological exposure limits noted fo	or the ingredient(s).
Eye/face protectionWear eye/face protection. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter.Skin protection Hand protectionWear appropriate chemical resistant gloves.OtherWear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Wear protective gloves.Respiratory protectionUse a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter.Thermal hazardsWear appropriate thermal protective clothing, when necessary.Observe any medical surveillance requirements. Do not get in eyes. Do not get this material in contact with skin. Do not get this material on clothing. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and befor eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.		maintain airborne levels below recomestablished, maintain airborne levels sufficient to maintain concentrations of (OEL), suitable respiratory protection operation which may generate dusts, below the recommended exposure lim	mended exposure limits. If exposure limits have not been to an acceptable level. If engineering measures are not of dust particulates below the Occupational Exposure Limit must be worn. If material is ground, cut, or used in any use appropriate local exhaust ventilation to keep exposures
Hand protectionWear appropriate chemical resistant gloves.OtherWear appropriate chemical resistant clothing. Use of an impervious apron is recommended. Wear appropriate chemical respirator if there is a risk of exposure to dust/fume at levels protective gloves.Respiratory protectionUse a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter.Thermal hazardsWear appropriate thermal protective clothing, when necessary.Observe any medical surveillance requirements. Do not get in eyes. Do not get this material in contact with skin. Do not get this material on clothing. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and befor eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	-	Wear eye/face protection. Chemical r	espirator with organic vapor cartridge, full facepiece, dust
Respiratory protectionUse a NIOSH/MSHA approved respirator if there is a risk of exposure to dust/fume at levels exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter.Thermal hazardsWear appropriate thermal protective clothing, when necessary.Observe any medical surveillance requirements. Do not get in eyes. Do not get this material in contact with skin. Do not get this material on clothing. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and befor eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	-	Wear appropriate chemical resistant	gloves.
 exceeding the exposure limits. Chemical respirator with organic vapor cartridge, full facepiece, dust and mist filter. Thermal hazards Wear appropriate thermal protective clothing, when necessary. Observe any medical surveillance requirements. Do not get in eyes. Do not get this material in contact with skin. Do not get this material on clothing. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. 	Other		clothing. Use of an impervious apron is recommended. Wear
neral hygiene considerations Observe any medical surveillance requirements. Do not get in eyes. Do not get this material in contact with skin. Do not get this material on clothing. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	Respiratory protection	exceeding the exposure limits. Chem	•
contact with skin. Do not get this material on clothing. Keep away from food and drink. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.	Thermal hazards	Wear appropriate thermal protective of	clothing, when necessary.
Physical and chemical properties	eneral hygiene considerations	contact with skin. Do not get this mate observe good personal hygiene meas eating, drinking, and/or smoking. Rou	erial on clothing. Keep away from food and drink. Always sures, such as washing after handling the material and before
v 1 1	Physical and chemical pro	operties	

Appearance	Powder.
Physical state	Solid.
Form	Powder.
Color	Not available.
Odor	Not available.
Odor threshold	Not available.

рН	Not available.
Melting point/freezing point	1211 °F (655 °C)
Initial boiling point and boiling range	2597 °F (1425 °C)
Flash point	Not available.
Evaporation rate	Not available.
Flammability (solid, gas)	Not available.
Upper/lower flammability or explos	sive limits
Explosive limit - lower (%)	Not available.
Explosive limit - upper (%)	Not available.
Vapor pressure	3.67 kPa (77 °F (25 °C))
Vapor density	Not available.
Relative density	Not available.
Solubility(ies)	
Solubility (water)	Not available.
Partition coefficient (n-octanol/water)	Not available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not available.
Other information	
Explosive properties	Not explosive.
Molecular formula	O3-Sb2
Molecular weight	291.52 g/mol
Oxidizing properties	Not oxidizing.
10. Stability and reactivity	
Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
Chemical stability	Material is stable under normal conditions

•	
Chemical stability	Material is stable under normal conditions.
Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use. Hazardous polymerization does not occur.
Conditions to avoid	Contact with incompatible materials.
Incompatible materials	None known.
Hazardous decomposition products	No hazardous decomposition products are known.


11. Toxicological information

Information on likely routes of exposure

Inhalation	Harmful if inhaled.
Skin contact	Causes severe skin burns.
Eye contact	Causes severe eye burns. Causes serious eye damage.
Ingestion	Causes digestive tract burns. Harmful if swallowed. Harmful if swallowed.
Symptoms related to the physical, chemical and toxicological characteristics	Burning pain and severe corrosive skin damage. Causes serious eye damage. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Permanent eye damage including blindness could result. Dusts may irritate the respiratory tract, skin and eyes.
Information on toxicological effects	
Acute toxicity	Causes severe skin burns and eye damage. Harmful if inhaled. Harmful if swallowed. Harmful if swallowed.
Skin corrosion/irritation	Causes severe skin burns and eye damage.
Material name: Antimony Oxide, Sb2C	SDS US

Serious eye damage/eye	Causes serious eye damage.				
irritation	Causes serious eye damage.				
Respiratory or skin sensitization	Due to look of data the classification is not possible				
Respiratory sensitization Skin sensitization	Due to lack of data the classification is not possible.				
Germ cell mutagenicity	Due to lack of data the classification is not possible. Due to lack of data the classification is not possible.				
Carcinogenicity		May cause cancer. May cause cancer.			
	-	-			
IARC Monographs. Overall Evaluation of Carcinogenicity Antimony oxide (CAS 1309-64-4) 2B Possibly carcinogenic to humans.					
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)					
Not listed.					
	gy Program (NTP) Report on Carcinogens				
Antimony oxide (CAS 13			o be a Human Carcinogen.		
Reproductive toxicity		Due to lack of data the classification is not possible.			
Specific target organ toxicity - single exposure	Not classified.	Not classified.			
Specific target organ toxicity - repeated exposure	Causes damage	Causes damage to organs through prolonged or repeated exposure.			
Aspiration hazard	Not an aspiratio	n hazard.			
Chronic effects		Prolonged inhalation may be harmful. Causes damage to organs through prolonged or repeated exposure. Prolonged exposure may cause chronic effects.			
12. Ecological information					
Ecotoxicity	Toxic to aquatic	life with long lasting effects. Accumulation	n in aquatic organisms is expected.		
Product	Species Te		Test Results		
Antimony oxide (CAS 1309-6-	4-4)				
Aquatic					
Acute	5050				
Crustacea		Water flea (Daphnia magna)	361.5 - 496 mg/l, 48 hours		
Fish	LC50 F	Fathead minnow (Pimephales promelas)	> 80 mg/l, 96 hours		
* Estimates for product may b	e based on addition	onal component data not shown.			
Persistence and degradability		able on the degradability of this product.			
Bioaccumulative potential		No data available.			
Mobility in soil		No data available.			
Other adverse effects		e environmental effects (e.g. ozone deple rine disruption, global warming potential)	-		
13. Disposal considerations					
Disposal instructions	This material and its container must be disposed of as hazardous waste. Dispose of this material and its container to hazardous or special waste collection point. Incinerate the material under controlled conditions in an approved incinerator. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.				
Local disposal regulations	-	Dispose in accordance with all applicable regulations.			
Hazardous waste code		prrosive material [pH ≤2 or =>12.5, or co should be assigned in discussion betwee ny.	-		

Waste from residues / unused products	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).	
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal.	
14. Transport information		
DOT		
UN number	UN1549	
UN proper shipping name Transport hazard class(es)	Antimony compounds, inorganic, solid, n.o.s. (Antimony oxide RQ = 1000 LBS)	
Class	6.1	
Subsidiary risk	-	
Label(s)	6.1	
Packing group		
Environmental hazards		
Marine pollutant	No.	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.	
Special provisions	35, IB8, IP3, T1, TP33	
Packaging exceptions	153	
Packaging non bulk	213	
Packaging bulk	240	
IATA		
UN number	UN1549	
UN proper shipping name	Antimony compound, inorganic, solid, n.o.s. (Antimony oxide)	
Transport hazard class(es)		
Class	6.1	
Subsidiary risk	-	
Packing group		
Environmental hazards	No.	
ERG Code	6L	
Special precautions for user Other information	Read safety instructions, SDS and emergency procedures before handling.	
Passenger and cargo aircraft	Allowed with restrictions.	
Cargo aircraft only	Allowed with restrictions.	
IMDG		
UN number	UN1549	
UN proper shipping name	ANTIMONY COMPOUND, INORGANIC, SOLID, N.O.S. (Antimony oxide), MARINE POLLUTANT, Limited Quantity	
Transport hazard class(es)		
Class	6.1	
Subsidiary risk	-	
Packing group		
Environmental hazards		
Marine pollutant	Yes	
EmS	F-A, S-A	
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.	
	read safety instructions, one and emergency procedures before nationing.	



SARA 313 (TRI reporting)				
Chemical name		CAS number	% by wt.	
Antimony oxide		1309-64-4	100	
Other federal regulations				
Clean Air Act (CAA) Section	112 Hazardous Air Polluta	ants (HAPs) List		
Antimony oxide (CAS 1	309-64-4)			
Clean Air Act (CAA) Section	112(r) Accidental Release	Prevention (40 CFR	68.130)	
Not regulated.				
Clean Water Act (CWA)	Hazardous substance			
Section 112(r) (40 CFR	Priority pollutant			
68.130)	Toxic pollutant			
Safe Drinking Water Act (SDWA)	Listed.			
US state regulations	WARNING: This produ	ict contains a chemica	I known to the State of California to	cause cancer.
US. California. Candida (a))	te Chemicals List. Safer C	onsumer Products Re	gulations (Cal. Code Regs, tit. 22, 6	39502.3, subd.
Antimony oxide (C	AS 1309-64-4)			

California Proposition 65



WARNING: This product can expose you to Antimony oxide, which is known to the State of California to cause cancer. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 - CRT: Listed date/Carcinogenic substance

Antimony oxide (CAS 1309-64-4)

Listed: October 1, 1990

16. Other information, including date of preparation or last revision

Issue date	06-12-2015
Revision date	08-07-2024
Version #	11
Further information	Transportation Emergency Call Chemtrec at: US: 800.424.9300 International: 703.741.5970 Spain: 900.868.538 Switzerland: 0800.564.402 Chemtrec's toll free, mobile-enabled number in Germany – 0800 1817059 South Korea Toll-free Number – 080-880-0468
References	ACGIH EPA: AQUIRE database NLM: Hazardous Substances Data Base US. IARC Monographs on Occupational Exposures to Chemical Agents
Disclaimer	This document has been prepared using data from sources considered to be technically reliable and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws, statutes and regulations.