# MATERION

# SAFETY DATA SHEET

## 1. Identification

Product identifier Graphite

Other means of identification

 SDS number
 1JR

 Materion Code
 1JR

 CAS number
 7782-42-5

Synonyms Carbon dust - natural and artificial diamonds, graphite

# Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name Materion Electronic Materials

Address 6070 Parkland Blvd

Mayfield Heights, Ohio 44124

**United States** 

**Telephone** 1.216.383.4019

E-mail Materion-PS@materion.com

Contact person Product Stewardship Director

Emergency phone number See Section 16

# 2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2B

Specific target organ toxicity, single exposure Category 3 respiratory tract irritation

Environmental hazards Not classified.

OSHA defined hazards Combustible dust

Label elements



Signal word Warning

**Hazard statement** The material as sold in solid form is generally not considered hazardous. However, if the process

involves grinding, melting, cutting or any other process that causes a release of dust or fumes, hazardous levels of airborne particulate could be generated. May form combustible dust

concentrations in air. Causes skin irritation. Causes eye irritation. May cause respiratory irritation.

Precautionary statement

Prevention Prevent dust accumulation to minimize explosion hazard. Keep away from heat/sparks/open

flames/hot surfaces. - No smoking. Keep container tightly closed. Ground/bond container and receiving equipment. Avoid breathing dust/fume/gas/mist/vapors/spray. Wash thoroughly after handling. Use only outdoors or in a well-ventilated area. Wear protective gloves. Observe good

industrial hygiene practices.

**Response** If inhaled: Remove person to fresh air and keep comfortable for breathing. If in eyes: Rinse

cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a poison center/doctor if you feel unwell. If skin irritation occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take off contaminated clothing and wash it before reuse. In case of fire: Use appropriate media to

extinguish.

Material name: Graphite SDS US

1JR Version #: 07 Revision date: 07-18-2024 Issue date: 05-15-2015

Storage Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise classified (HNOC)

None known.

**Supplemental information** For further information, please contact the Product Stewardship Department at +1.216.383.4019.

# 3. Composition/information on ingredients

#### Substances

Chemical name	Common name and synonyms	CAS number	%
Graphite	Carbon dust - natural and artificial	7782-42-5	100
	diamonds, graphite		

#### 4. First-aid measures

**Inhalation** Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a poison

center or doctor/physician if you feel unwell.

Skin contact Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get

medical advice/attention. Wash contaminated clothing before reuse.

Eye contact Do not rub eyes. Immediately flush eyes with plenty of water for at least 15 minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation

develops and persists.

**Ingestion** Rinse mouth. Get medical attention if symptoms occur.

Most important

symptoms/effects, acute and

delayed

Irritation of eyes. Exposed individuals may experience eye tearing, redness, and discomfort. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Skin irritation. May cause redness and

pain.

Indication of immediate medical attention and special treatment

needed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Symptoms may be delayed.

**General information** If you feel unwell, seek medical advice (show the label where possible). Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

# 5. Fire-fighting measures

Suitable extinguishing media Avoid high pressure media which could cause the formation of a potentially explosible dust-air

mixture. Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2). Apply extinguishing media

carefully to avoid creating airborne dust.

Unsuitable extinguishing media

Specific hazards arising from

the chemical

Do not use water jet as an extinguisher, as this will spread the fire.

Explosion hazard: Avoid generating dust; fine dust dispersed in air in sufficient concentrations and

in the presence of an ignition source is a potential dust explosion hazard. During fire, gases

Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

hazardous to health may be formed.

Special protective equipment and precautions for firefighters

Fire fighting

equipment/instructions

Specific methods

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you can do

so without risk.

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards May form combustible dust concentrations in air.

#### Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Use only non-sparking tools. Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are released into the atmosphere in sufficient concentration. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

# Methods and materials for containment and cleaning up

Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Take precautionary measures against static discharge. Use only non-sparking tools. Avoid dispersal of dust in the air (i.e., clearing dust surfaces with compressed air). The product is immiscible with water and will spread on the water surface. Stop the flow of material, if this is without risk.

Large Spills: Wet down with water and dike for later disposal. Shovel the material into waste container. Following product recovery, flush area with water.

Small Spills: Sweep up or vacuum up spillage and collect in suitable container for disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS. The product is insoluble in water.

#### **Environmental precautions**

Avoid discharge into drains, water courses or onto the ground.

# 7. Handling and storage

#### Precautions for safe handling

Minimize dust generation and accumulation. Avoid significant deposits of material, especially on horizontal surfaces, which may become airborne and form combustible dust clouds and may contribute to secondary explosions. Routine housekeeping should be instituted to ensure that dusts do not accumulate on surfaces. Dry powders can build static electricity charges when subjected to the friction of transfer and mixing operations. Provide adequate precautions, such as electrical grounding and bonding, or inert atmospheres. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Combustible dust clouds may be created where operations produce fine material (dust). Handling and processing operations should be conducted in accordance with 'best practices' (e.g. NFPA-654). Explosion-proof general and local exhaust ventilation. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store locked up. Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials (see Section 10 of the SDS).

# 8. Exposure controls/personal protection

#### Occupational exposure limits

**Biological limit values** 

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

#### US. OSHA Table Z-3 Permissible Exposure Limits (PEL) for Mineral Dusts (29 CFR 1910.1000)

Material	Туре	Value	
Graphite (CAS 7782-42-5)	TWA	15 mppcf	
US. ACGIH Threshold Limit Values (TLV)			
Material	Туре	Value	Form
Graphite (CAS 7782-42-5)	TWA	2 mg/m3	Respirable fraction.
NIOSH. Immediately Dangerous to Life or He	ealth (IDLH) Values, as amended		
Material	Туре	Value	
Graphite (CAS 7782-42-5)	IDLH	1250 mg/m3	
US. NIOSH: Pocket Guide to Chemical Haza	rds Recommended Exposure Limits (	(REL)	
Material	Туре	Value	Form
Graphite (CAS 7782-42-5)	TWA	2.5 mg/m3	Respirable.
US. California Code of Regulations, Title 8, S	Section 5155. Airborne Contaminants		
Material	Туре	Value	Form
Graphite (CAS 7782-42-5)	PEL	2.5 mg/m3	Respirable dust.

Material name: Graphite SDS US

No biological exposure limits noted for the ingredient(s).

1JR Version #: 07 Revision date: 07-18-2024 Issue date: 05-15-2015

#### Appropriate engineering controls

Explosion-proof general and local exhaust ventilation. Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. It is recommended that all dust control equipment such as local exhaust ventilation and material transport systems involved in handling of this product contain explosion relief vents or an explosion suppression system or an oxygen-deficient environment. Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment). Use only appropriately classified electrical equipment and powered industrial trucks. Provide eyewash station and safety shower.

#### Individual protection measures, such as personal protective equipment

**Eye/face protection** Wear safety glasses with side shields (or goggles).

Skin protection

**Hand protection** Wear protective gloves.

**Other** Wear appropriate chemical resistant clothing.

Respiratory protection If engineering controls do not maintain airborne concentrations below recommended exposure

limits (where applicable) or to an acceptable level (in countries where exposure limits have not

been established), an approved respirator must be worn.

**Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations When using, do not eat, drink or smoke. Always observe good personal hygiene measures, such

as washing after handling the material and before eating, drinking, and/or smoking. Routinely

wash work clothing and protective equipment to remove contaminants.

## Physical and chemical properties

**Appearance** 

Physical state Solid.
Form Solid.
Color Black
Odor None.

Odor threshold Not applicable.

PH Not available.

Melting point/freezing point Not available.

Initial boiling point and boiling

range

8117.6 °F (4492 °C) 1013.25 hPa

Flash point Not applicable.

Evaporation rate Not applicable.

Flammability (solid, gas) None known.

Upper/lower flammability or explosive limits

Explosive limit - lower (%) Not applicable.

Explosive limit - lower (%) Not applicable.

temperature

Explosive limit - upper (%) Not applicable.

Explosive limit - upper (%) Not applicable.

temperature

**Vapor pressure** 62128.05 kPa (77 °F (25 °C))

Vapor density Not applicable.

Relative density Not applicable.

Solubility(ies)

Solubility (water) Insoluble

Partition coefficient

(n-octanol/water)

Not applicable.

Auto-ignition temperature 845.6 °F (452 °C)

**Decomposition temperature** Not applicable.

Viscosity

Not available.

Other information

**Explosive properties** 

Not explosive.

Heat of combustion (NFPA

30B)

0 kJ/g

Kinematic viscosity Not applicable.

Molecular formula С

12.01 g/mol Molecular weight Oxidizing properties Not oxidizing.

10. Stability and reactivity

Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions. Possibility of hazardous

reactions

Hazardous polymerization does not occur.

Conditions to avoid Keep away from heat, sparks and open flame. Contact with incompatible materials. Minimize dust

generation and accumulation.

Incompatible materials Chlorine.

Hazardous decomposition

products

No hazardous decomposition products are known.

# 11. Toxicological information

Information on likely routes of exposure

Inhalation Not likely, due to the form of the product. Skin contact Not likely, due to the form of the product. Eye contact Not likely, due to the form of the product. Ingestion Not likely, due to the form of the product.

Symptoms related to the

physical, chemical and toxicological characteristics None known.

Information on toxicological effects

Acute toxicity Not known.

**Product Species Test Results** 

Graphite (CAS 7782-42-5)

**Acute** Oral

LD50 Rat > 10000 mg/kg

Skin corrosion/irritation Not likely, due to the form of the product. Serious eye damage/eye Not likely, due to the form of the product.

irritation

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization This product is not expected to cause skin sensitization.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

SDS US Material name: Graphite

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Not listed

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Not listed.

US. National Toxicology Program (NTP) Report on Carcinogens

Not listed.

Reproductive toxicity

This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity -

single exposure

May cause respiratory irritation.

Specific target organ toxicity -

repeated exposure

Not classified.

**Aspiration hazard** Not an aspiration hazard.

Chronic effects None known.

12. Ecological information

**Ecotoxicity**The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

Persistence and degradability No data is available on the degradability of this substance.

Bioaccumulative potential No data available.

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

**Disposal instructions**Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

**Local disposal regulations** Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

# 14. Transport information

DOT

Not regulated as dangerous goods.

IATA

Not regulated as dangerous goods.

**IMDG** 

Not regulated as dangerous goods.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

Toxic Substances Control Act (TSCA)

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

#### CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

#### SARA 304 Emergency release notification

Not regulated.

#### OSHA Specifically Regulated Substances (29 CFR 1910.1001-1053)

Yes

Not listed.

#### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous

Classified hazard

chemical

Combustible dust

categories Skin corrosion or irritation

Serious eye damage or eye irritation

Specific target organ toxicity (single or repeated exposure)

# SARA 313 (TRI reporting)

Not regulated.

# Other federal regulations

# Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

# Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

Not regulated.

(SDWA)

#### **US** state regulations

#### California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins. For more information go to www.P65Warnings.ca.gov.

# 16. Other information, including date of preparation or last revision

 Issue date
 05-15-2015

 Revision date
 07-18-2024

Version # 07

Further information Refer to:

OSHA 3371-08 2009, Hazard Communication Guidance for Combustible Dusts

NFPA 654, Standard for the Prevention of Fire and Dust Explosions from the Manufacturing,

Processing, and Handling of Combustible Particulate Solids

Transportation Emergency

Call Chemtrec at: US: 800.424.9300

International: 703.741.5970

Spain: 900.868.538 Switzerland: 0800.564.402

Chemtrec's toll free, mobile-enabled number in Germany - 0800 1817059

South Korea Toll-free Number - 080-880-0468

Disclaimer This document has been prepared using data from sources considered to be technically reliable

and the information is believed to be correct. Materion makes no warranties, expressed or implied, as to the accuracy of the information contained herein. Materion cannot anticipate all conditions under which this information and its products may be used and the actual conditions of use are beyond its control. The user is responsible to evaluate all available information when using this product for any particular use and to comply with all Federal, State, Provincial and Local laws,

statutes and regulations.

Revision information

This document has undergone significant changes and should be reviewed in its entirety.